

AS-INTERFACE ANALYZER V2,
DIAGNOSTIC UNIT WITH FUNCTIONALITY ACC.TO V2.1,
ENHANCED VERSION WITH ASISAFE EVALUATION AND
MEASUREMENT WIZARD



General technical data:

Power supply		using AS-Interface
Rated insulation voltage U_i / min	V	500
rated operational current I_e	mA	70
EMC		according to EN50081-2, EN61000-6-2
Status display / AS-Interface / LED		LED green (power): power on; LED yellow (ser active): RS232 interface in operation; LED green/red (test): test mode
Operating system		Windows 98, Windows ME, Windows 2000, Windows XP, Windows NT4
interfaces		AS-Interface, RS232 for connection to a PC, trigger input (24 V), trigger output (TTL)
system requirements		IBM compatible PC 80486 and higher
note		telegram memory for 256000 AS-Interface telegrams. Scope of delivery: AS-Interface analyser, PC software, D-Sub data cable

Ambient conditions:

Ambient temperature		
• during operating	°C	0 ... 55
• during storage	°C	-25 ... +70
degree of protection		
• device		IP20

Mechanical design:

Width	mm	150
Height	mm	30
Depth	mm	90
connection		using removable screw-type terminals to AS-i, PC/RS232 using 9-pole D-Sub connector

Certificates/approvals:

General Product Approval



Shipping Approval

other

[Confirmation](#)

[Declaration of
Conformity](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RK1904-3AB01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RK1904-3AB01

last change:

Feb 22, 2013