

PC CABLE, FOR PC/PG COMMUNICATION WITH
SIMOCODE PRO OR SIRIUS 3RW44 SOFT STARTER
OR MODULAR SAFETY SYSTEM 3RK3 VIA THE
SYSTEM INTERFACE



General technical data:

product brand name		SIRIUS
Product designation		USB PC cable
Design of the product		<kein Wert>
Protection class IP		<kein Wert>
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
• during transport	°C	-40 ... +80
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		<kein Wert>
Reference code acc. to DIN EN 61346-2		<kein Wert>

Certificates/ approvals:

General Product Approval	Test Certificates	Shipping Approval
--------------------------------	-------------------	-------------------



[Special Test
Certificate](#)

[Type Test
Certificates/Test
Report](#)



other

[PROFINET-
Certification](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF79410AA000>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3UF79410AA000/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

<http://www.automation.siemens.com/bilddb/index.aspx?attID9=3UF79410AA000&lang=en>