

CONNECTION CABLE; LENGTH 2,5M; ROUND; CONNECTION OF
BASIC UNIT TO CURRENT MEASURING MODULE,
CURRENT/VOLTAGE MEASUR. MODULE, OPERATOR PANEL
OR TO EXPANSION MODULES VIA SYSTEM INTERFACE



General technical data:	
product brand name	SIRIUS
Product designation	connecting cable
Ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C
Certificates/ approvals:	

General Product Approval	EMC	Test Certificates		Shipping Approval
	 UL	 C-TICK	spezielle Prüfbescheinigungen n	Typprüfbescheinigung/Werkszeugnis  ABS

Shipping Approval					
	 DNV	 GL	 LRS	 PRS	 RMRS

other					
Bestätigungen	PROFINET-Zertifizierung	PROFISafe-Zertifizierung		Profibus	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF79330BA000>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF79330BA000>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79330BA000>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF79330BA000&lang=en



