

Magnet coil for contactors 7.5 kW 24 V AC, 50 / 60 Hz, for motor contactors, Size S0, Screw terminal

| General technical data | |
|--|--------------|
| Product brand name | SIRIUS |
| Product designation | Magnet coil |
| Control circuit | |
| Type of voltage of the control supply voltage | AC |
| Power loss [V·A] of magnet coil at AC typical | 7.9 V·A |
| Control supply voltage | |
| • 1 at AC | |
| — at 50 Hz rated value | 24 V |
| — at 60 Hz rated value | 24 V |
| • 2 at AC | |
| — at 50 Hz rated value | 24 V |
| — at 60 Hz rated value | 24 V |
| Operating range factor control supply voltage rated value of magnet coil at AC | |
| • at 50 Hz | 0.8 ... 1.1 |
| • at 60 Hz | 0.85 ... 1.1 |
| Certificates/approvals | |

| General Product Approval | Declaration of Conformity | Shipping Approval |
|--------------------------|---------------------------|-------------------|
| | | |

other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AC21>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AC21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AC21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AC21&lang=en

last modified:

10/31/2018