

Magnet coil for contactors 7.5 kW 200 V AC, 50 / 60 Hz, 220 V, 60Hz, for motor contactors, Size S0, Screw terminal

General technical data	
Product brand name	SIRIUS
Product designation	Magnet coil

Control circuit	
Type of voltage of the control supply voltage	AC
Power loss [V·A] of magnet coil at AC typical	8.5 V·A
Control supply voltage	
• 1 at AC	
— at 50 Hz rated value	200 V
— at 60 Hz rated value	200 V
• 2 at AC	
— at 60 Hz rated value	220 V
Operating range factor control supply voltage rated value of magnet coil at AC	
• at 50 Hz	0.8 ... 1.1
• at 60 Hz	0.85 ... 1.1

Certificates/approvals		
General Product Approval	Declaration of Conformity	Shipping Approval



other

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AN61>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AN61>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AN61>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AN61&lang=en

last modified:

10/31/2018