

Magnet coil for contactors 7.5 kW 400 V AC, 50 Hz, for motor contactors, Size S0, Screw terminal

General technical data

Product brand name	SIRIUS
Product designation	Magnet coil

Control circuit

Type of voltage of the control supply voltage	AC
Power loss [V·A] of magnet coil at AC typical	7.6 V·A
Control supply voltage • 1 at AC — at 50 Hz rated value	400 V
Operating range factor control supply voltage rated value of magnet coil at AC • at 50 Hz • at 60 Hz	0.8 ... 1.1 0.85 ... 1.1

Certificates/approvals

General Product Approval	Declaration of Conformity	Shipping Approval
	 EG-Konf.	 ABS  BUREAU VERITAS  LRS  RMRS

other

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AV01>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AV01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AV01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AV01&lang=en

last modified:

10/31/2018