

Surge suppressor Diode combination (diode and Zener diode) with cable spacer 24-250 V DC short break time for mounting to coil terminal for contactor relays 3TH



General technical data

Product designation		surge suppressor
Design of the surge suppressor		with diode assemblies

Control circuit/ Control

Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC	V	24 ... 250

Certificates/ approvals

General Product Approval	Declaration of Conformity	other
 CSA	 UR	 EAC
	 EG-Konf.	Miscellaneous Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7402-3D>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3D>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3D>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3D&lang=en

last modified:

04/10/2020