



REMOTE SWITCH WITH 3 NO WITH CENTRAL ON-OFF-FUNCTION CONTACT FOR AC 230, 400V 16A CONTROL AC 230V

Similar to image

Technical data:		
Latching relay design		mechanical for central control
Type of mounting		DIN rail
Number of NC contacts		0
Number of NO contacts		3
Number of change-over switches		0
Width of opening / of contacts	mm	1.2
Stipulated clearance to live parts	mm	6
Switching current / with AC / per contact / minimum	mA	100
Switching voltage / of contacts / with AC / minimum	V	10
type of voltage		AC
Type of voltage / of control voltage_1		AC
Control voltage/ _1 / final value		
• initial value	V	184
•	V	253
• setpoint	V	230
Operating range factor control supply voltage rated value / at 50 Hz / for AC		
• initial value		0.8

• final value		1.1
<b>Control voltage / _2 / setpoint</b>	V	230
<b>Operating range factor / of control voltage_2</b>		0.8
<b>Supply voltage</b>	V	250 ... 250
<b>Breaking capacity current</b>		
• nominal value	A	16
• at cos phi 0.6	A	16
<b>Switching capacity real power / for filament lamp load</b>	W	2,000
<b>Switching capacity apparent power</b>		
• for uncorrected fluorescent lamp load	V·A	400
• for fluorescent lamp load with DUO circuit	V·A	700
• for fluorescent lamp load with parallel compensation	V·A	300
<b>Control voltage frequency / _1</b>		
• initial value	Hz	50
• final value	Hz	50
<b>Impulse voltage resistance / rated value</b>	kV	4
<b>Apparent power loss / of magnet coil / with pulse / rated value</b>	V·A	7
<b>Active power loss / at 16 A / per contact / rated value</b>	W	1.2
<b>Number of pitch units for width</b>		2.5
<b>Product function / direct operation</b>		Yes
<b>Product component / switch position indicator</b>		Yes
<b>Mounting height</b>	mm	90
<b>Mounting depth</b>	mm	70
<b>Galvanic isolation / between magnet coil and contact</b>		Yes
<b>Pulse duration / minimum</b>	ms	50
<b>Electrical endurance (operating cycles)</b>		50,000
<b>Number of terminals</b>		10
<b>Conductor cross section that can be connected</b>		
• for rigid conductor	mm <sup>2</sup>	1.5 ... 6
<b>Conductor cross section that can be connected / for flexible conductor</b>		
• with wire end processing	mm <sup>2</sup>	1 ... 6
<b>Ambient temperature / with relative humidity 95% / in accordance with DIN 50015</b>	°C	35
<b>Ambient temperature</b>	°C	-10 ... +40
<b>Protection class IP</b>		IP20, with connected conductors
<b>mounting position</b>		any

Certificates/approvals:



### Further information:

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TT4123-0/all>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT4123-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4123-0)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Aug 12, 2013