



RELAY,  
N-TYPE WITH 1 NO CONTACT FOR AC 230V 16A  
CONTROL AC 24V

Similar to image

Technical data:		
Mounting depth	mm	90
Number of NC contacts		0
Type of mounting		DIN rail
Number of change-over switches		0
Number of NO contacts		1
Number of pitch units for width		1
Type of voltage		
• of control voltage_1		AC
Switching capacity apparent power		
• for uncorrected fluorescent lamp load	V·A	400
Switching capacity real power / for filament lamp load	W	1,200
Switching capacity current / at cos phi 0.6	A	16
Operating current / rated value	A	16
Control voltage frequency		
• _1		
• initial value	Hz	50
• final value	Hz	50
Control voltage/_1		

• final value		
• initial value	V	24
•	V	24
<b>Type of voltage / of supply voltage</b>		AC
<b>Relay design</b>		partially electronic
<b>Supply voltage / maximum</b>	V	250
<b>Supply voltage / minimum</b>	V	250

#### Certificates/approvals:

General Product Approval	Declaration of Conformity	other
 CCC	 EG-Konf.	<a href="#">Environmental Confirmations</a>
 GOST	 VDE	

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TT4201-2/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TT4201-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4201-2)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

