SIEMENS


Product data sheet


AUXILIARY SWITCH, 1 NC CONTACT, 1 NO CONTACT, CONNECTION AUXILIARY CIRCUIT: SCREW TERMINAL,

General technical data:		
Product brand name		SIRIUS
product designation		auxiliary switch compact feeder
Protection class IP		IP20
Relative humidity		
during operating phase	%	10 90
Ambient temperature		
during transport	°C	-55 80
during storage	°C	-55 80
during operating	°C	-20 60
Item designation		
according to DIN EN 61346-2		К
 according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		к
Auxiliary circuit:		
Number of NC contacts		
for auxiliary contacts		1
Number of NO contacts		
for auxiliary contacts		1
Installation/mounting/dimensions:		
Width	mm	45
Height	mm	32
Depth	mm	25
Connections:		
Wire stripping length	mm	10
Design of the electrical connection		
 for auxiliary and control current circuit 		screw-type terminals
Design of screw-type connection		
for auxiliary contacts		M6
Tightening torque / for auxiliary contacts		

Type of the connectable conductor cross-section / for auxiliary contacts	
• solid	max. 2x (1 4 mm ²)
finely stranded	
with conductor end processing	2x (0.5 1.5 mm²), 2x (0.75 2.5 mm²)
Type of the connectable conductor cross-section / for AWG conductors	
for auxiliary contacts	2x (20 16), 2x (18 14), 1x 12

					_	
Verification of suitability		IEC / EN 60947-6-2				
General Product Approval Functional Safety /			/ Safety of Machinery			
(SA)	ROSTEST	other				
Shipping Approval				other		
B U R E A U VERITAS		PRS	RINA	<u>Manufacturer</u>	other	
Further information	nloadcenter (Cata					
udustry Mall (Online d	nuening system)	<i>(</i>)				
ndustry Mall (Online on the stress of the st	n/industrial-controls	s/mall				
	,	<u>s/mall</u>				





last change:

Oct 24, 2011