


AS-I ADD-ON MODULE WITH 1 FREE EXTERNAL INPUT  
AND OUTPUT



### General technical data:

<b>product brand name</b>		SIRIUS
<b>Product designation</b>		AS-i mounting module with one free input and one free output
<b>Protection class IP</b>		IP20
<b>Relative humidity</b>		
• during operating phase	%	10 ... 90
<b>Ambient temperature</b>		
• during transport	°C	-25 ... +70
• during storage	°C	-25 ... +80
• during operating	°C	-20 ... +60
<b>Reference code</b>		
• according to DIN EN 61346-2		K
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K

### Installation/ mounting/ dimensions:

<b>Width</b>	mm	45
<b>Height</b>	mm	50
<b>Depth</b>	mm	78

#### Connections/ terminals:

##### Wire stripping length

mm

7

##### Design of the electrical connection

- for auxiliary and control current circuit

screw-type terminals

##### Tightening torque / for auxiliary contacts

- with screw-type terminals

N·m

0.5 ... 0.6

#### Certificates/ approvals:

##### Verification of suitability

IEC / EN 60947-6-2

##### General Product Approval

EMC



##### Shipping Approval



##### other

[Declaration of  
Conformity](#)

[other](#)

[Environmental  
Confirmations](#)

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

##### Cax online generator



<http://www.siemens.com/cax>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RA6970-3D/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RA6970-3D](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RA6970-3D)



last change:

Mar 17, 2014