

LINK MODULE,
SPRING-LOADED ELECTRICAL AND MECHANICAL,
FOR 3RV2.21 AND 3RT2.2.,
(MULTI-UNIT PACKAGING)

General technical data:

Product brand name		SIRIUS
product designation		link module
Size of the circuit-breaker		S0
Size of the contactor		S0
Design of the product		actuating voltage contactor: AC and DC
Acceptability for application		contactor S0 - circuit breaker S0 - spring-loaded terminal

Installation/mounting/dimensions:

Type of mounting		clip-on
Width	mm	45
Height	mm	65.1
Depth	mm	103

Certificates/approvals:

General Product Approval	Test Certificates	
ROSTEST	Manufacturer	other
Shipping Approval		
 ABS	 DNV	 GL
		 LRS
		 PRS
		 RINA
Shipping Approval	other	
 RMRS	Manufacturer	other

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RA2921-2A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RA2921-2A



last change:

Oct 21, 2011