



CABLE-OPERATED SWITCH METAL ENCLOSURE,  
2X M20X1.5 1NO+2NC,  
LATCHES ACC. TO EN ISO 13850 BUTTON RESET WITH  
YELLOW COVER

### General technical data:

Product designation		cable-operated switch
Supply voltage <ul style="list-style-type: none"> <li>at 50 Hz / for AC / rated value</li> <li>maximum</li> </ul>	V	250
Number of indicator lights		1
Type of unlocking device		push-to-unlatch mechanism
Rope length / maximum	m	25
Product component / EMERGENCY STOP device		No
Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		S
Reference code / according to DIN EN 61346-2		S
Width	mm	52
Height	mm	171
Depth	mm	53.5

### Enclosure:

Mounting type		screw fixing
Material / of the enclosure		metal
Color / of top part of the enclosure		grey

**Contact:**

Number of NC contacts / for auxiliary contacts

2

Number of NO contacts / for auxiliary contacts

1

Switching function / arresting lock

Yes

**Certificates/ approvals:****General Product Approval**

EG-Konf.

**Shipping Approval**

ABS



LRS



PRS



RINA

**Ambient conditions:**

Protection class IP

IP65

Ambient temperature

- during operating

°C

-25 ... +70

**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**Cax online generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3SE7150-1BH00/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SE7150-1BH00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SE7150-1BH00)

last change:

Jan 21, 2013