

SIRIUS soft starter 200-480 V 25 A, 110-250 V AC spring-type terminals Analog output



Figure similar

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product brand name            | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Product category              | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Product designation           | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Manufacturer's article number | <div><ul style="list-style-type: none"><li>• of HMI module usable</li><li>• of HMI-Modul high-feature usable</li><li>• of communication module PROFINET standard usable</li><li>• of communication module PROFIBUS usable</li><li>• of communication module Modbus TCP usable</li><li>• of circuit breaker usable at 400 V</li><li>• of circuit breaker usable at 500 V</li><li>• of circuit breaker usable at 400 V at inside-delta circuit</li><li>• of circuit breaker usable at 500 V at inside-delta circuit</li><li>• of the gG fuse usable up to 690 V</li></ul></div> |

- [3RW5980-0HS00](#)
- [3RW5980-0HF00](#)
- [3RW5980-0CS00](#)
- [3RW5980-0CP00](#)
- [3RW5980-0CT00](#)
- [3RV2032-4EA10; Type of coordination 1, Iq = 65 kA, CLASS 10](#)
- [3RV2032-4EA10; Type of coordination 1, Iq = 15 kA, CLASS 10](#)
- [3RV2032-4VA10; Type of coordination 1, Iq = 65 kA, CLASS 10](#)
- [3RV2032-4VA10; Type of coordination 1, Iq = 15 kA, CLASS 10](#)
- [3NA3822-6; Type of coordination 1, Iq = 65 kA](#)

- of the gG fuse usable at inside-delta circuit up to 500 V
- of full range R fuse link for semiconductor protection usable up to 690 V
- of back-up R fuse link for semiconductor protection usable up to 690 V

[3NA3822-6; Type of coordination 1, I<sub>q</sub> = 65 kA](#)

[3NE1817-0; Type of coordination 2, I<sub>q</sub> = 65 kA](#)

[3NE8021-1; Type of coordination 2, I<sub>q</sub> = 65 kA](#)

#### General technical data

|                                                         |                                                                |
|---------------------------------------------------------|----------------------------------------------------------------|
| <b>Starting voltage [%]</b>                             | 30 ... 100 %                                                   |
| <b>Start-up ramp time of soft starter</b>               | 0 ... 20 s                                                     |
| <b>Product component</b>                                |                                                                |
| • is supported HMI-Standard                             | Yes                                                            |
| • is supported HMI-High Feature                         | Yes                                                            |
| <b>Product feature integrated bypass contact system</b> | Yes                                                            |
| <b>Number of controlled phases</b>                      | 3                                                              |
| <b>Trip class</b>                                       | CLASS 10A (default) / 10E / 20E; acc. to IEC 60947-4-2         |
| <b>Insulation voltage</b>                               |                                                                |
| • rated value                                           | 600 V                                                          |
| <b>Degree of pollution</b>                              | 3                                                              |
| <b>Impulse voltage rated value</b>                      | 6 kV                                                           |
| <b>Blocking voltage of the thyristor maximum</b>        | 1 600 V                                                        |
| <b>Service factor</b>                                   | 1                                                              |
| <b>Surge voltage resistance rated value</b>             | 6 kV                                                           |
| <b>maximum permissible voltage for safe isolation</b>   |                                                                |
| • between main and auxiliary circuit                    | 600 V                                                          |
| <b>Protection class IP</b>                              | IP20                                                           |
| <b>Usage category acc. to IEC 60947-4-2</b>             | AC 53a                                                         |
| <b>Shock resistance</b>                                 | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting |
| <b>Vibration resistance</b>                             | 15 mm to 6 Hz; 2g to 500 Hz                                    |
| <b>Reference code acc. to DIN EN 81346-2</b>            | Q                                                              |
| <b>Product function</b>                                 |                                                                |
| • ramp-up (soft starting)                               | Yes                                                            |
| • ramp-down (soft stop)                                 | Yes                                                            |
| • Soft Torque                                           | Yes                                                            |
| • Adjustable current limitation                         | Yes                                                            |
| • pump ramp down                                        | Yes                                                            |
| • Intrinsic device protection                           | Yes                                                            |
| • motor overload protection                             | Yes; Electronic motor overload protection                      |
| • Evaluation of thermistor motor protection             | No                                                             |
| • inside-delta circuit                                  | Yes                                                            |
| • Auto-reset                                            | Yes                                                            |
| • Manual RESET                                          | Yes                                                            |
| • remote reset                                          | Yes; By turning off the control supply voltage                 |

- communication function
- via software configurable
- firmware update
- removable terminal for control circuit
- analog output

Yes  
 Yes  
 Yes  
 Yes  
 Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI)

## Power Electronics

|                                                                                     |                                                    |
|-------------------------------------------------------------------------------------|----------------------------------------------------|
| <b>Operating current</b>                                                            |                                                    |
| • at 40 °C rated value                                                              | 25 A                                               |
| • at 50 °C rated value                                                              | 22.3 A                                             |
| • at 60 °C rated value                                                              | 19.6 A                                             |
| <b>Operating current at inside-delta circuit</b>                                    |                                                    |
| • at 40 °C rated value                                                              | 43.3 A                                             |
| • at 50 °C rated value                                                              | 39 A                                               |
| • at 60 °C rated value                                                              | 33.9 A                                             |
| <b>Operating voltage</b>                                                            |                                                    |
| • rated value                                                                       | 200 ... 480 V                                      |
| • at inside-delta circuit rated value                                               | 200 ... 480 V                                      |
| <b>Relative negative tolerance of the operating voltage</b>                         | -15 %                                              |
| <b>Relative positive tolerance of the operating voltage</b>                         | 10 %                                               |
| <b>Relative negative tolerance of the operating voltage at inside-delta circuit</b> | -15 %                                              |
| <b>Relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %                                               |
| <b>Operating power for three-phase motors</b>                                       |                                                    |
| • at 230 V at 40 °C rated value                                                     | 5.5 kW                                             |
| • at 230 V at inside-delta circuit at 40 °C rated value                             | 11 kW                                              |
| • at 400 V at 40 °C rated value                                                     | 11 kW                                              |
| • at 400 V at inside-delta circuit at 40 °C rated value                             | 18.5 kW                                            |
| <b>Operating frequency 1 rated value</b>                                            | 50 Hz                                              |
| <b>Operating frequency 2 rated value</b>                                            | 60 Hz                                              |
| <b>Relative negative tolerance of the operating frequency</b>                       | -10 %                                              |
| <b>Relative positive tolerance of the operating frequency</b>                       | 10 %                                               |
| <b>Adjustable motor current</b>                                                     |                                                    |
| • minimum                                                                           | 11.5 A                                             |
| • at inside-delta circuit minimum                                                   | 19.9 A                                             |
| <b>Minimum load [%]</b>                                                             | 15 %; Relative to smallest settable I <sub>e</sub> |
| <b>Power loss [W] for rated value of the current at AC</b>                          |                                                    |
| • at 40 °C to power-up                                                              | 20 W                                               |
| • at 50 °C to power-up                                                              | 19 W                                               |

- at 60 °C to power-up

18 W

#### Control circuit/ Control

|                                                                          |                                                                                                                                                                                |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of voltage of the control supply voltage                            | AC                                                                                                                                                                             |
| Control supply voltage at AC                                             |                                                                                                                                                                                |
| • at 50 Hz                                                               | 110 ... 250 V                                                                                                                                                                  |
| • at 60 Hz                                                               | 110 ... 250 V                                                                                                                                                                  |
| Relative negative tolerance of the control supply voltage at AC at 50 Hz | -15 %                                                                                                                                                                          |
| Relative positive tolerance of the control supply voltage at AC at 50 Hz | 10 %                                                                                                                                                                           |
| Relative negative tolerance of the control supply voltage at AC at 60 Hz | -15 %                                                                                                                                                                          |
| Relative positive tolerance of the control supply voltage at AC at 60 Hz | 10 %                                                                                                                                                                           |
| Control supply voltage frequency                                         | 50 ... 60 Hz                                                                                                                                                                   |
| Relative negative tolerance of the control supply voltage frequency      | -10 %                                                                                                                                                                          |
| Relative positive tolerance of the control supply voltage frequency      | 10 %                                                                                                                                                                           |
| Control supply current in standby mode rated value                       | 30 mA                                                                                                                                                                          |
| Holding current in the by-pass mode operating rated value                | 75 mA                                                                                                                                                                          |
| Starting current at close of by-pass contact maximum                     | 0.17 A                                                                                                                                                                         |
| Inrush current peak at connect of control supply voltage maximum         | 12.2 A                                                                                                                                                                         |
| Duration of inrush current peak at connect of control supply voltage     | 2.2 ms                                                                                                                                                                         |
| Design of the overvoltage protection                                     | Varistor                                                                                                                                                                       |
| Design of short-circuit protection for control circuit                   | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |

#### Inputs/ Outputs

|                                                 |                                                           |
|-------------------------------------------------|-----------------------------------------------------------|
| Number of digital inputs                        | 1                                                         |
| Number of digital outputs                       | 3                                                         |
| • not parameterizable                           | 2                                                         |
| Digital output version                          | 2 normally-open contacts (NO) / 1 changeover contact (CO) |
| Number of inputs for thermistor connection      | 0                                                         |
| Number of analog outputs                        | 1                                                         |
| Switching capacity current of the relay outputs |                                                           |
| • at AC-15 at 250 V rated value                 | 3 A                                                       |
| • at DC-13 at 24 V rated value                  | 1 A                                                       |

#### Installation/ mounting/ dimensions

|                   |                                                                                              |
|-------------------|----------------------------------------------------------------------------------------------|
| Mounting position | +/- 10° rotation possible and can be tilted forward or backward on vertical mounting surface |
|-------------------|----------------------------------------------------------------------------------------------|

|                                                                |                                             |
|----------------------------------------------------------------|---------------------------------------------|
| <b>Mounting type</b>                                           | screw fixing                                |
| <b>Height</b>                                                  | 275 mm                                      |
| <b>Width</b>                                                   | 170 mm                                      |
| <b>Depth</b>                                                   | 152 mm                                      |
| <b>Required spacing with side-by-side mounting</b>             |                                             |
| • forwards                                                     | 10 mm                                       |
| • Backwards                                                    | 0 mm                                        |
| • upwards                                                      | 100 mm                                      |
| • downwards                                                    | 75 mm                                       |
| • at the side                                                  | 5 mm                                        |
| <b>Installation altitude at height above sea level maximum</b> | 5 000 m; Derating as of 1000 m, see catalog |
| <b>Weight without packaging</b>                                | 2.1 kg                                      |

#### Connections/Terminals

|                                                                                           |                                                                      |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| <b>Type of electrical connection</b>                                                      |                                                                      |
| • for main current circuit                                                                | screw-type terminals                                                 |
| • for control circuit                                                                     | spring-loaded terminals                                              |
| <b>Type of connectable conductor cross-sections</b>                                       |                                                                      |
| • for main contacts                                                                       |                                                                      |
| — solid                                                                                   | 2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 10 mm <sup>2</sup> )  |
| — finely stranded with core end processing                                                | 2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6.0 mm <sup>2</sup> ) |
| <b>Type of connectable conductor cross-sections at AWG conductors for control circuit</b> |                                                                      |
| • solid                                                                                   | 2x (24 ... 16)                                                       |
| • finely stranded with core end processing                                                | 2x (24 ... 16)                                                       |
| <b>Wire length</b>                                                                        |                                                                      |
| • between soft starter and motor maximum                                                  | 800 m                                                                |
| • at the digital inputs at AC maximum                                                     | 100 m                                                                |

#### Ambient conditions

|                                              |                                                                                                                         |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Ambient temperature</b>                   |                                                                                                                         |
| • during operation                           | -25 ... +60 °C                                                                                                          |
| • during storage and transport               | -40 ... +80 °C                                                                                                          |
| <b>Environmental category</b>                |                                                                                                                         |
| • during operation acc. to IEC 60721         | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| • during storage acc. to IEC 60721           | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4                 |
| • during transport acc. to IEC 60721         | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                             |
| EMC emitted interference acc. to IEC 60947-1 | CISPR11, ambience A (industrial sector)                                                                                 |

#### Communication/ Protocol

|                                          |     |
|------------------------------------------|-----|
| <b>Communication module is supported</b> |     |
| • PROFINET standard                      | Yes |

- Modbus TCP
- PROFIBUS

Yes  
Yes

## UL/CSA ratings

### Manufacturer's article number

- of the fuse usable up to 575/600 V according to UL
- of the fuse usable at inside-delta circuit up to 575/600 V according to UL

Type: Class RK5 / K5, max. 100 A; Standard fault, I<sub>q</sub> = 5 kA

Type: Class RK5 / K5, max. 100 A

### Operating power [hp] for three-phase motors

- at 200/208 V at 50 °C rated value
- at 220/230 V at 50 °C rated value
- at 460/480 V at 50 °C rated value
- at 200/208 V at inside-delta circuit at 50 °C rated value
- at 220/230 V at inside-delta circuit at 50 °C rated value
- at 460/480 V at inside-delta circuit at 50 °C rated value

5 hp  
7.5 hp  
15 hp  
10 hp  
10 hp  
25 hp

### Contact rating of auxiliary contacts according to UL

R300-B300

### General Product Approval

### Declaration of Conformity

### other



[Confirmation](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5215-3AC14>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5215-3AC14>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5215-3AC14>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5215-3AC14&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5215-3AC14&lang=en)


### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5215-3AC14/char>

### Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5215-3AC14&objecttype=14&gridview=view1>





last modified:

07/04/2018