

SIRIUS soft starter 200-480 V 32 A, 110-250 V AC Screw terminals  
Analog output



Figure similar

|                               |   |
|-------------------------------|---|
| Product brand name            | SIRIUS  |
| Product category              | Hybrid switching devices  |
| Product designation           | Soft starter  |
| Manufacturer's article number | <div><ul style="list-style-type: none"><li>• of HMI module usable</li><li>• of HMI-Modul high-feature usable</li><li>• of communication module PROFINET standard usable</li><li>• of communication module PROFIBUS usable</li><li>• of communication module Modbus TCP usable</li><li>• of circuit breaker usable at 400 V</li><li>• of circuit breaker usable at 500 V</li><li>• of circuit breaker usable at 400 V at inside-delta circuit</li><li>• of circuit breaker usable at 500 V at inside-delta circuit</li><li>• of the gG fuse usable up to 690 V</li></ul></div> |

- [3RW5980-0HS00](#)
- [3RW5980-0HF00](#)
- [3RW5980-0CS00](#)
- [3RW5980-0CP00](#)
- [3RW5980-0CT00](#)
- [3RV2032-4VA10; Type of coordination 1, Iq = 65 kA, CLASS 10](#)
- [3RV2032-4VA10; Type of coordination 1, Iq = 10 kA, CLASS 10](#)
- [3RV2032-4JA10; Type of coordination 1, Iq = 65 kA, CLASS 10](#)
- [3RV2032-4JA10; Type of coordination 1, Iq = 10 kA, CLASS 10](#)
- [3NA3824-6; Type of coordination 1, Iq = 65 kA](#)

- of the gG fuse usable at inside-delta circuit up to 500 V
- of full range R fuse link for semiconductor protection usable up to 690 V
- of back-up R fuse link for semiconductor protection usable up to 690 V

[3NA3824-6; Type of coordination 1, I<sub>q</sub> = 65 kA](#)

[3NE1818-0; Type of coordination 2, I<sub>q</sub> = 65 kA](#)

[3NE8022-1; Type of coordination 2, I<sub>q</sub> = 65 kA](#)

#### General technical data

|   |   |
|---|---|
| <b>Starting voltage [%]</b>                             | 30 ... 100 %  |
| <b>Start-up ramp time of soft starter</b>               | 0 ... 20 s  |
| <b>Product component</b>                                |   |
| • is supported HMI-Standard                             | Yes   |
| • is supported HMI-High Feature                         | Yes   |
| <b>Product feature integrated bypass contact system</b> | Yes   |
| <b>Number of controlled phases</b>                      | 3   |
| <b>Trip class</b>                                       | CLASS 10A (default) / 10E / 20E; acc. to IEC 60947-4-2                          |
| <b>Insulation voltage</b>                               |   |
| • rated value   | 600 V   |
| <b>Degree of pollution</b>                              | 3   |
| <b>Impulse voltage rated value</b>                      | 6 kV  |
| <b>Blocking voltage of the thyristor maximum</b>        | 1 600 V   |
| <b>Service factor</b>                                   | 1   |
| <b>Surge voltage resistance rated value</b>             | 6 kV  |
| <b>maximum permissible voltage for safe isolation</b>   |   |
| • between main and auxiliary circuit                    | 600 V   |
| <b>Protection class IP</b>                              | IP00; IP20 with additional terminal covers for vertical touching from the front |
| <b>Usage category acc. to IEC 60947-4-2</b>             | AC 53a  |
| <b>Shock resistance</b>                                 | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting                  |
| <b>Vibration resistance</b>                             | 15 mm to 6 Hz; 2g to 500 Hz   |
| <b>Reference code acc. to DIN EN 81346-2</b>            | Q   |
| <b>Product function</b>                                 |   |
| • ramp-up (soft starting)                               | Yes   |
| • ramp-down (soft stop)                                 | Yes   |
| • Soft Torque   | Yes   |
| • Adjustable current limitation                         | Yes   |
| • pump ramp down  | Yes   |
| • Intrinsic device protection                           | Yes   |
| • motor overload protection                             | Yes; Electronic motor overload protection                                       |
| • Evaluation of thermistor motor protection             | No  |
| • inside-delta circuit                                  | Yes   |
| • Auto-reset  | Yes   |
| • Manual RESET  | Yes   |

- remote reset
- communication function
- via software configurable
- firmware update
- removable terminal for control circuit
- analog output

Yes; By turning off the control supply voltage

Yes

Yes

Yes

Yes

Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI)

## Power Electronics

|   |  |
|---|--|
| <b>Operating current</b>  |  |
| • at 40 °C rated value  | 32 A   |
| • at 50 °C rated value  | 28.4 A   |
| • at 60 °C rated value  | 26 A   |
| <b>Operating current at inside-delta circuit</b>                                    |  |
| • at 40 °C rated value  | 55.4 A   |
| • at 50 °C rated value  | 49 A   |
| • at 60 °C rated value  | 45 A   |
| <b>Operating voltage</b>  |  |
| • rated value   | 200 ... 480 V                                      |
| • at inside-delta circuit rated value   | 200 ... 480 V                                      |
| <b>Relative negative tolerance of the operating voltage</b>                         | -15 %  |
| <b>Relative positive tolerance of the operating voltage</b>                         | 10 %   |
| <b>Relative negative tolerance of the operating voltage at inside-delta circuit</b> | -15 %  |
| <b>Relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %   |
| <b>Operating power for three-phase motors</b>                                       |  |
| • at 230 V at 40 °C rated value   | 7.5 kW   |
| • at 230 V at inside-delta circuit at 40 °C rated value                             | 15 kW  |
| • at 400 V at 40 °C rated value   | 15 kW  |
| • at 400 V at inside-delta circuit at 40 °C rated value                             | 22 kW  |
| <b>Operating frequency 1 rated value</b>  | 50 Hz  |
| <b>Operating frequency 2 rated value</b>  | 60 Hz  |
| <b>Relative negative tolerance of the operating frequency</b>                       | -10 %  |
| <b>Relative positive tolerance of the operating frequency</b>                       | 10 %   |
| <b>Adjustable motor current</b>   |  |
| • minimum   | 14 A   |
| • at inside-delta circuit minimum   | 24.2 A   |
| <b>Minimum load [%]</b>   | 15 %; Relative to smallest settable I <sub>e</sub> |
| <b>Power loss [W] for rated value of the current at AC</b>                          |  |
| • at 40 °C to power-up  | 22 W   |

- at 50 °C to power-up
- at 60 °C to power-up

21 W

20 W

#### Control circuit/ Control

|  |  |
|--|--|
| Type of voltage of the control supply voltage                            | AC   |
| Control supply voltage at AC   |  |
| • at 50 Hz   | 110 ... 250 V  |
| • at 60 Hz   | 110 ... 250 V  |
| Relative negative tolerance of the control supply voltage at AC at 50 Hz | -15 %  |
| Relative positive tolerance of the control supply voltage at AC at 50 Hz | 10 %   |
| Relative negative tolerance of the control supply voltage at AC at 60 Hz | -15 %  |
| Relative positive tolerance of the control supply voltage at AC at 60 Hz | 10 %   |
| Control supply voltage frequency   | 50 ... 60 Hz   |
| Relative negative tolerance of the control supply voltage frequency      | -10 %  |
| Relative positive tolerance of the control supply voltage frequency      | 10 %   |
| Control supply current in standby mode rated value                       | 30 mA  |
| Holding current in the by-pass mode operating rated value                | 75 mA  |
| Starting current at close of by-pass contact maximum                     | 0.17 A   |
| Inrush current peak at connect of control supply voltage maximum         | 12.2 A   |
| Duration of inrush current peak at connect of control supply voltage     | 2.2 ms   |
| Design of the overvoltage protection                                     | Varistor   |
| Design of short-circuit protection for control circuit                   | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |

#### Inputs/ Outputs

|   |   |
|---|---|
| Number of digital inputs                        | 1   |
| Number of digital outputs                       | 3   |
| • not parameterizable                           | 2   |
| Digital output version                          | 2 normally-open contacts (NO) / 1 changeover contact (CO) |
| Number of inputs for thermistor connection      | 0   |
| Number of analog outputs                        | 1   |
| Switching capacity current of the relay outputs |   |
| • at AC-15 at 250 V rated value                 | 3 A   |
| • at DC-13 at 24 V rated value                  | 1 A   |

#### Installation/ mounting/ dimensions

|  |  |
|--|--|
| <b>Mounting position</b>                                       | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| <b>Mounting type</b>   | screw fixing   |
| <b>Height</b>  | 275 mm   |
| <b>Width</b>   | 170 mm   |
| <b>Depth</b>   | 152 mm   |
| <b>Required spacing with side-by-side mounting</b>             |  |
| • forwards   | 10 mm  |
| • Backwards  | 0 mm   |
| • upwards  | 100 mm   |
| • downwards  | 75 mm  |
| • at the side  | 5 mm   |
| <b>Installation altitude at height above sea level maximum</b> | 5 000 m; Derating as of 1000 m, see catalog  |
| <b>Weight without packaging</b>                                | 2.3 kg   |

#### Connections/Terminals

|   |  |
|---|--|
| <b>Type of electrical connection</b>  |  |
| • for main current circuit  | screw-type terminals                       |
| • for control circuit   | screw-type terminals                       |
| <b>Type of connectable conductor cross-sections</b>                                       |  |
| • for main contacts   |  |
| — solid   | 2x (1.0 ... 2.5 mm²), 2x (2.5 ... 10 mm²)  |
| — finely stranded with core end processing  | 2x (1.0 ... 2.5 mm²), 2x (2.5 ... 6.0 mm²) |
| <b>Type of connectable conductor cross-sections at AWG conductors for control circuit</b> |  |
| • solid   | 1x (20 ... 12), 2x (20 ... 14)             |
| <b>Wire length</b>  |  |
| • between soft starter and motor maximum  | 800 m                                      |
| • at the digital inputs at AC maximum   | 100 m                                      |

#### Ambient conditions

|  |   |
|--|---|
| <b>Ambient temperature</b>                   |   |
| • during operation                           | -25 ... +60 °C  |
| • during storage and transport               | -40 ... +80 °C  |
| <b>Environmental category</b>                |   |
| • during operation acc. to IEC 60721         | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| • during storage acc. to IEC 60721           | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4                 |
| • during transport acc. to IEC 60721         | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)   |
| EMC emitted interference acc. to IEC 60947-1 | CISPR11, ambience A (industrial sector)   |

#### Communication/ Protocol

|  |  |
|--|--|
| <b>Communication module is supported</b> |  |
|--|--|

- PROFINET standard
- Modbus TCP
- PROFIBUS

Yes  
Yes  
Yes

## UL/CSA ratings

### Manufacturer's article number

- of the fuse usable up to 575/600 V according to UL
- of the fuse usable at inside-delta circuit up to 575/600 V according to UL

Type: Class RK5 / K5, max. 125 A; Standard fault, I<sub>q</sub> = 5 kA

Type: Class RK5 / K5, max. 125 A

### Operating power [hp] for three-phase motors

- at 200/208 V at 50 °C rated value
- at 220/230 V at 50 °C rated value
- at 460/480 V at 50 °C rated value
- at 200/208 V at inside-delta circuit at 50 °C rated value
- at 220/230 V at inside-delta circuit at 50 °C rated value
- at 460/480 V at inside-delta circuit at 50 °C rated value

7.5 hp

10 hp

20 hp

15 hp

15 hp

30 hp

### Contact rating of auxiliary contacts according to UL

R300-B300

### General Product Approval

### Declaration of Conformity

### other



[Confirmation](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5216-1AC14>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5216-1AC14>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5216-1AC14>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5216-1AC14&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5216-1AC14&lang=en)

### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5216-1AC14/char>

### Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5216-1AC14&objecttype=14&gridview=view1>



