

Separation amplifier Loop power isolator, 1-channel input: 4-20 mA
output: 4-20 mA Width 6.2 mm Spring-type terminal (push-in)



Product brand name	SIRIUS
Product category	Signal converter
Product designation	Single-range converters
Design of the product	passive
Product type designation	3RS70

General technical data	
Display version LED	No
Number of channels	1
Insulation voltage • for overvoltage category III according to IEC 60664 — with degree of pollution 3 rated value	50 V
Voltage drop at operating resource	4.1 V
Surge voltage resistance rated value	1 500 V
Protection class IP	IP20
Shock resistance • acc. to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
Reference code acc. to DIN EN 81346-2	T
Reference code acc. to DIN EN 61346-2	K

Precision	
Relative metering precision	0.1 %
Temperature drift per °C	0.015 %/°C
Voltage ripple maximum	5 mV
Settling time for 1 % deviation	6 ms
Inputs/ Outputs	
Input voltage	30 V
Property of the output Short-circuit proof	No
Type of signal at input	4 ... 20 mA
Type of signal at output	4 ... 20 mA
Input impedance of current input maximum	100 Ω
Outputs	
Load	
• at the current output maximum	1 000 Ω
Influence of the load on measuring accuracy	0.06 %/100 Ω
Electromagnetic compatibility	
EMC emitted interference	
• acc. to IEC 60947-1	Environment B
EMI immunity	
• acc. to IEC 60947-1	corresponds to degree of severity 3
Conducted interference	
• due to burst acc. to IEC 61000-4-4	1 kV 5/50 ns
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Electrostatic discharge acc. to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge
Galvanic isolation	
Design of the electrical isolation	2 paths
Galvanic isolation	
• between entrance and outlet	Yes
• between the outputs	No
• between the inputs	No
• between the voltage supply and other circuits	No
Connections/Terminals	
Type of electrical connection	spring-loaded terminals
Type of connectable conductor cross-sections	
• solid	1x (0.25 ... 2.5 mm²)
• finely stranded with core end processing	1x (0.25 ... 1.5 mm²)
• finely stranded without core end processing	1x (0.25 ... 2.5 mm²)
• at AWG conductors solid	1 x (20 ... 14)

• at AWG conductors stranded	1x (20 ... 14)
Connectable conductor cross-section	
• solid	0.25 ... 2.5 mm ²
• finely stranded with core end processing	0.25 ... 1.5 mm ²
• finely stranded without core end processing	0.25 ... 2.5 mm ²
AWG number as coded connectable conductor cross section	
• solid	20 ... 14
• stranded	20 ... 14

Installation/ mounting/ dimensions

Mounting position	any
Mounting type	snap-on mounting
Height	93 mm
Width	6.2 mm
Depth	71 mm
Required spacing	
• with side-by-side mounting	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

Ambient conditions

Installation altitude at height above sea level	
• maximum	2 000 m
Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C

Relative humidity

- during operation

10 ... 95 %

Certificates/approvals

General Product Approval



EG-Konf.

Test Certificates

[Type Test Certificates/Test Report](#)

Marine / Shipping



other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RS7020-2ET00>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RS7020-2ET00>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RS7020-2ET00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RS7020-2ET00&lang=en





last modified:

02/15/2019