

Starter kit 18 2x 9 sensor bars incl. 18 and 1x data manager



Model	
Product brand name	SETRON
Product designation	7KT PAC1200
Design of the product	2x9 with system, 40 A
Product type designation	Starter kit
General technical data	
Measuring precision	Total accuracy +/-2% (of full-scale value / class 2)
Measured variable current / rated value	63 A
Line frequency / rated value	Yes
• 50 Hz	
Measurable line frequency	50 +/- 5%
• Full-scale value	
Electricity	
Current / at output / rated value	5 A
Suitability	
Suitability for use	
• reactive power meter	Yes
• revolution counter	No

• Frequency meter	Yes
• pulse counter	No
• voltmeter	No
• wattmeter	Yes
Protocol / is supported	Modbus TCP

Measuring inputs

Measurable supply voltage	
• between (PE)N and L / at AC / maximum rated value	230 V
• between the outer conductors / at AC / maximum rated value	400 V
Number of width units	4
Net weight	544 g

Certificates

Waste electronic equipment must not be disposed as unsorted municipal waste, e.g. household waste. For disposing the waste electronic equipment it is necessary to observe the current local national/international regulations.



Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KT1222>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KT1222>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KT1222

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



