

ENABLING MODULE FOR OPERATOR PANEL
3RA69350A

General technical data:

product brand name		SIRIUS
Product designation		dongle
Protection class IP		IP20
Relative humidity during operation	%	10 ... 90
Ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operation	°C	-20 ... +60
Equipment marking acc. to DIN EN 61346-2		T
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		T

Installation/ mounting/ dimensions:

Width	mm	18
Height	mm	16
Depth	mm	10

Certificates/ approvals:

Certificate of suitability	IEC / EN 60947-6-2
----------------------------	--------------------

General Product Approval	EMC	Declaration of Conformity	Shipping Approval
--------------------------	-----	---------------------------	-------------------



Shipping Approval	other
-------------------	-------



[Umweltbestätigung](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6936-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6936-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6936-0A&lang=en

last modified:

12/09/2016