

SETRON, measuring device, 7KM PAC4200 and strd mnt. rail adapt. LCD, L-L: 500 V, L-N: 289 V, 5 A, 3- phase, Modbus TCP, optional Modbus RTU / PROFINET / PROFIBUS / DI/DO, apparent/ Active/reactive energy / cos phi, harmonics: 3. - 31., THD, class 0.2 acc. to IEC61557-12 or cl. 0.2S acc. to IEC62053-22, ext-low volt. pwr sup. unit DC, screw terminals



Model	
Product brand name	SETRON
Product designation	7KM PAC4200 and mounting rail adapter
Design of the product	compact
Product type designation	Measuring instrument
Type of measured value detection	complete
Design of the power supply	Extra-low voltage power supply unit
General technical data	
Cutout width	92 mm
Cutout height	92 mm
Size of Power Monitoring Device / company-specific	size 96
Operating mode for measured value detection	
• automatic line frequency detection	Yes
• set at 50 Hz	No
• set to 60 Hz	No
Pulse duration	
• initial value	30 ms
• Full-scale value	500 ms

Voltage curve	Sinusoidal or distorted
Measurable line frequency / initial value	45 Hz
Measurable line frequency / Full-scale value	65 Hz
Measuring procedure / for voltage measurement	TRMS
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	P

#### Supply voltage

Type of voltage / of the supply voltage	DC
Measuring category / for supply voltage	CATIII
Consumed active power <ul style="list-style-type: none"> <li>• with expansion module / typical</li> <li>• without expansion module / typical</li> </ul>	11 W 5.5 W
Relative symmetrical tolerance / of the supply voltage	10 %

#### Protection class

Protection class IP <ul style="list-style-type: none"> <li>• on the front</li> <li>• Rear side</li> </ul>	IP65 IP20
Operating resource protection class / when installed	II

#### Electricity

Measurable current / 2 / at AC / Rated value	5 A
--	-----

#### Suitability

Suitability for operation	Installation in stationary control panels in closed rooms
Adjustable time period / minimum	10 ms

#### Product function

Product function <ul style="list-style-type: none"> <li>• Illuminance of display backlighting adjustable</li> <li>• Time-controlled reduction of the illuminance of display backlighting possible</li> <li>• reactive power measurement</li> <li>• frequency measurement</li> <li>• pulse measurement</li> <li>• Display contrast adjustable</li> <li>• voltage measurement</li> <li>• Current measurement</li> <li>• active power measurement</li> </ul>	Yes Yes Yes Yes Yes Yes Yes Yes Yes
---	---

#### Display and operation

Design of the display	LCD
Number of keys	4
Color / of the background of the display	white

National language / on the display screen / is supported	ger, en, fr, spa, ita, por, tur, rus, chi, pol
Product function / Display can be inverted (positive <=> negative mode)	Yes
Horizontal image resolution	128
Vertical screen resolution	96
Refresh time / on display	
• minimum	0.33 s
• maximum	3 s

### Communication

Number of active connections / at the Ethernet interface	3
Number of logical ports / at the Ethernet interface / is supported	2
Number of interfaces / acc. to Fast Ethernet	1
Design of cable / connectable / Twisted pair	Yes
Product function / at the Ethernet interface	
• auto-MDI(X)	Yes
• Autonegotiation	Yes
• serial gateway	Yes
Protocol	
• at the Ethernet interface / is supported	MODBUS TCP
• is supported	Modbus TCP
Transfer rate	
• minimum	10 000 kbit/s
• maximum	100 000 kbit/s
• 1 / for Ethernet	10 Mbit/s
• 2 / for Ethernet	100 Mbit/s

### Fault limits

Reference condition / for metering accuracy	Acc. to IEC61557-12
Formula for relative total measurement inaccuracy	
• for measured variable reactive energy	Class 2 according to IEC61557-12 and/or IEC62053-23
• for measured variable output	+/- 0,5 %
• for measured variable output factor	+/- 2 %
• for measured variable voltage	+/- 0,2 %
• for measured variable current	+/- 0,2 %
• for measured variable THD	+/- 2 %
• for measured variable active energy	Class 0.2 according to IEC61557-12 and/or class 0.2S according to IEC62053-22

### Inputs Outputs

Input voltage / at digital input	
• initial value for signal<1>-recognition	19 V

<ul style="list-style-type: none"> <li>• at DC / rated value</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	30 V
<ul style="list-style-type: none"> <li>• Full-scale value for signal&lt;0&gt; recognition</li> </ul>	10 V
Number of digital outputs	2
Number of digital inputs	2
Digital output version	switching or pulse output function
Type of switching output	solid state
Type of electrical connection	
<ul style="list-style-type: none"> <li>• at the digital inputs</li> </ul>	screw-type terminals
<ul style="list-style-type: none"> <li>• at the digital outputs</li> </ul>	screw-type terminals
Input current / at digital input	
<ul style="list-style-type: none"> <li>• for signal &lt;1&gt;</li> </ul>	4 mA
Output current	
<ul style="list-style-type: none"> <li>• at digital output / with signal &lt;0&gt; / maximum</li> </ul>	0.2 mA
<ul style="list-style-type: none"> <li>• at digital output / for signal &lt;1&gt; / minimum</li> </ul>	10 mA
<ul style="list-style-type: none"> <li>• at digital output / for signal &lt;1&gt; / maximum</li> </ul>	27 mA
<ul style="list-style-type: none"> <li>• at the digital outputs / at DC / limited to 100 ms / maximum</li> </ul>	300 mA
<ul style="list-style-type: none"> <li>• at the digital outputs / at DC / maximum</li> </ul>	100 mA
Output delay / at digital output	
<ul style="list-style-type: none"> <li>• for signal &lt;0&gt; to &lt;1&gt; / maximum</li> </ul>	5 ms
<ul style="list-style-type: none"> <li>• for signal &lt;1&gt; to &lt;0&gt; / maximum</li> </ul>	5 ms
Operating conditions for digital inputs / external voltage supply	Yes
Operating voltage / as output voltage / at DC / maximum permissible	30 V
Property of the output / Short-circuit proof	Yes
Input delay time / at digital input	
<ul style="list-style-type: none"> <li>• for signal &lt;0&gt; to &lt;1&gt; / maximum</li> </ul>	5 ms
<ul style="list-style-type: none"> <li>• for signal &lt;1&gt; to &lt;0&gt; / maximum</li> </ul>	5 ms
Internal resistance / at the digital outputs	55 Ω
Measuring category / for digital signals	CAT I
Switching frequency / at digital output / maximum	20 Hz
Transfer rate	
<ul style="list-style-type: none"> <li>• 1 / for fast Ethernet</li> </ul>	100 Mbit/s

### Measuring inputs

Outer conductors and neutral conductors internal resistance / for voltage measurement	1.05 MΩ
Measurable supply voltage	
<ul style="list-style-type: none"> <li>• between (PE)N and L / at AC / minimum</li> </ul>	11.5 V
<ul style="list-style-type: none"> <li>• between (PE)N and L / at AC / maximum</li> </ul>	346 V
<ul style="list-style-type: none"> <li>• between (PE)N and L / at AC / maximum rated value</li> </ul>	289 V

• between the outer conductors / at AC / minimum	20 V
• between the outer conductors / at AC / maximum	600 V
• between the outer conductors / at AC / maximum rated value	500 V
Voltage measuring range extension / with external voltage transformers	Yes
Current measuring range extension / with external current transformers	Yes
Measuring category / for voltage measurement	CATIII
Supply voltage / between the outer conductors / at AC / maximum permissible	600 V
Continuous current / at AC / maximum permissible	10 A
Measuring category / for current measurement	CATIII
Zero-point suppression / for current measurement	0 ... 10 %
Relative measurable current / at AC	
• minimum	1 %
• maximum	120 %
Apparent power consumption / for current measurement	
• with measuring range 1 A / per phase	4 mVA
• with measuring range 5 A / per phase	0.115 V·A
Measuring procedure / for current measurement	TRMS
Measurable current / 1 / at AC / Rated value	1 A

## Connections

### Type of connectable conductor cross-sections

• at the digital inputs / at AWG conductors / solid	1x 24 ... 12
• at the digital inputs / solid	1x (0.2 ... 2.5 mm²), 2x (0.2 ... 1.0 mm²)
• at the digital inputs / finely stranded / with core end processing	1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)
• at the digital outputs / at AWG conductors / solid	1x 24 ... 12
• at the digital outputs / solid	1x (0.2 ... 2.5 mm²), 2x (0.2 ... 1.0 mm²)
• at the digital outputs / finely stranded / with core end processing	1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)
• at the inputs for supply voltage / at AWG conductors / solid	2x 20 to 14
• at the inputs for supply voltage / solid	1x (0.5 ... 4 mm²), 2x (0.5 ... 2.5 mm²)
• at the inputs for supply voltage / finely stranded / with core end processing	1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.5 mm²)
• at the measurement inputs for voltage / at AWG conductors / solid	2x 20 to 14
• at the measurement inputs for voltage / solid	1x (0.5 ... 4 mm²), 2x (0.5 ... 2.5 mm²)

<ul style="list-style-type: none"> <li>• at the measurement inputs for voltage / finely stranded / with core end processing</li> <li>• at the measurement inputs for current / at AWG conductors / solid</li> <li>• at the measurement inputs for current / solid</li> <li>• at the measurement inputs for current / finely stranded / with core end processing</li> </ul>	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.5 mm <sup>2</sup> )  2x 20 to 14  1x (0.5 ... 4 mm <sup>2</sup> ), 2x (0.5 ... 2.5 mm <sup>2</sup> ) 1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.5 mm <sup>2</sup> )
<b>Type of electrical connection</b> <ul style="list-style-type: none"> <li>• at the inputs for supply voltage</li> <li>• at the measurement inputs for voltage</li> <li>• at the measurement inputs for current</li> <li>• of the fast Ethernet interface</li> </ul>	screw-type terminals screw-type terminals screw-type terminals RJ45 (8P8C)

Mechanical Design	
Height	96 mm
Height / of the display	54 mm
Width	96 mm
Width <ul style="list-style-type: none"> <li>• of the display</li> </ul>	72 mm
Depth	82 mm
Mounting position	vertical
Installation depth	77 mm
Installation depth / with expansion module / maximum	99 mm
Mounting type / panel mounting	Yes
Material thickness / of the control panel <ul style="list-style-type: none"> <li>• maximum</li> </ul>	4 mm
Net weight	905 g

Environmental conditions	
Degree of pollution	2
Installation altitude / at height above sea level / maximum	2 000 m
<b>Standard</b> <ul style="list-style-type: none"> <li>• for EMC for industrial sector</li> <li>• for EMC against unloading</li> <li>• for EMC against high frequency fields</li> <li>• for EMC against conducted LF disturbance variables (industry)</li> <li>• for EMC against conducted disturbance variables via HF fields</li> <li>• for EMC against magnetic fields with power engineering frequencies</li> <li>• for EMC against quick, transient electrical disturbances</li> </ul>	IEC 61000-6-2 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-6-4  IEC 61000-4-6  IEC 61000-4-8  IEC 61000-4-4

<ul style="list-style-type: none"> <li>• for EMC against voltage drops and interruptions</li> <li>• for EMC against surge voltages</li> <li>• for free fall</li> <li>• for pulse emitter</li> <li>• for cyclic, environmental damp heat check</li> <li>• for environmental coldness check</li> <li>• for environmental dry heat check</li> </ul>	<p>IEC 61000-4-11</p> <p>IEC 61000-4-5</p> <p>IEC 60068-2-32</p> <p>according to IEC62053-31</p> <p>IEC 60068-2-30</p> <p>IEC 60068-2-1</p> <p>IEC 60068-2-2</p>
<p>Relative humidity / at 25 °C / without condensation / during operation</p> <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	<p>5 %</p> <p>95 %</p>
<p>Ambient temperature</p> <ul style="list-style-type: none"> <li>• during operation / minimum</li> <li>• during operation / maximum</li> <li>• during storage / minimum</li> <li>• during storage / maximum</li> </ul>	<p>-10 °C</p> <p>55 °C</p> <p>-25 °C</p> <p>70 °C</p>
<b>Certificates</b>	
<p>Certificate of suitability</p> <ul style="list-style-type: none"> <li>• as EC declaration of conformity</li> <li>• as approval for Canada</li> <li>• as approval for USA</li> <li>• Approval Australia</li> <li>• Approval Russia</li> </ul>	<p>IEC 61010-1: 2001 (2nd Ed.) with Corr. 1, EN 61010-1: 2001 (2nd Ed.) and DIN EN 61010-1:2002 with "Berichtigung 1"</p> <p>UL 61010-1, 2nd Ed. CAN/CSA-C22.2 NO. 61010-1-04</p> <p>UL 61010-1, 2nd Ed. CAN/CSA-C22.2 NO. 61010-1-04</p> <p>Yes</p> <p>Yes</p>
<p>Reference code</p> <ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> </ul>	<p>P</p>

Waste electronic equipment must not be disposed as unsorted municipal waste, e.g. household waste. For disposing the waste electronic equipment it is necessary to observe the current local national/international regulations.



other

[Confirmation](#)

[Manufacturer Declaration](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM4211-1BB00-3AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7KM4211-1BB00-3AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KM4211-1BB00-3AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM4211-1BB00-3AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



