SIEMENS

Product data sheet



CIRCUIT BREAKER 230V 10KA, 1+N-POLE, C, 25A, D=70MM

Similar to image

Technical data:		
Overvoltage class		3
type of voltage		AC/DC
Tripping characteristic class		С
Degree of pollution		3
Mounting depth	mm	70
Energy limiting class		3
Number of poles		2
Number of pitch units for width		2
Product function / n-switching		Yes
Supply voltage frequency / rated value	Hz	50
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	20
Breaking capacity current / acc. to EN 60898 / rated value	kA	10
Supply voltage / for AC / rated value	V	230
Current / for AC / rated value	А	25
Protection class IP		IP20, with connected conductors
Product extension / can be installed / supplementary device		Yes
power loss		-

	-
	-
	-
	-
-	-
-	-
	-
	-
	-
А	25
А	23.75
А	23.25
А	22.5
А	21.75
А	21.25
	150m/s ² at 11ms half-sine
	A A A

Certificates/approvals:

General Product Approval

Image: circle of the state of the

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


 $\underline{ http://support.automation.siemens.com/WW/view/en/5SY4525-7/all} \\$


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY4525-7

CAx-Online-Generator

http://www.siemens.com/cax







last change:

Nov 3, 2011