## **SIEMENS**

Product data sheet 5SY8302-7

Similar to image

CIRCUIT BREAKER 400V 25KA, 3POLE, C, 2A, D=70MM

Technical data:		
Overvoltage class		3
type of voltage		AC/DC
Tripping characteristic class		С
Degree of pollution		3
Mounting depth	mm	70
Energy limiting class		3
Number of poles		3
Number of pitch units for width		3
Product function / n-switching		No
Supply voltage frequency / rated value	Hz	50
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	70
Supply voltage / for AC / rated value	V	400
Current / for AC / rated value	Α	2
Protection class IP		IP20, with connected conductors
Product extension / can be installed / supplementary device		Yes
power loss		-
Operational voltage Um		-
rated current In		-
Rated make-break capacity Icn		-
Rated service short-circuit breaking capacity lcs		-
Rated ultimate short-circuit breaking capacity Icu		-
Tripping characteristics Number		-
Tripping characteristic/-class Conventional tripping current I2, (x In)		
rated current In IEC, DIN/VDE		-
Tripping characteristic/-class Test current I4, hold (x In)		-
rated current In / IEC, DIN/VDE		
• at 30 Cel	Α	2
• at 40 Cel	Α	1.88
• at 45 Cel	Α	1.805
• at 50 Cel	Α	1.73

• at 55 Cel

• at 60 Cel

Resistance against shock / according to IEC 60068-2-27

A 1.655

A 1.58

150m/s² at 11ms half-sine

Certificates/approvals:

General Product Approval

Declaration of Conformity

Manufacturer other

## Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


http://support.automation.siemens.com/WW/view/en/5SY8302-7/all


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5SY8302-7

**CAx-Online-Generator** 

http://www.siemens.com/cax





last change: Nov 3, 2011