SIEMENS

Product data sheet 5SY8602-8



CIRCUIT BREAKER 400V 25KA, 3+N-POLE, D, 2A, D=70M

Similar to image

Technical data:				
Overvoltage class		3		
type of voltage		AC/DC		
Tripping characteristic class		D		
Degree of pollution		3		
Mounting depth	mm	70		
Energy limiting class		3		
Number of poles		4		
Number of pitch units for width		4		
Product function / n-switching		Yes		
Supply voltage frequency / rated value	Hz	50		
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	70		
Supply voltage / for AC / rated value	V	400		
Current / for AC / rated value	Α	2		
Protection class IP		IP20, with connected conductors		
Product extension / can be installed / supplementary device		Yes		
power loss		-		
Operational voltage Um		-		

	-
	-
	-
	-
	-
	-
	-
	-
Α	2
Α	1.88
Α	1.805
Α	1.73
Α	1.655
Α	1.58
	150m/s² at 11ms half-sine
	A A A

Certificat	tes/ap	prova	ls:

General Product Approval	Declaration of Conformity	other
ROSTEST	Manufacturer	<u>other</u>

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


http://support.automation.siemens.com/WW/view/en/5SY8602-8/all


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY8602-8

CAx-Online-Generator

http://www.siemens.com/cax





last change: Nov 3, 2011