SIEMENS

Product data sheet 5SY8632-7



CIRCUIT BREAKER 400V 25KA, 3+N-POLE, C, 32A, D=70M

Similar to image

Technical data:		
Overvoltage class		3
type of voltage		AC/DC
Tripping characteristic class		С
Degree of pollution		3
Mounting depth	mm	70
Energy limiting class		3
Number of poles		4
Number of pitch units for width		4
Product function / n-switching		Yes
Supply voltage frequency / rated value	Hz	50
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	30
Supply voltage / for AC / rated value	V	400
Current / for AC / rated value	Α	32
Protection class IP		IP20, with connected conductors
Product extension / can be installed / supplementary device		Yes
power loss		-
Operational voltage Um		-

	-
	-
	-
	-
	-
	-
	-
	-
Α	32
Α	30.72
Α	29.76
Α	28.8
Α	27.84
Α	26.88
	150m/s² at 11ms half-sine
	A A A

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
ROSTEST	Manufacturer	<u>other</u>

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

UL

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


 $\underline{\text{http://support.automation.siemens.com/WW/view/en/5SY8632-7/all}}$


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY8632-7

CAx-Online-Generator

http://www.siemens.com/cax





last change: Nov 3, 2011