



LV HRC FUSE LINK GL/GG WITH INSULATED GRIP LUGS  
WITH COMBINATION INDICATOR SIZE 1,  
63A, AC 500V/DC 440V

Similar to image

Technical data:		
Current / for AC / rated value	A	63
Operating class of the fuse link		gG
Size of the fallback-system / acc. to DIN EN 60269-1		NH1
Supply voltage		
• for AC / rated value	V	500
• for DC	V	440
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	120
• with DC / in accordance with IEC 60947-2 / rated value	kA	25
Design of an identification indicator		Combination alarms
Ambient temperature		
• minimum	°C	-5
• maximum	°C	40

Certificates/approvals:

## General Product Approval



[ROSTEST](#)



## Declaration of Conformity

[Manufacturer](#)

## Test Certificates

[Manufacturer](#)

## Shipping Approval



GL

## Further information:

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3NA6122/all>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA6122](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6122)

### CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Aug 26, 2011