





LV HRC FUSE LINK GL/GG WITH NON-INSULATED GRIP LUGS WITH COMBINATION INDICATOR SIZE 000, 6A, AC 500V/DC 250V

Similar to image

Technical data:		
Current / for AC / rated value	A	6
Operating class of the fuse link		gG
Size of the fallback-system / acc. to DIN EN 60269-1		NH000
Supply voltage		
• for AC / rated value	V	500
• for DC	V	250
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	120
• with DC / in accordance with IEC 60947-2 / rated value	kA	25
Design of an identification indicator		Combination alarms

Certificates/approvals:			
General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 KEMA	<a href="#">ROSTEST</a>  VDE	<a href="#">Manufacturer</a>  GL	<a href="#">Manufacturer</a>

Further information:

---

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

---

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

---

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NA7801/all>

---


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA7801](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7801)

---

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Aug 26, 2011