



LV HRC FUSE LINK GL/GG WITH INSULATED GRIP LUGS
WITH COMBINATION INDICATOR SIZE 2,
315A, AC 400V

Similar to image

Technical data:		
Current / for AC / rated value	A	315
Operating class of the fuse link		gG
Size of the fallback-system / acc. to DIN EN 60269-1		NH2
Supply voltage		
• for AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	120
Design of an identification indicator		Combination alarms
Ambient temperature		
• minimum	°C	-5
• maximum	°C	40

Certificates/approvals:	
General Product Approval	Test Certificates
ROSTEST	Manufacturer
	

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3NA6252-4/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6252-4

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Aug 26, 2011