



MAIN CONTROL SWITCH 3-POLE IU=100,
P/AC-23A AT 400V=37KW BASE MOUNTING MOUNTING
RAIL/TWO-HOLE MOUNTING ROTARY ACTUATOR
BLACK

Similar to image

General technical details:		
product brand name		SENTRON
product designation		main and EMERGENCY-OFF switches
Type from device		fixed mounting
Design of the operating mechanism		rotary actuator, black
Protection class IP		IP65
Number of poles		3
Acceptability for application		
• switch disconnecter		Yes
• main switch		Yes
• safety cut-out switch		Yes
• emergency stop switch		No
• maintenance/repair switch		Yes
Product equipment / interlock		Yes
Type of the driving mechanism / motor drive		No
Product extension / optional		
• motor drive		No
• voltage trigger		No
Ambient temperature / during operating	°C	-25 ... +55

Insulation voltage / rated value	V	690
Impulse voltage resistance / rated value	V	6,000
Active power loss / per conductor / typical	W	7.5
Mechanical operating cycles as operating time / of the main contacts / typical		100,000
Protection against electrical shock		finger-safe
Item designation / according to DIN EN 61346-2		S
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S

Main circuit:

Continuous current / rated value	A	100
Operating current / at AC-21 / rated value	A	100
Short-time current resistance (I _{cw}) / at 690 V / limited to 1 s / rated value	A	2,000
Operating frequency	Hz	50 ... 60
Operating voltage / at 50/60 Hz / for AC / rated value	V	690
Service power / at AC-3		
• at 400 V / rated value	kW	30
• at 690 V / rated value	kW	22
Service power / at AC-23 A		
• at 400 V / rated value	kW	37
• at 690 V / rated value	kW	30
Operating cycles / maximum	1/h	50

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		0
Continuous current / of the auxiliary contact / rated value	A	10
Operating voltage / of the auxiliary contacts / for AC / maximum	V	500
Insulation voltage / of the auxiliary switch / rated value	V	500

Short-circuit:

Design of the fuse link / for short-circuit protection of the main circuit / necessary		fuse gL/gG: 100 A
Design of the fuse link / for short-circuit protection of the auxiliary switch / required		fuse gL/gG: 10 A

Installation/mounting/dimensions:

Type of mounting		floor mounting
• front mounting		No
• front mounting with central fixation		No

• front mounting with 4-hole fixation		No
• series installation		Yes
• Rail installation		No
Width	mm	90
Height	mm	106
Depth	mm	470.5

Connection type:		
Design of the electrical connection / for main current circuit		connection terminals
Design of the electrical connection / for auxiliary contact		connection terminals
Type of the connectable conductor cross-section / for main contacts <ul style="list-style-type: none"> • solid • finely stranded / with conductor end processing • stranded 		4 ... 50 mm2 35 mm² 4 ... 50 mm2
Type of connectable conductor cross section / for auxiliary contacts <ul style="list-style-type: none"> • solid • stranded 		2x (0.75 to 2.5 mm2), 1x 4 mm2 2x (0.75 ... 2.5 mm2), 1x 4 mm2

Certificates/approvals:		
Verification of suitability		CSA / UL / CCC / GL / LRS / DNV / PRS
Conductor cross section that can be connected / for main contacts / solid / minimum	mm²	4
Conductor cross section that can be connected / for main contacts / solid / maximum	mm²	50
Conductor cross section that can be connected / for main contacts / stranded / minimum	mm²	4
Conductor cross section that can be connected / for main contacts / stranded / maximum	mm²	50
Conductor cross-section that can be connected / for main contacts / stranded wire / with conductor end processing / maximum	mm²	35
Conductor cross section that can be connected / for auxiliary contacts / solid / minimum	mm²	0.75
Conductor cross section that can be connected / for auxiliary contacts / solid / maximum	mm²	4
Conductor cross-section that can be connected / for auxiliary contact / stranded wire / with conductor end processing / minimum	mm²	0.75
Conductor cross-section that can be connected / for auxiliary contact / stranded wire / with conductor end processing / maximum	mm²	2.5
Conductor cross section that can be connected / for auxiliary contacts / stranded / min.	mm²	0.75

Conductor cross section that can be connected / for auxiliary contacts / stranded / max.

mm²

4

Certificates/approvals:

General Product Approval



CCC



CSA



GOST



UL

Test Certificates

[Special Test Certificate](#)

Shipping Approval



DNV



GL



LRS

other

[Declaration of Conformity](#)



UL

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3LD2714-0TK51/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2714-0TK51

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Apr 9, 2012