



MAIN/EMERG. STOP SWITCH 3-POLE IU=125, P/AC-23A AT 400V=45KW FLOOR MOUNTING DIN RAIL/TWO-HOLE MOUNTING KNOB RED/YELLOW (EMERG. STOP)

Similar to image

General technical details:		
product brand name		SETRON
product designation		main and EMERGENCY-OFF switches
Type from device		fixed mounting
Design of the operating mechanism		knob-operated mechanism, red/yellow
Protection class IP		IP44
Number of poles		3
Acceptability for application		
• switch disconnecter		Yes
• main switch		Yes
• safety cut-out switch		Yes
• emergency stop switch		Yes
• maintenance/repair switch		Yes
Product equipment / interlock		Yes
Type of the driving mechanism / motor drive		No
Product extension / optional		
• motor drive		No
• voltage trigger		No
Ambient temperature / during operating	°C	-25 ... +55

Insulation voltage / rated value	V	690
Impulse voltage resistance / rated value	V	6,000
Active power loss / per conductor / typical	W	12
Mechanical operating cycles as operating time / of the main contacts / typical		100,000
Protection against electrical shock		finger-safe
Item designation / according to DIN EN 61346-2		S
Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S

#### Main circuit:

Continuous current / rated value	A	125
Operating current / at AC-21 / rated value	A	125
Short-time current resistance (I <sub>cw</sub> ) / at 690 V / limited to 1 s / rated value	A	2,000
Operating frequency	Hz	50 ... 60
Operating voltage / at 50/60 Hz / for AC / rated value	V	690
Service power / at AC-3		
• at 400 V / rated value	kW	37
• at 690 V / rated value	kW	30
Service power / at AC-23 A		
• at 400 V / rated value	kW	45
• at 690 V / rated value	kW	37
Operating cycles / maximum	1/h	50

#### Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		0
Continuous current / of the auxiliary contact / rated value	A	10
Operating voltage / of the auxiliary contacts / for AC / maximum	V	500
Insulation voltage / of the auxiliary switch / rated value	V	500

#### Short-circuit:

Design of the fuse link / for short-circuit protection of the main circuit / necessary		fuse gL/gG: 125 A
Design of the fuse link / for short-circuit protection of the auxiliary switch / required		fuse gL/gG: 10 A

#### Installation/mounting/dimensions:

Type of mounting		floor mounting
• front mounting		No
• front mounting with central fixation		No

• front mounting with 4-hole fixation		No
• series installation		Yes
• Rail installation		No
<b>Width</b>	mm	71
<b>Height</b>	mm	83
<b>Depth</b>	mm	97

Connection type:		
<b>Design of the electrical connection / for main current circuit</b>		connection terminals
<b>Design of the electrical connection / for auxiliary contact</b>		connection terminals
<b>Type of the connectable conductor cross-section / for main contacts</b> <ul style="list-style-type: none"> <li>• solid</li> <li>• finely stranded / with conductor end processing</li> <li>• stranded</li> </ul>		4 ... 50 mm2 35 mm² 4 ... 50 mm2
<b>Type of connectable conductor cross section / for auxiliary contacts</b> <ul style="list-style-type: none"> <li>• solid</li> <li>• stranded</li> </ul>		2x (0.75 to 2.5 mm2), 1x 4 mm2 2x (0.75 ... 2.5 mm2), 1x 4 mm2

Certificates/approvals:		
<b>Verification of suitability</b>		CSA / UL / CCC / GL / LRS / DNV / PRS
<b>Conductor cross section that can be connected / for main contacts / solid / minimum</b>	mm²	4
<b>Conductor cross section that can be connected / for main contacts / solid / maximum</b>	mm²	50
<b>Conductor cross section that can be connected / for main contacts / stranded / minimum</b>	mm²	4
<b>Conductor cross section that can be connected / for main contacts / stranded / maximum</b>	mm²	50
<b>Conductor cross-section that can be connected / for main contacts / stranded wire / with conductor end processing / maximum</b>	mm²	35
<b>Conductor cross section that can be connected / for auxiliary contacts / solid / minimum</b>	mm²	0.75
<b>Conductor cross section that can be connected / for auxiliary contacts / solid / maximum</b>	mm²	4
<b>Conductor cross-section that can be connected / for auxiliary contact / stranded wire / with conductor end processing / minimum</b>	mm²	0.75
<b>Conductor cross-section that can be connected / for auxiliary contact / stranded wire / with conductor end processing / maximum</b>	mm²	2.5
<b>Conductor cross section that can be connected / for auxiliary contacts / stranded / min.</b>	mm²	0.75

Conductor cross section that can be connected / for auxiliary contacts / stranded / max.

mm<sup>2</sup>

4

#### Certificates/approvals:

##### General Product Approval



##### Test Certificates

[Special Test Certificate](#)

##### Shipping Approval



##### other

[Declaration of Conformity](#)



#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3LD2830-0TK13/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3LD2830-0TK13](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2830-0TK13)

##### CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Apr 9, 2012