

compact Pin Busbar, 10mm<sup>2</sup> connection: 2p (P & N) 1x RCCB 2-pole  
+ 5x AFDD 5SM6+ compact device 1-pole + auxiliary switch 0,5-pole  
touch protected 12 MW fixed length



| Model                                                                                                                                                                   |            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Product brand name                                                                                                                                                      | SENTRON    |
| Product designation                                                                                                                                                     | Pin busbar |
| General technical data                                                                                                                                                  |            |
| Surface processing / tin-plated                                                                                                                                         | No         |
| Main circuit                                                                                                                                                            |            |
| Operating current / rated value                                                                                                                                         | 63 A       |
| Product details                                                                                                                                                         |            |
| Product feature / flexible                                                                                                                                              | Yes        |
| Mechanical Design                                                                                                                                                       |            |
| Height                                                                                                                                                                  | 13.7 mm    |
| Width                                                                                                                                                                   | 42.4 mm    |
| Length                                                                                                                                                                  | 216.4 mm   |
| Thickness / of busbar                                                                                                                                                   | 1.8 mm     |
| Further information                                                                                                                                                     |            |
| <b>Information- and Downloadcenter (Catalogs, Brochures,...)</b><br><a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a> |            |

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3685-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3685-0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3685-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3685-0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

