

Fault signal contact with test and acknowledgment key 2 NO for miniature circuit breaker 5SL, 5SY, 5SP RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)



Model	
Product brand name	SENTRON
Product designation	Fault signal contact
Design of the product	Mountable
Electrical endurance (switching cycles) / typical	20 000
Protection class IP	IP20
Product details	
Product component	Yes
• fault signal contact	
Product extension	Fault signal contact
Connections	
Connectable conductor cross-section	0.5 mm² 2.5 mm²
• minimum	
• maximum	
Tightening torque / with screw-type terminals	0.5 N·m
• maximum	
Mechanical Design	
Height	90 mm

Width	9 mm
Depth	70 mm
Net weight	48 g
Ambient temperature	
• during operation / minimum	-25 °C
• during operation / maximum	55 °C
• during storage / minimum permissible	-40 °C
• during storage / maximum permissible	75 °C

Certificates

Reference code

- acc. to DIN EN 81346-2

SF

Declaration of Conformity

Railway

[Vibration and Shock](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3021-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3021-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3021-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



