

compact Pin Busbar, 10mm² connection: 1p/N (FI N-right) 1x RCCB
2-pole + 10x compact device 1-pole touch protected N-right 12 MW
cutable

Model	
Product brand name	SENTRON
Product designation	Pin busbar

General technical data	
Surface processing / tin-plated	No

Main circuit	
Operating current / rated value	63 A

Product details	
Product feature / flexible	Yes

Mechanical Design	
Height	13.7 mm
Width	42.4 mm
Length	215 mm
Thickness / of busbar	1.8 mm

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3784-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3784-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3784-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

