



Figure similar

CIRCUIT BREAKER 3VA1 IEC FRAME 160 BREAKING
CAPACITY CLASS H ICU=70KA @ 415 V 4-POLE,
LINE PROTECTION TM240, ATAM, IN=100A
OVERLOAD PROTECTION IR=70A ...100A SHORT
CIRCUIT PROTECTION II=5...10 X IN NEUTRAL
PROTECTION 100% CABLE CONNECTION

Model		
product brand name		SENTRON
Product designation		Molded case circuit breaker
Design of the product		Line protection
Product variations		General Applications
Ground fault monitoring version		Without
Design of the auxiliary release		Without auxiliary release
Design of the auxiliary switch		Without
Design of the operating mechanism		toggle handle
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		TM240
General technical data		
Number of poles		4
Trip class / of the L-trip / with I _{2t} characteristic / initial value		1
Trip class / of the L-trip / with I _{2t} characteristic / Full-scale value		1
Electrical endurance (switching cycles)		
• at AC-1 / at 380/415 V / at 50/60 Hz		8 000
circuit-breaker / Design		3VA
Mechanical service life (switching cycles) / typical		15 000
Voltage		
Insulation voltage		
• Rated value	V	800

Protection class		
Protective function of the overcurrent release		LI
Switching capacity		
Switching capacity class of the circuit breaker		H
Dissipation		
Active power loss		
• maximum	W	25
Electricity		
Operating current / at 45 °C / Rated value	A	100
Continuous current / Rated value / maximum	A	160
Continuous current		
• Rated value	A	100
Adjustable response value current		
• of the current-dependent overload release / Full-scale value	A	1
• of the instantaneous short-circuit release / initial value	A	5
Net weight	g	1 200
Main circuit		
Operating voltage		
• with AC / at 50/60 Hz / Rated value	V	690
• for DC / Rated value	V	600
Operating current		
• at 40 °C / Rated value	A	100
• at 50 °C / Rated value	A	100
• at 55 °C / Rated value	A	98
• at 60 °C / Rated value	A	96
• at 65 °C / Rated value	A	94
• at 70 °C / Rated value	A	91
Auxiliary circuit		
Number of CO contacts		
• for auxiliary contacts		0
Suitability		
• Suitability for use		system protection
Adjustable parameters		
Adjustable response value current		
• of I-trip / Full-scale value	A	10
• for N-conductor protection / initial value	A	100
• for N-conductor protection / Full-scale value	A	100

Adjustable response value current / of the current-dependent overload release / initial value	A	0.7
Appearance		
Product details		
Product component • Trip indicator • display • Voltage trigger • undervoltage release • undervoltage release with leading contact		No No No No No
Product property • for neutral conductors / upgradeable/retrofitable / Short-circuit and overload proof		No
Product expansion • optional — motor drive		Yes
Product function		
Product function • Intrinsic device protection • communication function • Phase failure detection • other measurement function		Yes No No No
Accessories		
Manufacturer article number / of the supplied basic switch		3VA1110-6GF46-0AA0
Short circuit		
Operational short-circuit current breaking capacity (Ics) • at 240 V / Rated value • at 415 V / Rated value • at 440 V / Rated value • at 500 V / Rated value • at 690 V / Rated value	kA kA kA kA kA	100 70 36 15 5
Maximum short-circuit current breaking capacity (Icu) • at 240 V / Rated value • at 415 V / Rated value • at 440 V / Rated value • at 500 V / Rated value • at 690 V / Rated value	kA kA kA kA kA	100 70 36 20 10
Short-circuit current making capacity (Icm)		

- at 240 V / Rated value
- at 415 V / Rated value
- at 690 V / Rated value

kA	220
kA	154
kA	17

Connections

Arrangement of electrical connectors		
• for main current circuit		Front terminal
Type of connectable conductor cross-section		
• of the round conductor terminal / stranded		1 x (1.5 - 70 mm ²)
Design of the electrical connection		
• for main current circuit		Box terminal

Mechanical Design

Height	mm	130
Width	mm	101.6
Depth	mm	70
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	-25
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates

Reference code		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

General Product Approval	EMC	Declaration of Conformity	Shipping Approval	other
---------------------------------	------------	----------------------------------	--------------------------	--------------



[other](#)



EG-Konf.



GL

[other](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA11106GF460AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VA11106GF460AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA11106GF460AA0




Figure similar



Figure similar

last modified:

21.10.2014