

Product-type designation

SCALANCE W786-2 RJ45



IWLAN ACCESS POINT,
SCALANCE W786-2 RJ45,
FOR USE OUTSIDE OF USA, 2 RADIOS,
6 R-SMA ANT.CONNECT.,
IEEE 802.11A/B/G/H/N, 2.4/5GHZ,
BRUTTO 450 MBIT/S PRO RADIO,
1 X RJ45 (MAX. 1 GBIT/S), POE, 24VDC,
IP65 (-40-+60 DGR C), POE,
WPA2/802.11i/E,
PLEASE NOTE NATIONAL APPROVALS! SCOPE OF
SUPPLY: MANUALS ON CD ROM GERMAN/ENGLISH,
1 X TERMINAL BLOCK.

Transmission rate

Transmission rate

• with W-LAN / maximum	450 Mbit/s
• with Industrial Ethernet	10 ... 1000 Mbit/s

Interfaces

Number of electrical connections

• for network components and terminal equipment	1
• for power supply	1
• for redundant power supply	1

Design of the electrical connection

• for network components and terminal equipment	RJ45 socket
• for power supply	2-pole connector (24 V DC) or optionally available power supply adapter (4-pole 24 V DC or 3-pole 110 to 230 V AC)

Version of the swap medium

• C-PLUG	Yes
• KEY-PLUG	Yes

Number of radio cards / permanently installed

2

Type of transmission / for multiple input multiple output (MIMO)

3x3

Number of spatial streams

3

Number of electrical connections / for external antenna(s)

6

Design of the electrical connection / for external antenna(s)	R-SMA (socket)
Product property / external antenna can be mounted directly on device	No
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage	
• 1 / from terminal block	19.2 V
• 2 / from terminal block	28.8 V
• from Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	48 V
• from Power-over-Ethernet according IEEE802.3at for type 2	50 V
Current consumed	
• at 24 V / with DC / typical	0.63 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.22 A
Active power loss	
• at 24V / for DC / typical	15 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-40 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	100 %
Protection class IP	IP65
Ambient condition / for (standard) operation mode	When using the power supply 100 to 240 V AC, an operating temperature of -40 °C to +60 °C is permissible
Design, dimensions and weight	
Width / of enclosure / without antenna	251 mm
Height / of enclosure / without antenna	251 mm
Depth / of enclosure / without antenna	72 mm
Net weight	2.24 kg
Mounting type	
• S7-1500 rail mounting	No
• wall mounting	Yes
Mounting type	For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required
Wireless frequencies	
Radio frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz

- for WLAN in 5 GHz frequency band

4.9 ... 5.8 GHz

Product properties, functions, components / general

Product function

- Access Point Mode
- Client Mode

Yes
Yes

Number of SSIDs

16

Product function

- Dual Client
- iPCF Access Point
 - note
- iPCF client
 - note
- iPCF-MC Access Point
- iPCF-MC client

No
Yes
Only in combination with the 'KEY-PLUG W780 iFeatures'
Yes
Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'
No
No

Number of iPCF-capable radio modules

2

Product functions / management, configuration

Number of manageable IP addresses / in client

8

Product function

- CLI
- web-based management
- MIB support
- TRAPs via email
- Configuration with STEP 7
- configuration with STEP 7 in the TIA Portal
- operation with IWLAN controller
- operation with Enterasys WLAN controller
- forced roaming with IWLAN
- WDS

Yes
Yes
Yes
Yes
No
No
No
No
Yes
Yes

Protocol / is supported

- Address Resolution Protocol (ARP)
- ICMP
- Telnet
- HTTP
- HTTPS
- TFTP
- SNMP v1
- SNMP v2
- SNMP v3
- DCP

Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes
Yes

• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / Diagnosis	
Product function	
• PROFINET IO diagnosis	No
• Link Check	No
• connection monitoring IP-Alive	No
• localization via Aeroscout	No
• SysLog	Yes
Product functions / VLAN	
Product function / function VLAN with IWLAN	Yes
Product functions / DHCP	
Product function / DHCP client	Yes
Product function / in Client Mode / DHCP server via LAN	No
Product functions / Redundancy	
Protocol / is supported / STP/RSTP	Yes
Product functions / Security	
Product function	
• Management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported / SSH	Yes
Product functions / Time	
Protocol / is supported / SNTP	Yes
Standards, specifications, approvals	
Standard	
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	-
Verification of suitability	
• CE mark	Yes
• EC declaration of conformity	Yes
• C-Tick	Yes
• Railway application in accordance with EN 50155	No

• E1 approval	No
• NEMA4X	Yes
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• Power-over-Ethernet according to IEEE802.3at for type 2	Yes
Standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Accessories	
Accessories	24 V DC screw terminal included in scope of delivery
letzte Änderung:	Mar 31, 2014