



Product Features

- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- CV cone
- flange connection
- with sidewise drain valve, rotatable hose connection element G 3/4
- with test port
- check valve with SST spring
- EPDM-seat gasket
- free from dead spots
- for any installation position

Standards and Approvals

- acc. to DVGW provisions
- plastic parts with KTW- and W 270 approval
- acc. to DIN EN 13959 provisions/DIN EN 558-1

Technical Data

- pressure rating PN 16
- max. operating temperature 100 °C

Part No.	DN	number of boreholes	A1	A2	D1 (mm)	D2 (mm)	D3 (mm)	H1 (mm)	L1 (mm)	S1 (mm)	kvs (m³/h)	? popening (hpa)	Zeta
1640205000	50	4	G 1/4	G 3/8	165	102	50	101	230	14	64.7	70	2.3
1640206500	65	4	G 1/4	G 3/8	185	122	65	137	290	15	116	120	2.1
1640208000	80	8	G 1/4	G 3/8	200	138	80	152	310	16	130	140	3.8

Accessories

- Gunmetal sampling valve, figure 187 00
- backing ring for stub flange, figure 410 00
- stub flange, figure 425 00
- threaded flange, figure 426 00
- gasket, figure 428 00