Elpress Mini

- electro-hydraulic crimping tool 0.14 to 50 mm²



The Elpress mini tool PVL130P in a new sleek design with a high performance Li-lon battery that streamlines your work with its improved battery capacity.

CHARACTERISTICS:

- Single-handed operation for easy control of all tool functions
- Powerful crimping head ensures long service life
- Optimum crimping due to parallel guided crimping dies
- Easy to use due to its low weight
- High-performance 10.8 V Li-lon battery with indication of charge status
- Open head, rotatable
- Easy and comfortable to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Automatic return of dies when crimping is completed

The tool is delivered without dies, they should be ordered separately.

Elpress MINI – crimping dies

Application	Area	Dies	Crimp geometry
Insulated	0,5 - 6 mm²	SA0760	\
Uninsulated	0,25 - 2,5 mm²	KB0325	8
Uninsulated	0,5 - 6 mm²	RB0560	FE
Uninsulated	4 - 10 mm²	WB4099	~~~
End sleeves	0,5 - 6 mm²	EB0560	
	4 - 10 mm²	EB4010	
	10 - 25 mm²	EB1025	
	35 - 50 mm²	EB3550	
End sleeve TWIN	2x4 - 2x10 mm²	EB4010- TWIN	

TECHNICAL DATA PVL130P:

Crimping process

Crimping force 13 kN
Crimping range 0.14 - 50 mm²

(dependent on material)

about 2 s

Number of crimps about 230 for 10 mm² Cu

Battery voltage 10.8 V
Battery capacity 1.5 Ah, Li-lon
Charge time about 40 minutes.

Weight including battery 1.5 kg

Ambient temperature -10°C to +40°C

Dimensions 330 x 85 x 60 mm





