



G2 MPOptimate® Multimode OM4 MPO-12 Distribution Module, 2x12F MPO pinned to 24F LC Aqua with internal shutters, Method A Pair Flipped

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	Fiber module

General Specifications

Adapters, quantity, front	12
Adapters, quantity, rear	2
Color, front	Aqua
Color, rear	Black
Interface Feature, front	Standard
Interface Feature, rear	Standard
Interface, front	LC
Interface, rear	MPO Pinned
Polarity	Pairs, flipped
Shuttered	Yes
Total Fibers, quantity	24
Total Ports, quantity, front	24

Dimensions

Height	26.42 mm 1.04 in
Width	96.52 mm 3.8 in
Depth	117.35 mm 4.62 in

Optical Specifications

Fiber Mode	Multimode
-------------------	-----------

760242496 | DM12-24LC-LS-AF

Fiber Type	OM4, LazrSPEED® 550
Insertion Loss, maximum	0.35 dB

Environmental Specifications

Qualification Standards	TIA/EIA-568-C.3
-------------------------	-----------------

Packaging and Weights

Packaging quantity	1
--------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted

