

ARG 110 ERGOTEC TWIN CLICK





GENERAL

Art. no.:	G-0110-C	E-class number:	40-02-01-02
EAN:	4030281077077	Customs no.:	63079098
Standard:	EN 361:2002		



ARG 110 ERGOTEC TWIN CLICK

FEATURES

Elastic belt strap:	yes	
Hand-washing:	40 °C	
Click buckles:	yes	
Max. service life:	6-8 Years	
Max. number of persons:	1	
Attachment Points:		
dorsal attachment point, s	sternal attachment point	
Temperature:		
from -35 °C to +45 °C		
Area of application:		
Facade / Window Cleaning, Fire brigade / Rescue / Special Forces		

DIMENSIONS

Size:	M/L
Waist size:	800-1200mm
Weight:	1,25 kg





MATERIAL

Material Click buckle:

Material: Polyester, Aluminium

Webbing material: Polyester

Sternal attachment point material:
Polyester

Restraint travelling attachment point material:
Aluminium

Aluminium



LOOP SEP 40 kN



GENERAL

Art. no.:	L-0397-0,75	E-class number:	40-02-01-04
EAN:	4030281100263	Customs no.:	63079098
Standard:	EN 354:2010 EN 566:2006 EN 795-B:2012		



LOOP SEP 40 kN

LOOP SEP was specially developed for working at sharp edges. The tensile force of 40 kN and the flexible casing made from special cutproof fibres make the loop practically indestructible. The fixing is stitched conically so that the loop does not get caught at this critical point.

FEATURES

Breaking load, major axis:

40 kN

Diameter:	30 mm
Hand-washing:	40 °C
Suitable for edges:	yes
Max. service life:	4-6 Years
Max. number of persons:	1
Patent	
- .	

Temperature:

from -35 °C to +45 °C

Area of application:

Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, Power Supplies / - Transmission / Telecommunications, Rope Access / Rigging

DIMENSIONS

Size:	0,75m
Weight:	0,48 kg



HARDWARE

Carabiner on belt side: KOBRA TW

MATERIAL

Material: Polyester, Steel



HK



GENERAL

Art. no.:	HSG-002-10	E-class number:	40-02-01-03
EAN:	4030281066491	Customs no.:	84798997
Standard:	EN 360:2002		



HK

SKYLOTEC automatic fall arrest blocks are light and compact and provide the maximum in functional safety and durability.

- -The spring return is very small, weighing just 1.5 kg.
- -The housing is manufactured from break-proof ABS plastic. The interior is made of saltwaterproof aluminium.
- -The carabiner is equipped with a fall indicator.
- -The cable is 5 mm thick and made of steel. The maintenance costs are low and the professional inspection, required annually, can take place without opening the device. The devices are also approved for horizontal use according to RFU (recommendation for use) in combination with the shock absorber package...

FEATURES

Fall indicator

Max. number of persons: 1

Temperature:

from -35 °C to +45 °C

Suspension element: Steel rope 5mm

Area of application:

Construction / Roofer / Carpenter

DIMENSIONS

Size: 10m

Weight: 3,87 kg

HARDWARE

Carabiner on rope: FS 51 WIB IND ANSI

MATERIAL

Material:

Acrylnitril-Butadien-Styrol, Steel, Aluminium



ROPE BAG



GENERAL

Art. no.: ACS-0009-3 E-class number: 40-02-92-90

EAN: 4030281050582 Customs no.: 39232990



ROPE BAG

Classic rope bag for easy transportation and stowage of climbing ropes.

Max. rope length Ø11mm: 90m

FEATURES

Diameter: 300 mm

Material load, max.: 20 kg

Area of application:

Fire brigade / Rescue / Special Forces, Mobile

Work Platforms

DIMENSIONS

 Size:
 3

 Contents:
 30 I

 Weight:
 0,39 kg

MATERIAL

Material: Polyamide