

SIMATIC ET 200SP, DIGITAL INPUT MODULE, DI 8X24VDC
BASIC, PACKING UNIT: 1 PIECE, FITS TO BU-TYPE A0, COLOR
CODE CC01, MODULE DIAGNOSIS



General information	
Product type designation	ET 200SP, DI 8x24VDC BA, VPE 1
Firmware version	V1.0
• FW update possible	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC01
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V13 SP1
• STEP 7 configurable/integrated as of version	V5.5 SP3 / -
• PROFIBUS as of GSD version/GSD revision	GSD Revision 5
• PROFINET as of GSD version/GSD revision	GSDML V2.3
Operating mode	
• DI	Yes
• Counter	No
• Oversampling	No

- MSI

No

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption (rated value)	8 mA; without sensor supply
Current consumption, max.	70 mA; All channels are supplied from the encoder supply

Encoder supply

Number of outputs	8
Output voltage encoder supply, min.	19.2 V
Short-circuit protection	No

24 V encoder supply

• 24 V	Yes
• Short-circuit protection	Yes
• Output current, max.	700 mA

Power loss

Power loss, typ.	1.6 W; 24 V, 8 inputs supplied via encoder supply
------------------	---

Address area

Address space per module	
• Address space per module, max.	1 byte
• Inputs	1 byte

Digital inputs

Number of digital inputs	8
m/p-reading	p-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No

Input voltage

• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V

Input current

• for signal "1", typ.	6.8 mA
--	--------

Input delay (for rated value of input voltage)

for standard inputs	
— parameterizable	Yes; None / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 µs to 500 µs, depending on line length)
for interrupt inputs	
— parameterizable	No
for counter/technological functions	
— parameterizable	No
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	2 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostics	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes
— parameterizable	Yes
• Monitoring of encoder power supply	No
• Wire-break	No
• Short-circuit	No
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	No

Permissible potential difference	
between different circuits	75 V DC/60 V AC (base isolation)
Isolation	
Isolation tested with	707 V DC (type test)
Dimensions	
Width	15 mm
Weights	
Weight, approx.	28 g
last modified:	22.01.2016