

Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483 Add:912 Xicun section Shilina Road Shawan Panyu Guangzhou,China.511483

Tel:86-20-39196888

Fax:86-20-61981166

MATERIAL SAFETY DATA SHEET

Date : Jan 1st, 2021 File No.: PH-W5-104

1. Identification of the substance/preparation and of the company/undertaking

Identification of the product

Product name : Lithium Ion Battery
Chemical System: Li(NiCoMn)O2/C

Model: ICR18650 4400mAh 7.4V 32.56Wh

Designated for RECHARGE? \underline{X} Yes \underline{N} No

Manufacturer/supplier identification

Company: Guangzhou Great Power Energy & Technology Co.,

Ltd.

Contact for information: 912 Xicun Section, Shiliang Road, Shawan, Panyu,

Guangzhou, GD, PRC

Emergency telephone No.: 0086-20-39196888

2. Composition/information on ingredients

Ingredient	Percent	CAS Index	Molar	Molecular	Symb
		No./EC No.	mass	formula	ol
Ternary Materials	28.4%	182442-95-1		Li(NiCoMn)O	
				2	
Graphite	17.1%	7782-42-5		С	
Lithium hexafluorophosphate	1.3%	21324-40-3		LiPF6	
Ethylene carbonate	3.4%	96-49-1	C3H4O3		



Aluminum

广州鹏辉能源科技股份有限公司

Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483 Add:912 Xicun section Shilina Road Shawan Panyu Guangzhou,China.511483

Fax:86-20-61981166

Αl

Diethyl carbonate	4.7%	105-58-8	C5H10O3
Dimethyl carbonate	3.8%	616-38-6	C3H6O3
Polypropylene	2%	9003-07-0	(C3H6)n
Steel	31.1%	7439-89-6	Fe
Copper	5.7%	7440-50-8	Cu

7429-90-5

Tel:86-20-39196888

Weight of metallic lithium per cell: 0g. There is no metallic lithium in the lithium-ion battery. The lithium polymer battery is with a Watt-hour rating \leq 20 Wh/Cell (cell), \leq 100 Wh (battery pack).

2.5%

3. Hazards identification

Health Hazards (Acute and Chronic):

For the battery cell, chemical materials are stored in a hermetically sealed can, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, or added electric stress by misuse the cell case will be breached and hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

Carcinogenicity:

NTP: None IARC Monograph: None OSHA Regulated: None

Medical Conditions Generally Aggravated by Exposure:

An acute exposure will not generally aggravate any medical condition.

Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

W

广州鹏辉能源科技股份有限公司

Guangzhou Great Power Energy & Technology CO.,LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483 Add:912 Xicun section Shilina Road Shawan Panyu

Guangzhou, China. 511483

Tel:86-20-39196888

Fax:86-20-61981166

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and the stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and the stimulation on the eye. Inflammation of the eyes may occur.

Environmental effects:

Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it may generate detrimental hydrogen fluoride. Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

4. First aid measures

After inhalation contact: Make the victim blow his/her nose, gargle. Seek medical

attention if necessary.

After skin contact: Remove contaminated clothes and shoes immediately.

Immediately wash extraneous matter or contact region with soap

and plenty of water.

After eye contact: Do not rub eyes. Immediately flush eyes with water continuously

for at least 15 minutes. Seek medical attention.

After ingestion contact: Make the victim vomit. Immediately seek medical attention.

5. Fire-fighting measures

Extinguishing Media: Plenty of water, CO₂ gas, nitrogen gas, chemical powder fire

extinguishing medium and fire foam.

Specific methods of

fire-fighting:

When the battery burns with other combustibles simultaneously,

take fire extinguishing method which corresponds to the

combustibles. Extinguish a fire from the windward as much as



Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483 Add:912 Xicun section Shilina Road Shawan Panyu Guangzhou,China.511483

Tel:86-20-39196888 Fax:86-20-61981166

possible.

Flammable Limits: Not available

6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

7. Handling and storage

Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Specific control parameter:

Personal protective equipment :

Respiratory protection (Specify Not necessary under conditions of normal use.

Type):

Ventilation:

Protective Gloves:

Not necessary under conditions of normal use.

(Clothing or Equipment):

9. Physical and chemical properties

W

广州鹏辉能源科技股份有限公司

Guangzhou Great Power Energy & Technology CO.,LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483

Add:912 Xicun section Shilina Road Shawan Panyu Guangzhou,China.511483

Tel:86-20-39196888

Fax:86-20-61981166

Appearance

Physical state: Solid

Form: Cylindrical
Color: Metallic color
Odor: No odor

PH N/A

Specific temperatures Temperature ranges changes in physical state occur.

Flash point N/A Explosion properties N/A Density N/A

Solubility with indication of the solvent(s): Insoluble in water

10. Stability and reactivity

Stability: Stable

Conditions to Avoid: When cell is exposed to an external short-circuit, crushes, deformation,

high temperature above 100 degree C, it will cause heat generation

and ignition. Avoid direct sunlight and high humidity.

Hazardous Acrid or harmful gas is emitted during fire.

Decomposition or

By-products:

Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong

acids.

Hazardous polymerization will not occur.

11. Toxicological information



Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483

Add:912 Xicun section Shilina Road Shawan Panyu

Guangzhou, China. 511483

Tel:86-20-39196888 Fax:8

Fax:86-20-61981166

Acute toxicity:

Copper 60-100mg sized coarse particulate causes a gastrointestinal

disturbance with nausea and inflammation. TDLo, hypodermic

- Rabbit 375mg/kg

Organic electrolyte LD50, oral - Rat 2,000mg/kg or more

Further toxicological

information:

Aluminum By the long-term inhalation of coarse particulate or fume, it is

possible to cause lung damage (aluminum lungs).

Graphite Long-term inhalation of high levels of graphite coarse

particulate may cause lung disease or a tracheal disease.

12. Ecological information

Ecotoxic effects: N/A

Further ecological data: N/A

13. Disposal considerations

Great Power encourages battery recycling. Our Li-ion batteries are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) *Charge Up to Recycle! Program*. For information call 1-800-8-BATTERY or see their website at www.rbrc.org. Li-ion batteries must be handled in accordance with all applicable state and federal laws and regulations.

DO NOT INCINERATE or subject battery cells to temperatures in excess of 212° F. Such treatment can vaporize the liquid electrolyte causing cell rupture. Do not use in combination with fresh and used lithium batteries neither with other type of battery.



Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483

Add:912 Xicun section Shilina Road Shawan Panyu

Guangzhou, China. 511483

Tel:86-20-39196888

Fax:86-20-61981166

14. Transport information

International transport 1. International Air Transport Association (IATA) pursuant to

regulations: Packing Instruction 965-967, Section II

2. International Maritime Dangerous Goods Code, SP188 of IM

DG 38-16.

4. U.S. hazardous materials regulations pursuant to 49 CFR

173.185 and Special Provision A188.

UN-No.: 3480

IATA Packaging Instruction Packing Instruction 965-967 Section II

Great Power Li-ion cells pass the tests defined in UN model regulation section 38.3. Cells and batteries are packed according to the requirement of 60th Edition of the IATA Dangerous Goods Regulations (DGR).

If Great Power Li-ion cells are used to construct battery packs, the assembler of that pack is responsible to ensure the battery has been tested in accordance with the requirements contained in the UN Model Regulations, Manual of Test and Criteria. Part III, subsection 38.3.

15. Regulatory information		
N/A		
16. Other information		



Guangzhou Great Power Energy & Technology CO., LTD

广东省广州市番禺区沙湾镇市良路西村段 912 号 P.C.:511483 Add:912 Xicun section Shilina Road Shawan Panyu Guangzhou,China.511483

Tel:86-20-39196888

Fax:86-20-61981166

Make people:

Professional post: R&D Engineer

Name(sign): James Lee

Make unit:

Name: R&D Department

Phone: 0086-20-39196888

tune not bepartment

Address: R&D Dept., Panyu Plant.,

Date of issue: 2021/01/01

DISCLAIMER:

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Guangzhou Great Power Energy & Technology Co.,Ltd makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

