


WC-SYSTEM FOR DRY-WALL CONSTRUCTION VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922309
Collection	ViConnect
PROJECTS	 PLUS
Width	525 mm
Height	1120 mm
Depth	135 mm
Weight	14,8 kg

description

for covering with plasterboard, Easy connection to flush plate via flexible cables with bayonet joint, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, installation onto a solid brick wall, in dry-wall constructions etc, adjustment range front to wall: 135-205mm (when mounted on wall brackets), installation onto or in front of a solid brick wall incl. 4 wall mounts and fastening materials, incl. self-locking feet with adjustable base plates, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate tested in accordance with DIN EN 14055 packaged in a box For combination with: for wall-mounted WC self-supporting powder-coated steel frame, fully pre-assembled, front operated, with small inspection opening Please order flush plate separately. concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, adjustable flush flow control for adaptation to rimless toilet bowls, corner valve R1/2 for water connection in the cistern, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, filling valve Noise Class I, certification marks for concealed cistern: Noise Class I for dry-wall construction

Specification texts

ViConnect; Toilet installation system; Size: 525 x 1120 x 135 mm; for covering with plasterboard, Easy connection to flush plate via flexible cables with bayonet joint, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, installation onto a solid brick wall, in dry-wall constructions etc, adjustment range front to wall: 135-205mm (when mounted on wall brackets), installation onto or in front of a solid brick wall; incl. 4 wall mounts and fastening materials, incl. self-locking feet with adjustable base plates, 2 times M12 WC retaining bolts adjustable to 180/230mm with protection plugs and nuts, installation instructions, without flush plate; tested in accordance with DIN EN 14055; packaged in a box; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled, front operated, with small inspection opening; Please order flush plate separately.; concealed cistern insulated against condensation water, with dual flush (7.5-4.5 l / 4-2 l), factory setting 6/3 l, adjustable flush flow control for adaptation to rimless toilet bowls, corner valve R1/2 for water connection in the cistern, drain bend clamp, 4 adjustment settings, PE toilet connecting bend DN 90 (Ø 90) with reducing sleeve DN 90 (Ø 90) / DN 100 (Ø 110) with protection plugs, complete WC connection set DN 90 (Ø 90) / 180 mm, protection box for access opening can be cut to size, flexible hose for filling valve, can be tightened by hand, filling valve Noise Class I, certification marks for concealed cistern: Noise Class I; for dry-wall construction

COLOURS

92230900 4051202844493

TECHNICAL DRAWINGS

922309

