

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data 1FK7042-2AF71-1QA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Physical constants	
Rated speed	3000 rpm	Torque constant	1.38 Nm/A
Number of poles	8	Voltage constant at 20° C	90.0 V/1000*min ⁻¹
Rated torque (100 K)	2.6 Nm	Winding resistance at 20° C	4.67 Ω
Rated current	1.9 A	Rotating field inductance	35.0 mH
Static torque (60 K)	2.50 Nm	Electrical time constant	7.50 ms
Static torque (100 K)	3.0 Nm	Mechanical time constant	2.15 ms
Stall current (60 K)	1.8 A	Thermal time constant	30 min
Stall current (100 K)	2.2 A	Shaft torsional stiffness	15500 Nm/rad
Rotor moment of inertia	2.900 kgcm ²	Net weight of the motor	4.6 kg
Efficiency	89.0 %		

Mechanical data			
Motor type	Compact	Electrical connectors	Connectors for signals and power rotatable
Shaft height	48	Color of the housing	Standard painting (Anthracite RAL 7016)
Cooling	Natural cooling	Holding brake	without holding brake
Radial runout tolerance	0.040 mm	Shaft extension	Feather key
Concentricity tolerance	0.08 mm	Encoder system	Encoder AS20DQI: absolute encoder single-turn 20 bits
Axial runout tolerance	0.08 mm		
Vibration severity grade	Grade A		
Connector size	1		
Degree of protection	IP64		
Design acc. to Code I	IM B5 (IM V1, IM V3)		
Temperature monitoring	KTY84 temperature sensor in the stator winding		



Figure similar

MLFB-Ordering data 1FK7042-2AF71-1QA0

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	3 A
Optimum power	0.8 kW	Maximum inverter current	6 A
Limiting data		Maximum torque	8.20 Nm
Max. permissible speed (mech.)	6400 rpm		