

Declaration of performance

No. DoP-ISG-3452-r01

1. Unique identification code of the product-type:

Product name: Stelrad Accord, 4 Connections Hygiene, Design Flat Front, Stelrad Novello, Stelrad Compact All in, Design Flat Front double Sided Planar

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: In heating systems in buildings

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Stelrad Radiator Group Limited
Newcastle Upon Tyne
NE1 3JE
United Kingdom
dop@srgl.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Institut für GebäudeEnergetik, Universität Stuttgart
Pfaffenwaldring 35
70569 Stuttgart, Deutschland
Identification number: 0626

performed the assessment and evaluation of the product under system 3 by determination of the product-type on the basis of type testing

and issued the corresponding test reports.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

Declaration of performance

No. DoP-ISG-3452-r01

9. Declared performance:

Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1	EN 442-1:2014
Release of dangerous substances	None	
Pressure tightness	No leakage at 1.3 x maximum operating pressure. Max. operating pressure: 1000 kPa	
Surface temperature	Maximum 110 °C	
Resistance to pressure	No failure at 1.69 x maximum operating pressure (kPa)	
Rated thermal outputs	See Annex 1	
Thermal output in different operating conditions (<i>characteristic curve</i>)	$\Phi = (K_M \times \Delta T^n) \times L/1000$ (K_M , n and L : see Annex 1)	
Durability as:		
Resistance against corrosion	No corrosion after 100h humidity	
Resistance against minor impact	Class 0	

4 connections Hygiene						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K_M
10	300	400	70	135	1,2829	2,2352
10	300	500	88	169	1,2829	2,2352
10	300	600	105	203	1,2829	2,2352
10	300	700	123	237	1,2829	2,2352
10	300	800	140	270	1,2829	2,2352
10	300	900	158	304	1,2829	2,2352
10	300	1000	176	338	1,2829	2,2352
10	300	1100	193	372	1,2829	2,2352
10	300	1200	211	406	1,2829	2,2352
10	300	1300	228	439	1,2829	2,2352
10	300	1400	246	473	1,2829	2,2352
10	300	1500	263	507	1,2829	2,2352
10	300	1600	281	541	1,2829	2,2352
10	300	1700	298	575	1,2829	2,2352
10	300	1800	316	608	1,2829	2,2352
10	300	1900	333	642	1,2829	2,2352
10	300	2000	351	676	1,2829	2,2352
10	300	2100	369	710	1,2829	2,2352
10	300	2200	386	744	1,2829	2,2352
10	300	2300	404	777	1,2829	2,2352
10	300	2400	421	811	1,2829	2,2352
10	300	2500	439	845	1,2829	2,2352
10	300	2600	456	879	1,2829	2,2352
10	300	2700	474	913	1,2829	2,2352

Declaration of performance

No. DoP-ISG-3452-r01

10	300	2800	491	946	1,2829	2,2352
10	300	2900	509	980	1,2829	2,2352
10	300	3000	527	1014	1,2829	2,2352
10	400	400	89	172	1,2933	2,7302
10	400	500	111	215	1,2933	2,7302
10	400	600	133	258	1,2933	2,7302
10	400	700	155	301	1,2933	2,7302
10	400	800	178	344	1,2933	2,7302
10	400	900	200	387	1,2933	2,7302
10	400	1000	222	430	1,2933	2,7302
10	400	1100	244	473	1,2933	2,7302
10	400	1200	267	516	1,2933	2,7302
10	400	1300	289	559	1,2933	2,7302
10	400	1400	311	602	1,2933	2,7302
10	400	1500	333	645	1,2933	2,7302
10	400	1600	355	688	1,2933	2,7302
10	400	1700	378	731	1,2933	2,7302
10	400	1800	400	774	1,2933	2,7302
10	400	1900	422	817	1,2933	2,7302
10	400	2000	444	860	1,2933	2,7302
10	400	2100	466	903	1,2933	2,7302
10	400	2200	489	946	1,2933	2,7302
10	400	2300	511	989	1,2933	2,7302
10	400	2400	533	1032	1,2933	2,7302
10	400	2500	555	1075	1,2933	2,7302
10	400	2600	577	1118	1,2933	2,7302
10	400	2700	600	1161	1,2933	2,7302
10	400	2800	622	1204	1,2933	2,7302
10	400	2900	644	1247	1,2933	2,7302
10	400	3000	666	1290	1,2933	2,7302
10	500	400	107	208	1,3038	3,1748
10	500	500	134	261	1,3038	3,1748
10	500	600	161	313	1,3038	3,1748
10	500	700	187	365	1,3038	3,1748
10	500	800	214	417	1,3038	3,1748
10	500	900	241	469	1,3038	3,1748
10	500	1000	268	521	1,3038	3,1748
10	500	1100	294	573	1,3038	3,1748
10	500	1200	321	625	1,3038	3,1748
10	500	1300	348	677	1,3038	3,1748
10	500	1400	375	729	1,3038	3,1748
10	500	1500	401	782	1,3038	3,1748
10	500	1600	428	834	1,3038	3,1748
10	500	1700	455	886	1,3038	3,1748
10	500	1800	482	938	1,3038	3,1748
10	500	1900	509	990	1,3038	3,1748
10	500	2000	535	1042	1,3038	3,1748
10	500	2100	562	1094	1,3038	3,1748
10	500	2200	589	1146	1,3038	3,1748
10	500	2300	616	1198	1,3038	3,1748
10	500	2400	642	1250	1,3038	3,1748
10	500	2500	669	1303	1,3038	3,1748
10	500	2600	696	1355	1,3038	3,1748
10	500	2700	723	1407	1,3038	3,1748
10	500	2800	749	1459	1,3038	3,1748
10	500	2900	776	1511	1,3038	3,1748
10	500	3000	803	1563	1,3038	3,1748

Declaration of performance

No. DoP-ISG-3452-r01

10	600	400	125	244	1,3142	3,5690
10	600	500	156	305	1,3142	3,5690
10	600	600	187	366	1,3142	3,5690
10	600	700	218	427	1,3142	3,5690
10	600	800	249	488	1,3142	3,5690
10	600	900	281	549	1,3142	3,5690
10	600	1000	312	610	1,3142	3,5690
10	600	1100	343	671	1,3142	3,5690
10	600	1200	374	732	1,3142	3,5690
10	600	1300	405	793	1,3142	3,5690
10	600	1400	436	854	1,3142	3,5690
10	600	1500	468	915	1,3142	3,5690
10	600	1600	499	976	1,3142	3,5690
10	600	1700	530	1037	1,3142	3,5690
10	600	1800	561	1098	1,3142	3,5690
10	600	1900	592	1159	1,3142	3,5690
10	600	2000	623	1220	1,3142	3,5690
10	600	2100	655	1281	1,3142	3,5690
10	600	2200	686	1342	1,3142	3,5690
10	600	2300	717	1403	1,3142	3,5690
10	600	2400	748	1464	1,3142	3,5690
10	600	2500	779	1525	1,3142	3,5690
10	600	2600	810	1586	1,3142	3,5690
10	600	2700	842	1647	1,3142	3,5690
10	600	2800	873	1708	1,3142	3,5690
10	600	2900	904	1769	1,3142	3,5690
10	600	3000	935	1830	1,3142	3,5690
10	700	400	142	280	1,3197	4,0026
10	700	500	178	350	1,3197	4,0026
10	700	600	214	419	1,3197	4,0026
10	700	700	249	489	1,3197	4,0026
10	700	800	285	559	1,3197	4,0026
10	700	900	321	629	1,3197	4,0026
10	700	1000	356	699	1,3197	4,0026
10	700	1100	392	769	1,3197	4,0026
10	700	1200	427	839	1,3197	4,0026
10	700	1300	463	909	1,3197	4,0026
10	700	1400	499	979	1,3197	4,0026
10	700	1500	534	1049	1,3197	4,0026
10	700	1600	570	1118	1,3197	4,0026
10	700	1700	606	1188	1,3197	4,0026
10	700	1800	641	1258	1,3197	4,0026
10	700	1900	677	1328	1,3197	4,0026
10	700	2000	712	1398	1,3197	4,0026
10	700	2100	748	1468	1,3197	4,0026
10	700	2200	784	1538	1,3197	4,0026
10	700	2300	819	1608	1,3197	4,0026
10	700	2400	855	1678	1,3197	4,0026
10	700	2500	891	1748	1,3197	4,0026
10	700	2600	926	1817	1,3197	4,0026

Declaration of performance

No. DoP-ISG-3452-r01

10	700	2700	962	1887	1,3197	4,0026
10	700	2800	997	1957	1,3197	4,0026
10	700	2900	1033	2027	1,3197	4,0026
10	700	3000	1069	2097	1,3197	4,0026
10	900	400	178	351	1,3307	4,8104
10	900	500	222	439	1,3307	4,8104
10	900	600	267	526	1,3307	4,8104
10	900	700	311	614	1,3307	4,8104
10	900	800	356	702	1,3307	4,8104
10	900	900	400	789	1,3307	4,8104
10	900	1000	444	877	1,3307	4,8104
10	900	1100	489	965	1,3307	4,8104
10	900	1200	533	1052	1,3307	4,8104
10	900	1300	578	1140	1,3307	4,8104
10	900	1400	622	1228	1,3307	4,8104
10	900	1500	667	1316	1,3307	4,8104
10	900	1600	711	1403	1,3307	4,8104
10	900	1700	755	1491	1,3307	4,8104
10	900	1800	800	1579	1,3307	4,8104
10	900	1900	844	1666	1,3307	4,8104
10	900	2000	889	1754	1,3307	4,8104
10	900	2100	933	1842	1,3307	4,8104
10	900	2200	978	1929	1,3307	4,8104
10	900	2300	1022	2017	1,3307	4,8104
10	900	2400	1067	2105	1,3307	4,8104
10	900	2500	1111	2193	1,3307	4,8104
10	900	2600	1155	2280	1,3307	4,8104
10	900	2700	1200	2368	1,3307	4,8104
10	900	2800	1244	2456	1,3307	4,8104
10	900	2900	1289	2543	1,3307	4,8104
10	900	3000	1333	2631	1,3307	4,8104

Stelrad Accord						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
11	300	400	106	207	1,3145	3,0213
11	300	500	132	259	1,3145	3,0213
11	300	600	158	310	1,3145	3,0213
11	300	700	185	362	1,3145	3,0213
11	300	800	211	414	1,3145	3,0213
11	300	900	238	465	1,3145	3,0213
11	300	1000	264	517	1,3145	3,0213
11	300	1100	291	569	1,3145	3,0213
11	300	1200	317	620	1,3145	3,0213
11	300	1300	343	672	1,3145	3,0213
11	300	1400	370	724	1,3145	3,0213
11	300	1500	396	776	1,3145	3,0213
11	300	1600	423	827	1,3145	3,0213
11	300	1700	449	879	1,3145	3,0213
11	300	1800	475	931	1,3145	3,0213

Declaration of performance

No. DoP-ISG-3452-r01

11	300	1900	502	982	1,3145	3,0213
11	300	2000	528	1034	1,3145	3,0213
11	300	2100	555	1086	1,3145	3,0213
11	300	2200	581	1137	1,3145	3,0213
11	300	2300	608	1189	1,3145	3,0213
11	300	2400	634	1241	1,3145	3,0213
11	300	2500	660	1293	1,3145	3,0213
11	300	2600	687	1344	1,3145	3,0213
11	300	2700	713	1396	1,3145	3,0213
11	300	2800	740	1448	1,3145	3,0213
11	300	2900	766	1499	1,3145	3,0213
11	300	3000	792	1551	1,3145	3,0213
11	400	400	141	275	1,3057	4,1554
11	400	500	176	344	1,3057	4,1554
11	400	600	212	412	1,3057	4,1554
11	400	700	247	481	1,3057	4,1554
11	400	800	282	550	1,3057	4,1554
11	400	900	317	618	1,3057	4,1554
11	400	1000	353	687	1,3057	4,1554
11	400	1100	388	756	1,3057	4,1554
11	400	1200	423	824	1,3057	4,1554
11	400	1300	458	893	1,3057	4,1554
11	400	1400	494	962	1,3057	4,1554
11	400	1500	529	1031	1,3057	4,1554
11	400	1600	564	1099	1,3057	4,1554
11	400	1700	599	1168	1,3057	4,1554
11	400	1800	635	1237	1,3057	4,1554
11	400	1900	670	1305	1,3057	4,1554
11	400	2000	705	1374	1,3057	4,1554
11	400	2100	740	1443	1,3057	4,1554
11	400	2200	776	1511	1,3057	4,1554
11	400	2300	811	1580	1,3057	4,1554
11	400	2400	846	1649	1,3057	4,1554
11	400	2500	882	1718	1,3057	4,1554
11	400	2600	917	1786	1,3057	4,1554
11	400	2700	952	1855	1,3057	4,1554
11	400	2800	987	1924	1,3057	4,1554
11	400	2900	1023	1992	1,3057	4,1554
11	400	3000	1058	2061	1,3057	4,1554

11	500	400	175	339	1,2968	5,3109
11	500	500	219	424	1,2968	5,3109
11	500	600	262	509	1,2968	5,3109
11	500	700	306	594	1,2968	5,3109
11	500	800	350	678	1,2968	5,3109
11	500	900	394	763	1,2968	5,3109
11	500	1000	437	848	1,2968	5,3109
11	500	1100	481	933	1,2968	5,3109
11	500	1200	525	1018	1,2968	5,3109
11	500	1300	568	1102	1,2968	5,3109
11	500	1400	612	1187	1,2968	5,3109

Declaration of performance

No. DoP-ISG-3452-r01

11	500	1500	656	1272	1,2968	5,3109
11	500	1600	700	1357	1,2968	5,3109
11	500	1700	743	1442	1,2968	5,3109
11	500	1800	787	1526	1,2968	5,3109
11	500	1900	831	1611	1,2968	5,3109
11	500	2000	874	1696	1,2968	5,3109
11	500	2100	918	1781	1,2968	5,3109
11	500	2200	962	1866	1,2968	5,3109
11	500	2300	1006	1950	1,2968	5,3109
11	500	2400	1049	2035	1,2968	5,3109
11	500	2500	1093	2120	1,2968	5,3109
11	500	2600	1137	2205	1,2968	5,3109
11	500	2700	1181	2290	1,2968	5,3109
11	500	2800	1224	2374	1,2968	5,3109
11	500	2900	1268	2459	1,2968	5,3109
11	500	3000	1312	2544	1,2968	5,3109
11	600	400	207	400	1,2880	6,4823
11	600	500	259	500	1,2880	6,4823
11	600	600	311	600	1,2880	6,4823
11	600	700	363	700	1,2880	6,4823
11	600	800	414	800	1,2880	6,4823
11	600	900	466	900	1,2880	6,4823
11	600	1000	518	1000	1,2880	6,4823
11	600	1100	570	1100	1,288	6,4823
11	600	1200	621	1200	1,288	6,4823
11	600	1300	673	1300	1,288	6,4823
11	600	1400	725	1400	1,288	6,4823
11	600	1500	777	1500	1,288	6,4823
11	600	1600	829	1600	1,288	6,4823
11	600	1700	880	1700	1,288	6,4823
11	600	1800	932	1800	1,288	6,4823
11	600	1900	984	1900	1,288	6,4823
11	600	2000	1036	2000	1,288	6,4823
11	600	2100	1088	2100	1,288	6,4823
11	600	2200	1139	2200	1,288	6,4823
11	600	2300	1191	2300	1,288	6,4823
11	600	2400	1243	2400	1,288	6,4823
11	600	2500	1295	2500	1,288	6,4823
11	600	2600	1347	2600	1,288	6,4823
11	600	2700	1398	2700	1,288	6,4823
11	600	2800	1450	2800	1,288	6,4823
11	600	2900	1502	2900	1,288	6,4823
11	600	3000	1554	3000	1,288	6,4823
11	700	400	236	457	1,2889	7,3767
11	700	500	296	571	1,2889	7,3767
11	700	600	355	685	1,2889	7,3767
11	700	700	414	799	1,2889	7,3767
11	700	800	473	914	1,2889	7,3767
11	700	900	532	1028	1,2889	7,3767
11	700	1000	591	1142	1,2889	7,3767
11	700	1100	650	1256	1,2889	7,3767
11	700	1200	709	1370	1,2889	7,3767
11	700	1300	769	1485	1,2889	7,3767
11	700	1400	828	1599	1,2889	7,3767
11	700	1500	887	1713	1,2889	7,3767
11	700	1600	946	1827	1,2889	7,3767
11	700	1700	1005	1941	1,2889	7,3767

Declaration of performance

No. DoP-ISG-3452-r01

11	700	1800	1064	2056	1,2889	7,3767
11	700	1900	1123	2170	1,2889	7,3767
11	700	2000	1182	2284	1,2889	7,3767
11	700	2100	1241	2398	1,2889	7,3767
11	700	2200	1301	2512	1,2889	7,3767
11	700	2300	1360	2627	1,2889	7,3767
11	700	2400	1419	2741	1,2889	7,3767
11	700	2500	1478	2855	1,2889	7,3767
11	700	2600	1537	2969	1,2889	7,3767
11	700	2700	1596	3083	1,2889	7,3767
11	700	2800	1655	3198	1,2889	7,3767
11	700	2900	1714	3312	1,2889	7,3767
11	700	3000	1774	3426	1,2889	7,3767
11	900	400	289	559	1,2907	8,9606
11	900	500	361	699	1,2907	8,9606
11	900	600	434	838	1,2907	8,9606
11	900	700	506	978	1,2907	8,9606
11	900	800	578	1118	1,2907	8,9606
11	900	900	650	1257	1,2907	8,9606
11	900	1000	723	1397	1,2907	8,9606
11	900	1100	795	1537	1,2907	8,9606
11	900	1200	867	1676	1,2907	8,9606
11	900	1300	939	1816	1,2907	8,9606
11	900	1400	1012	1956	1,2907	8,9606
11	900	1500	1084	2096	1,2907	8,9606
11	900	1600	1156	2235	1,2907	8,9606
11	900	1700	1228	2375	1,2907	8,9606
11	900	1800	1301	2515	1,2907	8,9606
11	900	1900	1373	2654	1,2907	8,9606
11	900	2000	1445	2794	1,2907	8,9606
11	900	2100	1517	2934	1,2907	8,9606
11	900	2200	1590	3073	1,2907	8,9606
11	900	2300	1662	3213	1,2907	8,9606
11	900	2400	1734	3353	1,2907	8,9606
11	900	2500	1806	3493	1,2907	8,9606
11	900	2600	1879	3632	1,2907	8,9606
11	900	2700	1951	3772	1,2907	8,9606
11	900	2800	2023	3912	1,2907	8,9606
11	900	2900	2095	4051	1,2907	8,9606
11	900	3000	2168	4191	1,2907	8,9606

4 connections Hygiene						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
20	300	400	115	228	1,3352	3,0773
20	300	500	144	286	1,3352	3,0773
20	300	600	173	343	1,3352	3,0773
20	300	700	202	400	1,3352	3,0773
20	300	800	231	457	1,3352	3,0773
20	300	900	260	514	1,3352	3,0773
20	300	1000	289	571	1,3352	3,0773
20	300	1100	318	628	1,3352	3,0773

Declaration of performance

No. DoP-ISG-3452-r01

20	300	1200	346	685	1,3352	3,0773
20	300	1300	375	742	1,3352	3,0773
20	300	1400	404	799	1,3352	3,0773
20	300	1500	433	857	1,3352	3,0773
20	300	1600	462	914	1,3352	3,0773
20	300	1700	491	971	1,3352	3,0773
20	300	1800	520	1028	1,3352	3,0773
20	300	1900	549	1085	1,3352	3,0773
20	300	2000	577	1142	1,3352	3,0773
20	300	2100	606	1199	1,3352	3,0773
20	300	2200	635	1256	1,3352	3,0773
20	300	2300	664	1313	1,3352	3,0773
20	300	2400	693	1370	1,3352	3,0773
20	300	2500	722	1428	1,3352	3,0773
20	300	2600	751	1485	1,3352	3,0773
20	300	2700	779	1542	1,3352	3,0773
20	300	2800	808	1599	1,3352	3,0773
20	300	2900	837	1656	1,3352	3,0773
20	300	3000	866	1713	1,3352	3,0773
20	400	400	148	292	1,329	4,0308
20	400	500	185	365	1,329	4,0308
20	400	600	222	438	1,329	4,0308
20	400	700	259	511	1,329	4,0308
20	400	800	296	584	1,329	4,0308
20	400	900	333	657	1,329	4,0308
20	400	1000	370	730	1,3290	4,0308
20	400	1100	407	803	1,329	4,0308
20	400	1200	444	876	1,329	4,0308
20	400	1300	481	949	1,329	4,0308
20	400	1400	518	1022	1,329	4,0308
20	400	1500	555	1095	1,329	4,0308
20	400	1600	592	1168	1,329	4,0308
20	400	1700	629	1241	1,329	4,0308
20	400	1800	666	1314	1,329	4,0308
20	400	1900	703	1387	1,329	4,0308
20	400	2000	740	1460	1,329	4,0308
20	400	2100	778	1533	1,329	4,0308
20	400	2200	815	1606	1,329	4,0308
20	400	2300	852	1679	1,329	4,0308
20	400	2400	889	1752	1,329	4,0308
20	400	2500	926	1825	1,329	4,0308
20	400	2600	963	1898	1,329	4,0308
20	400	2700	1000	1971	1,329	4,0308
20	400	2800	1037	2044	1,329	4,0308
20	400	2900	1074	2117	1,329	4,0308
20	400	3000	1111	2190	1,329	4,0308
20	500	400	180	353	1,3228	4,9953
20	500	500	225	442	1,3228	4,9953
20	500	600	270	530	1,3228	4,9953
20	500	700	314	618	1,3228	4,9953
20	500	800	359	706	1,3228	4,9953

Declaration of performance

No. DoP-ISG-3452-r01

20	500	900	404	795	1,3228	4,9953
20	500	1000	449	883	1,3228	4,9953
20	500	1100	494	971	1,3228	4,9953
20	500	1200	539	1060	1,3228	4,9953
20	500	1300	584	1148	1,3228	4,9953
20	500	1400	629	1236	1,3228	4,9953
20	500	1500	674	1325	1,3228	4,9953
20	500	1600	719	1413	1,3228	4,9953
20	500	1700	764	1501	1,3228	4,9953
20	500	1800	809	1589	1,3228	4,9953
20	500	1900	854	1678	1,3228	4,9953
20	500	2000	899	1766	1,3228	4,9953
20	500	2100	943	1854	1,3228	4,9953
20	500	2200	988	1943	1,3228	4,9953
20	500	2300	1033	2031	1,3228	4,9953
20	500	2400	1078	2119	1,3228	4,9953
20	500	2500	1123	2208	1,3228	4,9953
20	500	2600	1168	2296	1,3228	4,9953
20	500	2700	1213	2384	1,3228	4,9953
20	500	2800	1258	2472	1,3228	4,9953
20	500	2900	1303	2561	1,3228	4,9953
20	500	3000	1348	2649	1,3228	4,9953
20	600	400	210	412	1,3166	5,9758
20	600	500	263	516	1,3166	5,9758
20	600	600	316	619	1,3166	5,9758
20	600	700	368	722	1,3166	5,9758
20	600	800	421	825	1,3166	5,9758
20	600	900	474	928	1,3166	5,9758
20	600	1000	526	1031	1,3166	5,9758
20	600	1100	579	1134	1,3166	5,9758
20	600	1200	631	1237	1,3166	5,9758
20	600	1300	684	1340	1,3166	5,9758
20	600	1400	737	1443	1,3166	5,9758
20	600	1500	789	1547	1,3166	5,9758
20	600	1600	842	1650	1,3166	5,9758
20	600	1700	895	1753	1,3166	5,9758
20	600	1800	947	1856	1,3166	5,9758
20	600	1900	1000	1959	1,3166	5,9758
20	600	2000	1052	2062	1,3166	5,9758
20	600	2100	1105	2165	1,3166	5,9758
20	600	2200	1158	2268	1,3166	5,9758
20	600	2300	1210	2371	1,3166	5,9758
20	600	2400	1263	2474	1,3166	5,9758
20	600	2500	1316	2578	1,3166	5,9758
20	600	2600	1368	2681	1,3166	5,9758
20	600	2700	1421	2784	1,3166	5,9758
20	600	2800	1473	2887	1,3166	5,9758
20	600	2900	1526	2990	1,3166	5,9758
20	600	3000	1579	3093	1,3166	5,9758
20	700	400	239	470	1,3201	6,7121
20	700	500	299	587	1,3201	6,7121
20	700	600	359	704	1,3201	6,7121

Declaration of performance

No. DoP-ISG-3452-r01

20	700	700	419	822	1,3201	6,7121
20	700	800	479	939	1,3201	6,7121
20	700	900	538	1057	1,3201	6,7121
20	700	1000	598	1174	1,3201	6,7121
20	700	1100	658	1291	1,3201	6,7121
20	700	1200	718	1409	1,3201	6,7121
20	700	1300	778	1526	1,3201	6,7121
20	700	1400	837	1644	1,3201	6,7121
20	700	1500	897	1761	1,3201	6,7121
20	700	1600	957	1878	1,3201	6,7121
20	700	1700	1017	1996	1,3201	6,7121
20	700	1800	1077	2113	1,3201	6,7121
20	700	1900	1136	2231	1,3201	6,7121
20	700	2000	1196	2348	1,3201	6,7121
20	700	2100	1256	2465	1,3201	6,7121
20	700	2200	1316	2583	1,3201	6,7121
20	700	2300	1376	2700	1,3201	6,7121
20	700	2400	1436	2818	1,3201	6,7121
20	700	2500	1495	2935	1,3201	6,7121
20	700	2600	1555	3052	1,3201	6,7121
20	700	2700	1615	3170	1,3201	6,7121
20	700	2800	1675	3287	1,3201	6,7121
20	700	2900	1735	3405	1,3201	6,7121
20	700	3000	1794	3522	1,3201	6,7121
20	900	400	294	580	1,3270	8,0637
20	900	500	368	725	1,3270	8,0637
20	900	600	441	869	1,3270	8,0637
20	900	700	515	1014	1,3270	8,0637
20	900	800	589	1159	1,3270	8,0637
20	900	900	662	1304	1,3270	8,0637
20	900	1000	736	1449	1,3270	8,0637
20	900	1100	809	1594	1,3270	8,0637
20	900	1200	883	1739	1,3270	8,0637
20	900	1300	956	1884	1,3270	8,0637
20	900	1400	1030	2029	1,3270	8,0637
20	900	1500	1103	2174	1,3270	8,0637
20	900	1600	1177	2318	1,3270	8,0637
20	900	1700	1251	2463	1,3270	8,0637
20	900	1800	1324	2608	1,3270	8,0637
20	900	1900	1398	2753	1,3270	8,0637
20	900	2000	1471	2898	1,3270	8,0637
20	900	2100	1545	3043	1,3270	8,0637
20	900	2200	1618	3188	1,3270	8,0637
20	900	2300	1692	3333	1,3270	8,0637
20	900	2400	1766	3478	1,3270	8,0637
20	900	2500	1839	3623	1,3270	8,0637
20	900	2600	1913	3767	1,3270	8,0637
20	900	2700	1986	3912	1,3270	8,0637
20	900	2800	2060	4057	1,3270	8,0637
20	900	2900	2133	4202	1,3270	8,0637
20	900	3000	2207	4347	1,3270	8,0637

Declaration of performance

No. DoP-ISG-3452-r01

Stelrad Accord						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
21	300	400	157	310	1,329	4,2848
21	300	500	197	388	1,329	4,2848
21	300	600	236	466	1,329	4,2848
21	300	700	276	543	1,329	4,2848
21	300	800	315	621	1,329	4,2848
21	300	900	354	698	1,329	4,2848
21	300	1000	394	776	1,3290	4,2848
21	300	1100	433	854	1,329	4,2848
21	300	1200	472	931	1,329	4,2848
21	300	1300	512	1009	1,329	4,2848
21	300	1400	551	1086	1,329	4,2848
21	300	1500	590	1164	1,329	4,2848
21	300	1600	630	1242	1,329	4,2848
21	300	1700	669	1319	1,329	4,2848
21	300	1800	708	1397	1,329	4,2848
21	300	1900	748	1474	1,329	4,2848
21	300	2000	787	1552	1,329	4,2848
21	300	2100	827	1630	1,329	4,2848
21	300	2200	866	1707	1,329	4,2848
21	300	2300	905	1785	1,329	4,2848
21	300	2400	945	1862	1,329	4,2848
21	300	2500	984	1940	1,329	4,2848
21	300	2600	1023	2018	1,329	4,2848
21	300	2700	1063	2095	1,329	4,2848
21	300	2800	1102	2173	1,329	4,2848
21	300	2900	1141	2250	1,329	4,2848
21	300	3000	1181	2328	1,329	4,2848
21	400	400	203	400	1,3284	5,5346
21	400	500	254	500	1,3284	5,5346
21	400	600	304	600	1,3284	5,5346
21	400	700	355	700	1,3284	5,5346
21	400	800	406	800	1,3284	5,5346
21	400	900	457	900	1,3284	5,5346
21	400	1000	507	1000	1,3284	5,5346
21	400	1100	558	1100	1,3284	5,5346
21	400	1200	609	1200	1,3284	5,5346
21	400	1300	660	1300	1,3284	5,5346
21	400	1400	710	1400	1,3284	5,5346
21	400	1500	761	1500	1,3284	5,5346
21	400	1600	812	1600	1,3284	5,5346
21	400	1700	862	1700	1,3284	5,5346
21	400	1800	913	1800	1,3284	5,5346
21	400	1900	964	1900	1,3284	5,5346
21	400	2000	1015	2000	1,3284	5,5346
21	400	2100	1065	2100	1,3284	5,5346
21	400	2200	1116	2200	1,3284	5,5346

Declaration of performance

No. DoP-ISG-3452-r01

21	400	2300	1167	2300	1,3284	5,5346
21	400	2400	1218	2400	1,3284	5,5346
21	400	2500	1268	2500	1,3284	5,5346
21	400	2600	1319	2600	1,3284	5,5346
21	400	2700	1370	2700	1,3284	5,5346
21	400	2800	1421	2800	1,3284	5,5346
21	400	2900	1471	2900	1,3284	5,5346
21	400	3000	1522	3000	1,3284	5,5346
21	500	400	246	484	1,3278	6,7126
21	500	500	307	605	1,3278	6,7126
21	500	600	368	726	1,3278	6,7126
21	500	700	430	847	1,3278	6,7126
21	500	800	491	968	1,3278	6,7126
21	500	900	553	1089	1,3278	6,7126
21	500	1000	614	1210	1,3278	6,7126
21	500	1100	675	1331	1,3278	6,7126
21	500	1200	737	1452	1,3278	6,7126
21	500	1300	798	1573	1,3278	6,7126
21	500	1400	860	1694	1,3278	6,7126
21	500	1500	921	1815	1,3278	6,7126
21	500	1600	983	1936	1,3278	6,7126
21	500	1700	1044	2057	1,3278	6,7126
21	500	1800	1105	2178	1,3278	6,7126
21	500	1900	1167	2299	1,3278	6,7126
21	500	2000	1228	2420	1,3278	6,7126
21	500	2100	1290	2541	1,3278	6,7126
21	500	2200	1351	2662	1,3278	6,7126
21	500	2300	1412	2783	1,3278	6,7126
21	500	2400	1474	2904	1,3278	6,7126
21	500	2500	1535	3025	1,3278	6,7126
21	500	2600	1597	3146	1,3278	6,7126
21	500	2700	1658	3267	1,3278	6,7126
21	500	2800	1719	3388	1,3278	6,7126
21	500	2900	1781	3509	1,3278	6,7126
21	500	3000	1842	3630	1,3278	6,7126
21	600	400	286	564	1,3272	7,8350
21	600	500	358	705	1,3272	7,8350
21	600	600	429	845	1,3272	7,8350
21	600	700	501	986	1,3272	7,8350
21	600	800	572	1127	1,3272	7,8350
21	600	900	644	1268	1,3272	7,8350
21	600	1000	715	1409	1,3272	7,8350
21	600	1100	787	1550	1,3272	7,8350
21	600	1200	858	1691	1,3272	7,8350
21	600	1300	930	1832	1,3272	7,8350
21	600	1400	1001	1973	1,3272	7,8350
21	600	1500	1073	2114	1,3272	7,8350
21	600	1600	1144	2254	1,3272	7,8350
21	600	1700	1216	2395	1,3272	7,8350
21	600	1800	1287	2536	1,3272	7,8350
21	600	1900	1359	2677	1,3272	7,8350

Declaration of performance

No. DoP-ISG-3452-r01

21	600	2000	1431	2818	1,3272	7,8350
21	600	2100	1502	2959	1,3272	7,8350
21	600	2200	1574	3100	1,3272	7,8350
21	600	2300	1645	3241	1,3272	7,8350
21	600	2400	1717	3382	1,3272	7,8350
21	600	2500	1788	3523	1,3272	7,8350
21	600	2600	1860	3663	1,3272	7,8350
21	600	2700	1931	3804	1,3272	7,8350
21	600	2800	2003	3945	1,3272	7,8350
21	600	2900	2074	4086	1,3272	7,8350
21	600	3000	2146	4227	1,3272	7,8350
21	700	400	323	639	1,3367	8,5564
21	700	500	403	799	1,3367	8,5564
21	700	600	484	958	1,3367	8,5564
21	700	700	565	1118	1,3367	8,5564
21	700	800	645	1278	1,3367	8,5564
21	700	900	726	1437	1,3367	8,5564
21	700	1000	807	1597	1,3367	8,5564
21	700	1100	887	1757	1,3367	8,5564
21	700	1200	968	1916	1,3367	8,5564
21	700	1300	1049	2076	1,3367	8,5564
21	700	1400	1130	2236	1,3367	8,5564
21	700	1500	1210	2396	1,3367	8,5564
21	700	1600	1291	2555	1,3367	8,5564
21	700	1700	1372	2715	1,3367	8,5564
21	700	1800	1452	2875	1,3367	8,5564
21	700	1900	1533	3034	1,3367	8,5564
21	700	2000	1614	3194	1,3367	8,5564
21	700	2100	1694	3354	1,3367	8,5564
21	700	2200	1775	3513	1,3367	8,5564
21	700	2300	1856	3673	1,3367	8,5564
21	700	2400	1936	3833	1,3367	8,5564
21	700	2500	2017	3993	1,3367	8,5564
21	700	2600	2098	4152	1,3367	8,5564
21	700	2700	2178	4312	1,3367	8,5564
21	700	2800	2259	4472	1,3367	8,5564
21	700	2900	2340	4631	1,3367	8,5564
21	700	3000	2420	4791	1,3367	8,5564
21	900	400	388	776	1,3557	9,6545
21	900	500	486	971	1,3557	9,6545
21	900	600	583	1165	1,3557	9,6545
21	900	700	680	1359	1,3557	9,6545
21	900	800	777	1553	1,3557	9,6545
21	900	900	874	1747	1,3557	9,6545
21	900	1000	971	1941	1,3557	9,6545
21	900	1100	1068	2135	1,3557	9,6545
21	900	1200	1165	2329	1,3557	9,6545
21	900	1300	1262	2523	1,3557	9,6545
21	900	1400	1360	2717	1,3557	9,6545
21	900	1500	1457	2912	1,3557	9,6545
21	900	1600	1554	3106	1,3557	9,6545

Declaration of performance

No. DoP-ISG-3452-r01

21	900	1700	1651	3300	1,3557	9,6545
21	900	1800	1748	3494	1,3557	9,6545
21	900	1900	1845	3688	1,3557	9,6545
21	900	2000	1942	3882	1,3557	9,6545
21	900	2100	2039	4076	1,3557	9,6545
21	900	2200	2136	4270	1,3557	9,6545
21	900	2300	2234	4464	1,3557	9,6545
21	900	2400	2331	4658	1,3557	9,6545
21	900	2500	2428	4853	1,3557	9,6545
21	900	2600	2525	5047	1,3557	9,6545
21	900	2700	2622	5241	1,3557	9,6545
21	900	2800	2719	5435	1,3557	9,6545
21	900	2900	2816	5629	1,3557	9,6545
21	900	3000	2913	5823	1,3557	9,6545

Stelrad Accord						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
22	300	400	205	405	1,3329	5,5033
22	300	500	256	506	1,3329	5,5033
22	300	600	307	607	1,3329	5,5033
22	300	700	359	708	1,3329	5,5033
22	300	800	410	810	1,3329	5,5033
22	300	900	461	911	1,3329	5,5033
22	300	1000	512	1012	1,3329	5,5033
22	300	1100	563	1113	1,3329	5,5033
22	300	1200	615	1214	1,3329	5,5033
22	300	1300	666	1316	1,3329	5,5033
22	300	1400	717	1417	1,3329	5,5033
22	300	1500	768	1518	1,3329	5,5033
22	300	1600	820	1619	1,3329	5,5033
22	300	1700	871	1720	1,3329	5,5033
22	300	1800	922	1822	1,3329	5,5033
22	300	1900	973	1923	1,3329	5,5033
22	300	2000	1024	2024	1,3329	5,5033
22	300	2100	1076	2125	1,3329	5,5033
22	300	2200	1127	2226	1,3329	5,5033
22	300	2300	1178	2328	1,3329	5,5033
22	300	2400	1229	2429	1,3329	5,5033
22	300	2500	1281	2530	1,3329	5,5033
22	300	2600	1332	2631	1,3329	5,5033
22	300	2700	1383	2732	1,3329	5,5033
22	300	2800	1434	2834	1,3329	5,5033
22	300	2900	1486	2935	1,3329	5,5033
22	300	3000	1537	3036	1,3329	5,5033
22	400	400	259	512	1,3321	6,988
22	400	500	324	641	1,3321	6,988
22	400	600	389	769	1,3321	6,988

Declaration of performance

No. DoP-ISG-3452-r01

22	400	700	454	897	1,3321	6,988
22	400	800	519	1025	1,3321	6,988
22	400	900	584	1153	1,3321	6,988
22	400	1000	649	1281	1,3321	6,9880
22	400	1100	714	1409	1,3321	6,988
22	400	1200	778	1537	1,3321	6,988
22	400	1300	843	1665	1,3321	6,988
22	400	1400	908	1793	1,3321	6,988
22	400	1500	973	1922	1,3321	6,988
22	400	1600	1038	2050	1,3321	6,988
22	400	1700	1103	2178	1,3321	6,988
22	400	1800	1168	2306	1,3321	6,988
22	400	1900	1232	2434	1,3321	6,988
22	400	2000	1297	2562	1,3321	6,988
22	400	2100	1362	2690	1,3321	6,988
22	400	2200	1427	2818	1,3321	6,988
22	400	2300	1492	2946	1,3321	6,988
22	400	2400	1557	3074	1,3321	6,988
22	400	2500	1622	3203	1,3321	6,988
22	400	2600	1687	3331	1,3321	6,988
22	400	2700	1751	3459	1,3321	6,988
22	400	2800	1816	3587	1,3321	6,988
22	400	2900	1881	3715	1,3321	6,988
22	400	3000	1946	3843	1,3321	6,988
22	500	400	311	614	1,3314	8,3965
22	500	500	389	768	1,3314	8,3965
22	500	600	467	921	1,3314	8,3965
22	500	700	544	1075	1,3314	8,3965
22	500	800	622	1228	1,3314	8,3965
22	500	900	700	1382	1,3314	8,3965
22	500	1000	778	1535	1,3314	8,3965
22	500	1100	855	1689	1,3314	8,3965
22	500	1200	933	1842	1,3314	8,3965
22	500	1300	1011	1996	1,3314	8,3965
22	500	1400	1089	2149	1,3314	8,3965
22	500	1500	1166	2303	1,3314	8,3965
22	500	1600	1244	2456	1,3314	8,3965
22	500	1700	1322	2610	1,3314	8,3965
22	500	1800	1400	2763	1,3314	8,3965
22	500	1900	1477	2917	1,3314	8,3965
22	500	2000	1555	3070	1,3314	8,3965
22	500	2100	1633	3224	1,3314	8,3965
22	500	2200	1711	3377	1,3314	8,3965
22	500	2300	1788	3531	1,3314	8,3965
22	500	2400	1866	3684	1,3314	8,3965
22	500	2500	1944	3838	1,3314	8,3965
22	500	2600	2022	3991	1,3314	8,3965
22	500	2700	2099	4145	1,3314	8,3965
22	500	2800	2177	4298	1,3314	8,3965
22	500	2900	2255	4452	1,3314	8,3965
22	500	3000	2333	4605	1,3314	8,3965

Declaration of performance

No. DoP-ISG-3452-r01

22	600	400	360	711	1,3306	9,7562
22	600	500	451	889	1,3306	9,7562
22	600	600	541	1067	1,3306	9,7562
22	600	700	631	1245	1,3306	9,7562
22	600	800	721	1422	1,3306	9,7562
22	600	900	811	1600	1,3306	9,7562
22	600	1000	901	1778	1,3306	9,7562
22	600	1100	991	1956	1,3306	9,7562
22	600	1200	1081	2134	1,3306	9,7562
22	600	1300	1171	2311	1,3306	9,7562
22	600	1400	1261	2489	1,3306	9,7562
22	600	1500	1352	2667	1,3306	9,7562
22	600	1600	1442	2845	1,3306	9,7562
22	600	1700	1532	3023	1,3306	9,7562
22	600	1800	1622	3200	1,3306	9,7562
22	600	1900	1712	3378	1,3306	9,7562
22	600	2000	1802	3556	1,3306	9,7562
22	600	2100	1892	3734	1,3306	9,7562
22	600	2200	1982	3912	1,3306	9,7562
22	600	2300	2072	4089	1,3306	9,7562
22	600	2400	2162	4267	1,3306	9,7562
22	600	2500	2253	4445	1,3306	9,7562
22	600	2600	2343	4623	1,3306	9,7562
22	600	2700	2433	4801	1,3306	9,7562
22	600	2800	2523	4978	1,3306	9,7562
22	600	2900	2613	5156	1,3306	9,7562
22	600	3000	2703	5334	1,3306	9,7562
22	700	400	406	804	1,3369	10,7661
22	700	500	508	1006	1,3369	10,7661
22	700	600	610	1207	1,3369	10,7661
22	700	700	711	1408	1,3369	10,7661
22	700	800	813	1609	1,3369	10,7661
22	700	900	914	1810	1,3369	10,7661
22	700	1000	1016	2011	1,3369	10,7661
22	700	1100	1117	2212	1,3369	10,7661
22	700	1200	1219	2413	1,3369	10,7661
22	700	1300	1321	2614	1,3369	10,7661
22	700	1400	1422	2815	1,3369	10,7661
22	700	1500	1524	3017	1,3369	10,7661
22	700	1600	1625	3218	1,3369	10,7661
22	700	1700	1727	3419	1,3369	10,7661
22	700	1800	1829	3620	1,3369	10,7661
22	700	1900	1930	3821	1,3369	10,7661
22	700	2000	2032	4022	1,3369	10,7661
22	700	2100	2133	4223	1,3369	10,7661
22	700	2200	2235	4424	1,3369	10,7661
22	700	2300	2336	4625	1,3369	10,7661
22	700	2400	2438	4826	1,3369	10,7661
22	700	2500	2540	5028	1,3369	10,7661
22	700	2600	2641	5229	1,3369	10,7661
22	700	2700	2743	5430	1,3369	10,7661

Declaration of performance

No. DoP-ISG-3452-r01

22	700	2800	2844	5631	1,3369	10,7661
22	700	2900	2946	5832	1,3369	10,7661
22	700	3000	3048	6033	1,3369	10,7661
22	900	400	492	981	1,3494	12,5057
22	900	500	616	1227	1,3494	12,5057
22	900	600	739	1472	1,3494	12,5057
22	900	700	862	1717	1,3494	12,5057
22	900	800	985	1962	1,3494	12,5057
22	900	900	1108	2208	1,3494	12,5057
22	900	1000	1231	2453	1,3494	12,5057
22	900	1100	1354	2698	1,3494	12,5057
22	900	1200	1477	2944	1,3494	12,5057
22	900	1300	1601	3189	1,3494	12,5057
22	900	1400	1724	3434	1,3494	12,5057
22	900	1500	1847	3680	1,3494	12,5057
22	900	1600	1970	3925	1,3494	12,5057
22	900	1700	2093	4170	1,3494	12,5057
22	900	1800	2216	4415	1,3494	12,5057
22	900	1900	2339	4661	1,3494	12,5057
22	900	2000	2462	4906	1,3494	12,5057
22	900	2100	2586	5151	1,3494	12,5057
22	900	2200	2709	5397	1,3494	12,5057
22	900	2300	2832	5642	1,3494	12,5057
22	900	2400	2955	5887	1,3494	12,5057
22	900	2500	3078	6133	1,3494	12,5057
22	900	2600	3201	6378	1,3494	12,5057
22	900	2700	3324	6623	1,3494	12,5057
22	900	2800	3447	6868	1,3494	12,5057
22	900	2900	3571	7114	1,3494	12,5057
22	900	3000	3694	7359	1,3494	12,5057

4 connections Hygiene						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
30	300	400	177	344	1,2994	5,3254
30	300	500	221	430	1,2994	5,3254
30	300	600	265	515	1,2994	5,3254
30	300	700	310	601	1,2994	5,3254
30	300	800	354	687	1,2994	5,3254
30	300	900	398	773	1,2994	5,3254
30	300	1000	442	859	1,2994	5,3254
30	300	1100	487	945	1,2994	5,3254
30	300	1200	531	1031	1,2994	5,3254
30	300	1300	575	1117	1,2994	5,3254
30	300	1400	619	1203	1,2994	5,3254
30	300	1500	663	1289	1,2994	5,3254
30	300	1600	708	1374	1,2994	5,3254
30	300	1700	752	1460	1,2994	5,3254

Declaration of performance

No. DoP-ISG-3452-r01

30	300	1800	796	1546	1,2994	5,3254
30	300	1900	840	1632	1,2994	5,3254
30	300	2000	885	1718	1,2994	5,3254
30	300	2100	929	1804	1,2994	5,3254
30	300	2200	973	1890	1,2994	5,3254
30	300	2300	1017	1976	1,2994	5,3254
30	300	2400	1062	2062	1,2994	5,3254
30	300	2500	1106	2148	1,2994	5,3254
30	300	2600	1150	2233	1,2994	5,3254
30	300	2700	1194	2319	1,2994	5,3254
30	300	2800	1238	2405	1,2994	5,3254
30	300	2900	1283	2491	1,2994	5,3254
30	300	3000	1327	2577	1,2994	5,3254
30	400	400	221	429	1,3027	6,5668
30	400	500	276	537	1,3027	6,5668
30	400	600	331	644	1,3027	6,5668
30	400	700	386	751	1,3027	6,5668
30	400	800	441	858	1,3027	6,5668
30	400	900	496	966	1,3027	6,5668
30	400	1000	552	1073	1,3027	6,5668
30	400	1100	607	1180	1,3027	6,5668
30	400	1200	662	1288	1,3027	6,5668
30	400	1300	717	1395	1,3027	6,5668
30	400	1400	772	1502	1,3027	6,5668
30	400	1500	827	1610	1,3027	6,5668
30	400	1600	883	1717	1,3027	6,5668
30	400	1700	938	1824	1,3027	6,5668
30	400	1800	993	1931	1,3027	6,5668
30	400	1900	1048	2039	1,3027	6,5668
30	400	2000	1103	2146	1,3027	6,5668
30	400	2100	1158	2253	1,3027	6,5668
30	400	2200	1213	2361	1,3027	6,5668
30	400	2300	1269	2468	1,3027	6,5668
30	400	2400	1324	2575	1,3027	6,5668
30	400	2500	1379	2683	1,3027	6,5668
30	400	2600	1434	2790	1,3027	6,5668
30	400	2700	1489	2897	1,3027	6,5668
30	400	2800	1544	3004	1,3027	6,5668
30	400	2900	1600	3112	1,3027	6,5668
30	400	3000	1655	3219	1,3027	6,5668
30	500	400	262	511	1,3059	7,7180
30	500	500	328	639	1,3059	7,7180
30	500	600	393	766	1,3059	7,7180
30	500	700	459	894	1,3059	7,7180
30	500	800	524	1022	1,3059	7,7180
30	500	900	590	1149	1,3059	7,7180
30	500	1000	655	1277	1,3059	7,7180
30	500	1100	721	1405	1,3059	7,7180

Declaration of performance

No. DoP-ISG-3452-r01

30	500	1200	786	1532	1,3059	7,7180
30	500	1300	852	1660	1,3059	7,7180
30	500	1400	918	1788	1,3059	7,7180
30	500	1500	983	1916	1,3059	7,7180
30	500	1600	1049	2043	1,3059	7,7180
30	500	1700	1114	2171	1,3059	7,7180
30	500	1800	1180	2299	1,3059	7,7180
30	500	1900	1245	2426	1,3059	7,7180
30	500	2000	1311	2554	1,3059	7,7180
30	500	2100	1376	2682	1,3059	7,7180
30	500	2200	1442	2809	1,3059	7,7180
30	500	2300	1507	2937	1,3059	7,7180
30	500	2400	1573	3065	1,3059	7,7180
30	500	2500	1638	3193	1,3059	7,7180
30	500	2600	1704	3320	1,3059	7,7180
30	500	2700	1769	3448	1,3059	7,7180
30	500	2800	1835	3576	1,3059	7,7180
30	500	2900	1901	3703	1,3059	7,7180
30	500	3000	1966	3831	1,3059	7,7180
30	600	400	302	590	1,3092	8,7944
30	600	500	378	737	1,3092	8,7944
30	600	600	453	884	1,3092	8,7944
30	600	700	529	1032	1,3092	8,7944
30	600	800	604	1179	1,3092	8,7944
30	600	900	680	1327	1,3092	8,7944
30	600	1000	755	1474	1,3092	8,7944
30	600	1100	831	1621	1,3092	8,7944
30	600	1200	906	1769	1,3092	8,7944
30	600	1300	982	1916	1,3092	8,7944
30	600	1400	1057	2064	1,3092	8,7944
30	600	1500	1133	2211	1,3092	8,7944
30	600	1600	1208	2358	1,3092	8,7944
30	600	1700	1284	2506	1,3092	8,7944
30	600	1800	1359	2653	1,3092	8,7944
30	600	1900	1435	2801	1,3092	8,7944
30	600	2000	1510	2948	1,3092	8,7944
30	600	2100	1586	3095	1,3092	8,7944
30	600	2200	1661	3243	1,3092	8,7944
30	600	2300	1737	3390	1,3092	8,7944
30	600	2400	1812	3538	1,3092	8,7944
30	600	2500	1888	3685	1,3092	8,7944
30	600	2600	1963	3832	1,3092	8,7944
30	600	2700	2039	3980	1,3092	8,7944
30	600	2800	2115	4127	1,3092	8,7944
30	600	2900	2190	4275	1,3092	8,7944
30	600	3000	2266	4422	1,3092	8,7944
30	700	400	340	666	1,3158	9,6866
30	700	500	425	833	1,3158	9,6866

Declaration of performance

No. DoP-ISG-3452-r01

30	700	600	510	1000	1,3158	9,6866
30	700	700	595	1166	1,3158	9,6866
30	700	800	681	1333	1,3158	9,6866
30	700	900	766	1499	1,3158	9,6866
30	700	1000	851	1666	1,3158	9,6866
30	700	1100	936	1833	1,3158	9,6866
30	700	1200	1021	1999	1,3158	9,6866
30	700	1300	1106	2166	1,3158	9,6866
30	700	1400	1191	2332	1,3158	9,6866
30	700	1500	1276	2499	1,3158	9,6866
30	700	1600	1361	2666	1,3158	9,6866
30	700	1700	1446	2832	1,3158	9,6866
30	700	1800	1531	2999	1,3158	9,6866
30	700	1900	1616	3165	1,3158	9,6866
30	700	2000	1701	3332	1,3158	9,6866
30	700	2100	1786	3499	1,3158	9,6866
30	700	2200	1871	3665	1,3158	9,6866
30	700	2300	1957	3832	1,3158	9,6866
30	700	2400	2042	3998	1,3158	9,6866
30	700	2500	2127	4165	1,3158	9,6866
30	700	2600	2212	4332	1,3158	9,6866
30	700	2700	2297	4498	1,3158	9,6866
30	700	2800	2382	4665	1,3158	9,6866
30	700	2900	2467	4831	1,3158	9,6866
30	700	3000	2552	4998	1,3158	9,6866
30	900	400	414	816	1,3289	11,2630
30	900	500	517	1020	1,3289	11,2630
30	900	600	621	1223	1,3289	11,2630
30	900	700	724	1427	1,3289	11,2630
30	900	800	827	1631	1,3289	11,2630
30	900	900	931	1835	1,3289	11,2630
30	900	1000	1034	2039	1,3289	11,2630
30	900	1100	1138	2243	1,3289	11,2630
30	900	1200	1241	2447	1,3289	11,2630
30	900	1300	1344	2651	1,3289	11,2630
30	900	1400	1448	2855	1,3289	11,2630
30	900	1500	1551	3059	1,3289	11,2630
30	900	1600	1655	3262	1,3289	11,2630
30	900	1700	1758	3466	1,3289	11,2630
30	900	1800	1862	3670	1,3289	11,2630
30	900	1900	1965	3874	1,3289	11,2630
30	900	2000	2068	4078	1,3289	11,2630
30	900	2100	2172	4282	1,3289	11,2630
30	900	2200	2275	4486	1,3289	11,2630
30	900	2300	2379	4690	1,3289	11,2630
30	900	2400	2482	4894	1,3289	11,2630
30	900	2500	2585	5098	1,3289	11,2630
30	900	2600	2689	5301	1,3289	11,2630

Declaration of performance

No. DoP-ISG-3452-r01

30	900	2700	2792	5505	1,3289	11,2630
30	900	2800	2896	5709	1,3289	11,2630
30	900	2900	2999	5913	1,3289	11,2630
30	900	3000	3103	6117	1,3289	11,2630

Stelrad Accord						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
33	300	400	290	567	1,3155	8,2543
33	300	500	362	709	1,3155	8,2543
33	300	600	434	851	1,3155	8,2543
33	300	700	507	993	1,3155	8,2543
33	300	800	579	1134	1,3155	8,2543
33	300	900	652	1276	1,3155	8,2543
33	300	1000	724	1418	1,3155	8,2543
33	300	1100	797	1560	1,3155	8,2543
33	300	1200	869	1702	1,3155	8,2543
33	300	1300	941	1843	1,3155	8,2543
33	300	1400	1014	1985	1,3155	8,2543
33	300	1500	1086	2127	1,3155	8,2543
33	300	1600	1159	2269	1,3155	8,2543
33	300	1700	1231	2411	1,3155	8,2543
33	300	1800	1303	2552	1,3155	8,2543
33	300	1900	1376	2694	1,3155	8,2543
33	300	2000	1448	2836	1,3155	8,2543
33	300	2100	1521	2978	1,3155	8,2543
33	300	2200	1593	3120	1,3155	8,2543
33	300	2300	1666	3261	1,3155	8,2543
33	300	2400	1738	3403	1,3155	8,2543
33	300	2500	1810	3545	1,3155	8,2543
33	300	2600	1883	3687	1,3155	8,2543
33	300	2700	1955	3829	1,3155	8,2543
33	300	2800	2028	3970	1,3155	8,2543
33	300	2900	2100	4112	1,3155	8,2543
33	300	3000	2172	4254	1,3155	8,2543
33	400	400	367	722	1,3261	10,0803
33	400	500	458	903	1,3261	10,0803
33	400	600	550	1083	1,3261	10,0803
33	400	700	642	1264	1,3261	10,0803
33	400	800	733	1444	1,3261	10,0803
33	400	900	825	1625	1,3261	10,0803
33	400	1000	917	1805	1,3261	10,0803
33	400	1100	1009	1986	1,3261	10,0803
33	400	1200	1100	2166	1,3261	10,0803
33	400	1300	1192	2347	1,3261	10,0803
33	400	1400	1284	2527	1,3261	10,0803
33	400	1500	1375	2708	1,3261	10,0803

Declaration of performance

No. DoP-ISG-3452-r01

33	400	1600	1467	2888	1,3261	10,0803
33	400	1700	1559	3069	1,3261	10,0803
33	400	1800	1650	3249	1,3261	10,0803
33	400	1900	1742	3430	1,3261	10,0803
33	400	2000	1834	3610	1,3261	10,0803
33	400	2100	1925	3791	1,3261	10,0803
33	400	2200	2017	3971	1,3261	10,0803
33	400	2300	2109	4152	1,3261	10,0803
33	400	2400	2200	4332	1,3261	10,0803
33	400	2500	2292	4513	1,3261	10,0803
33	400	2600	2384	4693	1,3261	10,0803
33	400	2700	2475	4874	1,3261	10,0803
33	400	2800	2567	5054	1,3261	10,0803
33	400	2900	2659	5235	1,3261	10,0803
33	400	3000	2750	5415	1,3261	10,0803
33	500	400	438	868	1,3367	11,6211
33	500	500	548	1085	1,3367	11,6211
33	500	600	657	1301	1,3367	11,6211
33	500	700	767	1518	1,3367	11,6211
33	500	800	877	1735	1,3367	11,6211
33	500	900	986	1952	1,3367	11,6211
33	500	1000	1096	2169	1,3367	11,6211
33	500	1100	1205	2386	1,3367	11,6211
33	500	1200	1315	2603	1,3367	11,6211
33	500	1300	1424	2820	1,3367	11,6211
33	500	1400	1534	3037	1,3367	11,6211
33	500	1500	1644	3254	1,3367	11,6211
33	500	1600	1753	3470	1,3367	11,6211
33	500	1700	1863	3687	1,3367	11,6211
33	500	1800	1972	3904	1,3367	11,6211
33	500	1900	2082	4121	1,3367	11,6211
33	500	2000	2192	4338	1,3367	11,6211
33	500	2100	2301	4555	1,3367	11,6211
33	500	2200	2411	4772	1,3367	11,6211
33	500	2300	2520	4989	1,3367	11,6211
33	500	2400	2630	5206	1,3367	11,6211
33	500	2500	2739	5423	1,3367	11,6211
33	500	2600	2849	5639	1,3367	11,6211
33	500	2700	2959	5856	1,3367	11,6211
33	500	2800	3068	6073	1,3367	11,6211
33	500	2900	3178	6290	1,3367	11,6211
33	500	3000	3287	6507	1,3367	11,6211
33	600	400	505	1006	1,3473	12,9224
33	600	500	632	1257	1,3473	12,9224
33	600	600	758	1508	1,3473	12,9224
33	600	700	884	1760	1,3473	12,9224
33	600	800	1011	2011	1,3473	12,9224
33	600	900	1137	2263	1,3473	12,9224
33	600	1000	1263	2514	1,3473	12,9224

Declaration of performance

No. DoP-ISG-3452-r01

33	600	1100	1390	2765	1,3473	12,9224
33	600	1200	1516	3017	1,3473	12,9224
33	600	1300	1642	3268	1,3473	12,9224
33	600	1400	1768	3520	1,3473	12,9224
33	600	1500	1895	3771	1,3473	12,9224
33	600	1600	2021	4022	1,3473	12,9224
33	600	1700	2147	4274	1,3473	12,9224
33	600	1800	2274	4525	1,3473	12,9224
33	600	1900	2400	4777	1,3473	12,9224
33	600	2000	2526	5028	1,3473	12,9224
33	600	2100	2653	5279	1,3473	12,9224
33	600	2200	2779	5531	1,3473	12,9224
33	600	2300	2905	5782	1,3473	12,9224
33	600	2400	3032	6034	1,3473	12,9224
33	600	2500	3158	6285	1,3473	12,9224
33	600	2600	3284	6536	1,3473	12,9224
33	600	2700	3411	6788	1,3473	12,9224
33	600	2800	3537	7039	1,3473	12,9224
33	600	2900	3663	7291	1,3473	12,9224
33	600	3000	3790	7542	1,3473	12,9224
33	700	400	569	1136	1,3545	14,1976
33	700	500	711	1421	1,3545	14,1976
33	700	600	853	1705	1,3545	14,1976
33	700	700	996	1989	1,3545	14,1976
33	700	800	1138	2273	1,3545	14,1976
33	700	900	1280	2557	1,3545	14,1976
33	700	1000	1422	2841	1,3545	14,1976
33	700	1100	1564	3125	1,3545	14,1976
33	700	1200	1707	3409	1,3545	14,1976
33	700	1300	1849	3693	1,3545	14,1976
33	700	1400	1991	3977	1,3545	14,1976
33	700	1500	2133	4262	1,3545	14,1976
33	700	1600	2276	4546	1,3545	14,1976
33	700	1700	2418	4830	1,3545	14,1976
33	700	1800	2560	5114	1,3545	14,1976
33	700	1900	2702	5398	1,3545	14,1976
33	700	2000	2845	5682	1,3545	14,1976
33	700	2100	2987	5966	1,3545	14,1976
33	700	2200	3129	6250	1,3545	14,1976
33	700	2300	3271	6534	1,3545	14,1976
33	700	2400	3413	6818	1,3545	14,1976
33	700	2500	3556	7103	1,3545	14,1976
33	700	2600	3698	7387	1,3545	14,1976
33	700	2700	3840	7671	1,3545	14,1976
33	700	2800	3982	7955	1,3545	14,1976
33	700	2900	4125	8239	1,3545	14,1976
33	700	3000	4267	8523	1,3545	14,1976
33	900	400	685	1379	1,3689	16,2872
33	900	500	857	1724	1,3689	16,2872

Declaration of performance

No. DoP-ISG-3452-r01

33	900	600	1028	2069	1,3689	16,2872
33	900	700	1199	2414	1,3689	16,2872
33	900	800	1371	2758	1,3689	16,2872
33	900	900	1542	3103	1,3689	16,2872
33	900	1000	1713	3448	1,3689	16,2872
33	900	1100	1885	3793	1,3689	16,2872
33	900	1200	2056	4138	1,3689	16,2872
33	900	1300	2228	4482	1,3689	16,2872
33	900	1400	2399	4827	1,3689	16,2872
33	900	1500	2570	5172	1,3689	16,2872
33	900	1600	2742	5517	1,3689	16,2872
33	900	1700	2913	5862	1,3689	16,2872
33	900	1800	3084	6206	1,3689	16,2872
33	900	1900	3256	6551	1,3689	16,2872
33	900	2000	3427	6896	1,3689	16,2872
33	900	2100	3598	7241	1,3689	16,2872
33	900	2200	3770	7586	1,3689	16,2872
33	900	2300	3941	7930	1,3689	16,2872
33	900	2400	4112	8275	1,3689	16,2872
33	900	2500	4284	8620	1,3689	16,2872
33	900	2600	4455	8965	1,3689	16,2872
33	900	2700	4626	9310	1,3689	16,2872
33	900	2800	4798	9654	1,3689	16,2872
33	900	2900	4969	9999	1,3689	16,2872
33	900	3000	5140	10344	1,3689	16,2872

Stelrad Novello&Stelrad Compact All in						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
22	200	400	134	260	1,3019	3,9966
22	200	500	167	326	1,3019	3,9966
22	200	600	201	391	1,3019	3,9966
22	200	700	234	456	1,3019	3,9966
22	200	800	268	521	1,3019	3,9966
22	200	900	301	586	1,3019	3,9966
22	200	1000	335	651	1,3019	3,9966
22	200	1100	368	716	1,3019	3,9966
22	200	1200	402	781	1,3019	3,9966
22	200	1300	435	846	1,3019	3,9966
22	200	1400	469	911	1,3019	3,9966
22	200	1500	502	977	1,3019	3,9966
22	200	1600	536	1042	1,3019	3,9966
22	200	1700	569	1107	1,3019	3,9966
22	200	1800	603	1172	1,3019	3,9966
22	200	1900	636	1237	1,3019	3,9966
22	200	2000	670	1302	1,3019	3,9966
22	200	2100	703	1367	1,3019	3,9966
22	200	2200	737	1432	1,3019	3,9966

Declaration of performance

No. DoP-ISG-3452-r01

22	200	2300	770	1497	1,3019	3,9966
22	200	2400	803	1562	1,3019	3,9966
22	200	2500	837	1628	1,3019	3,9966
22	200	2600	870	1693	1,3019	3,9966
22	200	2700	904	1758	1,3019	3,9966
22	200	2800	937	1823	1,3019	3,9966
22	200	2900	971	1888	1,3019	3,9966
22	200	3000	1004	1953	1,3019	3,9966
33	200	400	193	373	1,2917	5,961
33	200	500	241	467	1,2917	5,961
33	200	600	289	560	1,2917	5,961
33	200	700	338	653	1,2917	5,961
33	200	800	386	746	1,2917	5,961
33	200	900	434	840	1,2917	5,961
33	200	1000	482	933	1,2917	5,9610
33	200	1100	531	1026	1,2917	5,961
33	200	1200	579	1120	1,2917	5,961
33	200	1300	627	1213	1,2917	5,961
33	200	1400	675	1306	1,2917	5,961
33	200	1500	723	1400	1,2917	5,961
33	200	1600	772	1493	1,2917	5,961
33	200	1700	820	1586	1,2917	5,961
33	200	1800	868	1679	1,2917	5,961
33	200	1900	916	1773	1,2917	5,961
33	200	2000	965	1866	1,2917	5,961
33	200	2100	1013	1959	1,2917	5,961
33	200	2200	1061	2053	1,2917	5,961
33	200	2300	1109	2146	1,2917	5,961
33	200	2400	1158	2239	1,2917	5,961
33	200	2500	1206	2333	1,2917	5,961
33	200	2600	1254	2426	1,2917	5,961
33	200	2700	1302	2519	1,2917	5,961
33	200	2800	1350	2612	1,2917	5,961
33	200	2900	1399	2706	1,2917	5,961
33	200	3000	1447	2799	1,2917	5,961
44	200	400	249	485	1,3022	7,4320
44	200	500	312	606	1,3022	7,4320
44	200	600	374	727	1,3022	7,4320
44	200	700	436	848	1,3022	7,4320
44	200	800	499	970	1,3022	7,4320
44	200	900	561	1091	1,3022	7,4320
44	200	1000	623	1212	1,3022	7,4320
44	200	1100	685	1333	1,3022	7,4320
44	200	1200	748	1454	1,3022	7,4320
44	200	1300	810	1576	1,3022	7,4320
44	200	1400	872	1697	1,3022	7,4320
44	200	1500	935	1818	1,3022	7,4320
44	200	1600	997	1939	1,3022	7,4320
44	200	1700	1059	2060	1,3022	7,4320
44	200	1800	1122	2182	1,3022	7,4320
44	200	1900	1184	2303	1,3022	7,4320
44	200	2000	1246	2424	1,3022	7,4320

Declaration of performance

No. DoP-ISG-3452-r01

44	200	2100	1309	2545	1,3022	7,4320
44	200	2200	1371	2666	1,3022	7,4320
44	200	2300	1433	2788	1,3022	7,4320
44	200	2400	1496	2909	1,3022	7,4320
44	200	2500	1558	3030	1,3022	7,4320
44	200	2600	1620	3151	1,3022	7,4320
44	200	2700	1683	3272	1,3022	7,4320
44	200	2800	1745	3394	1,3022	7,4320
44	200	2900	1807	3515	1,3022	7,4320
44	200	3000	1870	3636	1,3022	7,4320

Design Flatfront						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
22	200	400	128	244	1,2614	4,395
22	200	500	160	306	1,2614	4,395
22	200	600	192	367	1,2614	4,395
22	200	700	225	428	1,2614	4,395
22	200	800	257	489	1,2614	4,395
22	200	900	289	550	1,2614	4,395
22	200	1000	321	611	1,2614	4,3950
22	200	1100	353	672	1,2614	4,395
22	200	1200	385	733	1,2614	4,395
22	200	1300	417	794	1,2614	4,395
22	200	1400	449	855	1,2614	4,395
22	200	1500	481	917	1,2614	4,395
22	200	1600	513	978	1,2614	4,395
22	200	1700	545	1039	1,2614	4,395
22	200	1800	577	1100	1,2614	4,395
22	200	1900	609	1161	1,2614	4,395
22	200	2000	642	1222	1,2614	4,395
22	200	2100	674	1283	1,2614	4,395
22	200	2200	706	1344	1,2614	4,395
22	200	2300	738	1405	1,2614	4,395
22	200	2400	770	1466	1,2614	4,395
22	200	2500	802	1528	1,2614	4,395
22	200	2600	834	1589	1,2614	4,395
22	200	2700	866	1650	1,2614	4,395
22	200	2800	898	1711	1,2614	4,395
22	200	2900	930	1772	1,2614	4,395
22	200	3000	962	1833	1,2614	4,395
33	200	400	191	367	1,2768	6,2172
33	200	500	239	459	1,2768	6,2172
33	200	600	287	551	1,2768	6,2172
33	200	700	335	643	1,2768	6,2172
33	200	800	383	734	1,2768	6,2172
33	200	900	430	826	1,2768	6,2172
33	200	1000	478	918	1,2768	6,2172
33	200	1100	526	1010	1,2768	6,2172

Declaration of performance

No. DoP-ISG-3452-r01

33	200	1200	574	1102	1,2768	6,2172
33	200	1300	622	1193	1,2768	6,2172
33	200	1400	669	1285	1,2768	6,2172
33	200	1500	717	1377	1,2768	6,2172
33	200	1600	765	1469	1,2768	6,2172
33	200	1700	813	1561	1,2768	6,2172
33	200	1800	861	1652	1,2768	6,2172
33	200	1900	909	1744	1,2768	6,2172
33	200	2000	956	1836	1,2768	6,2172
33	200	2100	1004	1928	1,2768	6,2172
33	200	2200	1052	2020	1,2768	6,2172
33	200	2300	1100	2111	1,2768	6,2172
33	200	2400	1148	2203	1,2768	6,2172
33	200	2500	1195	2295	1,2768	6,2172
33	200	2600	1243	2387	1,2768	6,2172
33	200	2700	1291	2479	1,2768	6,2172
33	200	2800	1339	2570	1,2768	6,2172
33	200	2900	1387	2662	1,2768	6,2172
33	200	3000	1435	2754	1,2768	6,2172
44	200	400	248	479	1,2915	7,6538
44	200	500	309	599	1,2915	7,6538
44	200	600	371	718	1,2915	7,6538
44	200	700	433	838	1,2915	7,6538
44	200	800	495	958	1,2915	7,6538
44	200	900	557	1077	1,2915	7,6538
44	200	1000	619	1197	1,2915	7,6538
44	200	1100	681	1317	1,2915	7,6538
44	200	1200	743	1436	1,2915	7,6538
44	200	1300	804	1556	1,2915	7,6538
44	200	1400	866	1676	1,2915	7,6538
44	200	1500	928	1796	1,2915	7,6538
44	200	1600	990	1915	1,2915	7,6538
44	200	1700	1052	2035	1,2915	7,6538
44	200	1800	1114	2155	1,2915	7,6538
44	200	1900	1176	2274	1,2915	7,6538
44	200	2000	1238	2394	1,2915	7,6538
44	200	2100	1300	2514	1,2915	7,6538
44	200	2200	1361	2633	1,2915	7,6538
44	200	2300	1423	2753	1,2915	7,6538
44	200	2400	1485	2873	1,2915	7,6538
44	200	2500	1547	2993	1,2915	7,6538
44	200	2600	1609	3112	1,2915	7,6538
44	200	2700	1671	3232	1,2915	7,6538
44	200	2800	1733	3352	1,2915	7,6538
44	200	2900	1795	3471	1,2915	7,6538
44	200	3000	1857	3591	1,2915	7,6538

Design Flatfront (Double sided planar)						
T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M

Declaration of performance

No. DoP-ISG-3452-r01

22	200	400	121	230	1,2678	4,0408
22	200	500	151	288	1,2678	4,0408
22	200	600	181	346	1,2678	4,0408
22	200	700	211	403	1,2678	4,0408
22	200	800	241	461	1,2678	4,0408
22	200	900	271	518	1,2678	4,0408
22	200	1000	301	576	1,2678	4,0408
22	200	1100	332	634	1,2678	4,0408
22	200	1200	362	691	1,2678	4,0408
22	200	1300	392	749	1,2678	4,0408
22	200	1400	422	806	1,2678	4,0408
22	200	1500	452	864	1,2678	4,0408
22	200	1600	482	922	1,2678	4,0408
22	200	1700	512	979	1,2678	4,0408
22	200	1800	543	1037	1,2678	4,0408
22	200	1900	573	1094	1,2678	4,0408
22	200	2000	603	1152	1,2678	4,0408
22	200	2100	633	1210	1,2678	4,0408
22	200	2200	663	1267	1,2678	4,0408
22	200	2300	693	1325	1,2678	4,0408
22	200	2400	723	1382	1,2678	4,0408
22	200	2500	754	1440	1,2678	4,0408
22	200	2600	784	1498	1,2678	4,0408
22	200	2700	814	1555	1,2678	4,0408
22	200	2800	844	1613	1,2678	4,0408
22	200	2900	874	1670	1,2678	4,0408
22	200	3000	904	1728	1,2678	4,0408
33	200	400	191	362	1,2579	6,6068
33	200	500	238	453	1,2579	6,6068
33	200	600	286	544	1,2579	6,6068
33	200	700	334	634	1,2579	6,6068
33	200	800	381	725	1,2579	6,6068
33	200	900	429	815	1,2579	6,6068
33	200	1000	477	906	1,2579	6,6068
33	200	1100	524	997	1,2579	6,6068
33	200	1200	572	1087	1,2579	6,6068
33	200	1300	619	1178	1,2579	6,6068
33	200	1400	667	1268	1,2579	6,6068
33	200	1500	715	1359	1,2579	6,6068
33	200	1600	762	1450	1,2579	6,6068
33	200	1700	810	1540	1,2579	6,6068
33	200	1800	858	1631	1,2579	6,6068
33	200	1900	905	1721	1,2579	6,6068
33	200	2000	953	1812	1,2579	6,6068
33	200	2100	1001	1903	1,2579	6,6068
33	200	2200	1048	1993	1,2579	6,6068
33	200	2300	1096	2084	1,2579	6,6068
33	200	2400	1144	2174	1,2579	6,6068
33	200	2500	1191	2265	1,2579	6,6068
33	200	2600	1239	2356	1,2579	6,6068
33	200	2700	1287	2446	1,2579	6,6068
33	200	2800	1334	2537	1,2579	6,6068

Declaration of performance

No. DoP-ISG-3452-r01

33	200	2900	1382	2627	1,2579	6,6068
33	200	3000	1430	2718	1,2579	6,6068
44	200	400	245	472	1,2843	7,7672
44	200	500	306	591	1,2843	7,7672
44	200	600	368	709	1,2843	7,7672
44	200	700	429	827	1,2843	7,7672
44	200	800	490	945	1,2843	7,7672
44	200	900	552	1063	1,2843	7,7672
44	200	1000	613	1181	1,2843	7,7672
44	200	1100	674	1299	1,2843	7,7672
44	200	1200	735	1417	1,2843	7,7672
44	200	1300	797	1535	1,2843	7,7672
44	200	1400	858	1653	1,2843	7,7672
44	200	1500	919	1772	1,2843	7,7672
44	200	1600	981	1890	1,2843	7,7672
44	200	1700	1042	2008	1,2843	7,7672
44	200	1800	1103	2126	1,2843	7,7672
44	200	1900	1164	2244	1,2843	7,7672
44	200	2000	1226	2362	1,2843	7,7672
44	200	2100	1287	2480	1,2843	7,7672
44	200	2200	1348	2598	1,2843	7,7672
44	200	2300	1409	2716	1,2843	7,7672
44	200	2400	1471	2834	1,2843	7,7672
44	200	2500	1532	2953	1,2843	7,7672
44	200	2600	1593	3071	1,2843	7,7672
44	200	2700	1655	3189	1,2843	7,7672
44	200	2800	1716	3307	1,2843	7,7672
44	200	2900	1777	3425	1,2843	7,7672
44	200	3000	1838	3543	1,2843	7,7672

Stelrad Compact All in

T	H (mm)	L (mm)	Heat output dT30 (W)	Heat output dT50 (W)	n	K _M
11	300	400	104	204	1,3216	2,8991
11	300	500	130	255	1,3216	2,8991
11	300	600	155	305	1,3216	2,8991
11	300	700	181	356	1,3216	2,8991
11	300	800	207	407	1,3216	2,8991
11	300	900	233	458	1,3216	2,8991
11	300	1000	259	509	1,3216	2,8931
11	300	1100	285	560	1,3216	2,8991
11	300	1200	311	611	1,3216	2,8991
11	300	1300	337	662	1,3216	2,8991
11	300	1400	363	713	1,3216	2,8991
11	300	1500	389	764	1,3216	2,8991
11	300	1600	415	814	1,3216	2,8991
11	300	1700	441	865	1,3216	2,8991
11	300	1800	466	916	1,3216	2,8991
11	300	1900	492	967	1,3216	2,8991
11	300	2000	518	1018	1,3216	2,8991

Declaration of performance

No. DoP-ISG-3452-r01

11	300	2100	544	1069	1,3216	2,8991
11	300	2200	570	1120	1,3216	2,8991
11	300	2300	596	1171	1,3216	2,8991
11	300	2400	622	1222	1,3216	2,8991
11	300	2500	648	1273	1,3216	2,8991
11	300	2600	674	1323	1,3216	2,8991
11	300	2700	700	1374	1,3216	2,8991
11	300	2800	726	1425	1,3216	2,8991
11	300	2900	751	1476	1,3216	2,8991
11	300	3000	777	1527	1,3216	2,8991
11	400	400	138	270	1,3117	3,994
11	400	500	173	338	1,3117	3,994
11	400	600	208	406	1,3117	3,994
11	400	700	242	473	1,3117	3,994
11	400	800	277	541	1,3117	3,994
11	400	900	311	608	1,3117	3,994
11	400	1000	346	676	1,3117	3,9940
11	400	1100	380	744	1,3117	3,994
11	400	1200	415	811	1,3117	3,994
11	400	1300	450	879	1,3117	3,994
11	400	1400	484	946	1,3117	3,994
11	400	1500	519	1014	1,3117	3,994
11	400	1600	553	1082	1,3117	3,994
11	400	1700	588	1149	1,3117	3,994
11	400	1800	623	1217	1,3117	3,994
11	400	1900	657	1284	1,3117	3,994
11	400	2000	692	1352	1,3117	3,994
11	400	2100	726	1420	1,3117	3,994
11	400	2200	761	1487	1,3117	3,994
11	400	2300	796	1555	1,3117	3,994
11	400	2400	830	1622	1,3117	3,994
11	400	2500	865	1690	1,3117	3,994
11	400	2600	899	1758	1,3117	3,994
11	400	2700	934	1825	1,3117	3,994
11	400	2800	969	1893	1,3117	3,994
11	400	2900	1003	1960	1,3117	3,994
11	400	3000	1038	2028	1,3117	3,994
11	500	400	171	333	1,3018	5,1159
11	500	500	214	417	1,3018	5,1159
11	500	600	257	500	1,3018	5,1159
11	500	700	300	583	1,3018	5,1159
11	500	800	343	666	1,3018	5,1159
11	500	900	386	750	1,3018	5,1159
11	500	1000	428	833	1,3018	5,1159
11	500	1100	471	916	1,3018	5,1159
11	500	1200	514	1000	1,3018	5,1159
11	500	1300	557	1083	1,3018	5,1159
11	500	1400	600	1166	1,3018	5,1159
11	500	1500	643	1250	1,3018	5,1159
11	500	1600	685	1333	1,3018	5,1159
11	500	1700	728	1416	1,3018	5,1159
11	500	1800	771	1499	1,3018	5,1159
11	500	1900	814	1583	1,3018	5,1159
11	500	2000	857	1666	1,3018	5,1159
11	500	2100	900	1749	1,3018	5,1159

Declaration of performance

No. DoP-ISG-3452-r01

11	500	2200	942	1833	1,3018	5,1159
11	500	2300	985	1916	1,3018	5,1159
11	500	2400	1028	1999	1,3018	5,1159
11	500	2500	1071	2083	1,3018	5,1159
11	500	2600	1114	2166	1,3018	5,1159
11	500	2700	1157	2249	1,3018	5,1159
11	500	2800	1200	2332	1,3018	5,1159
11	500	2900	1242	2416	1,3018	5,1159
11	500	3000	1285	2499	1,3018	5,1159
11	600	400	203	392	1,2919	6,2564
11	600	500	253	490	1,2919	6,2564
11	600	600	304	588	1,2919	6,2564
11	600	700	355	686	1,2919	6,2564
11	600	800	405	784	1,2919	6,2564
11	600	900	456	882	1,2919	6,2564
11	600	1000	507	980	1,2919	6,2564
11	600	1100	557	1078	1,2919	6,2564
11	600	1200	608	1176	1,2919	6,2564
11	600	1300	659	1274	1,2919	6,2564
11	600	1400	709	1372	1,2919	6,2564
11	600	1500	760	1470	1,2919	6,2564
11	600	1600	810	1568	1,2919	6,2564
11	600	1700	861	1666	1,2919	6,2564
11	600	1800	912	1764	1,2919	6,2564
11	600	1900	962	1862	1,2919	6,2564
11	600	2000	1013	1960	1,2919	6,2564
11	600	2100	1064	2058	1,2919	6,2564
11	600	2200	1114	2156	1,2919	6,2564
11	600	2300	1165	2254	1,2919	6,2564
11	600	2400	1216	2352	1,2919	6,2564
11	600	2500	1266	2450	1,2919	6,2564
11	600	2600	1317	2548	1,2919	6,2564
11	600	2700	1368	2646	1,2919	6,2564
11	600	2800	1418	2744	1,2919	6,2564
11	600	2900	1469	2842	1,2919	6,2564
11	600	3000	1520	2940	1,2919	6,2564
11	700	400	231	447	1,2919	7,1311
11	700	500	289	559	1,2919	7,1311
11	700	600	346	670	1,2919	7,1311
11	700	700	404	782	1,2919	7,1311
11	700	800	462	894	1,2919	7,1311
11	700	900	520	1005	1,2919	7,1311
11	700	1000	577	1117	1,2919	7,1311
11	700	1100	635	1229	1,2919	7,1311
11	700	1200	693	1340	1,2919	7,1311
11	700	1300	751	1452	1,2919	7,1311
11	700	1400	808	1564	1,2919	7,1311
11	700	1500	866	1676	1,2919	7,1311
11	700	1600	924	1787	1,2919	7,1311
11	700	1700	982	1899	1,2919	7,1311
11	700	1800	1039	2011	1,2919	7,1311
11	700	1900	1097	2122	1,2919	7,1311
11	700	2000	1155	2234	1,2919	7,1311
11	700	2100	1212	2346	1,2919	7,1311
11	700	2200	1270	2457	1,2919	7,1311

Declaration of performance

No. DoP-ISG-3452-r01

11	700	2300	1328	2569	1,2919	7,1311
11	700	2400	1386	2681	1,2919	7,1311
11	700	2500	1443	2793	1,2919	7,1311
11	700	2600	1501	2904	1,2919	7,1311
11	700	2700	1559	3016	1,2919	7,1311
11	700	2800	1617	3128	1,2919	7,1311
11	700	2900	1674	3239	1,2919	7,1311
11	700	3000	1732	3351	1,2919	7,1311
11	900	400	281	544	1,2919	8,6824
11	900	500	351	680	1,2919	8,6824
11	900	600	422	816	1,2919	8,6824
11	900	700	492	952	1,2919	8,6824
11	900	800	562	1088	1,2919	8,6824
11	900	900	633	1224	1,2919	8,6824
11	900	1000	703	1360	1,2919	8,6824
11	900	1100	773	1496	1,2919	8,6824
11	900	1200	844	1632	1,2919	8,6824
11	900	1300	914	1768	1,2919	8,6824
11	900	1400	984	1904	1,2919	8,6824
11	900	1500	1054	2040	1,2919	8,6824
11	900	1600	1125	2176	1,2919	8,6824
11	900	1700	1195	2312	1,2919	8,6824
11	900	1800	1265	2448	1,2919	8,6824
11	900	1900	1336	2584	1,2919	8,6824
11	900	2000	1406	2720	1,2919	8,6824
11	900	2100	1476	2856	1,2919	8,6824
11	900	2200	1547	2992	1,2919	8,6824
11	900	2300	1617	3128	1,2919	8,6824
11	900	2400	1687	3264	1,2919	8,6824
11	900	2500	1757	3400	1,2919	8,6824
11	900	2600	1828	3536	1,2919	8,6824
11	900	2700	1898	3672	1,2919	8,6824
11	900	2800	1968	3808	1,2919	8,6824
11	900	2900	2039	3944	1,2919	8,6824
11	900	3000	2109	4080	1,2919	8,6824
21	300	400	151	298	1,3297	4,1024
21	300	500	189	373	1,3297	4,1024
21	300	600	227	447	1,3297	4,1024
21	300	700	264	522	1,3297	4,1024
21	300	800	302	596	1,3297	4,1024
21	300	900	340	671	1,3297	4,1024
21	300	1000	378	745	1,3297	4,1024
21	300	1100	415	820	1,3297	4,1024
21	300	1200	453	894	1,3297	4,1024
21	300	1300	491	969	1,3297	4,1024
21	300	1400	529	1043	1,3297	4,1024
21	300	1500	567	1118	1,3297	4,1024
21	300	1600	604	1192	1,3297	4,1024
21	300	1700	642	1267	1,3297	4,1024
21	300	1800	680	1341	1,3297	4,1024
21	300	1900	718	1416	1,3297	4,1024
21	300	2000	755	1490	1,3297	4,1024
21	300	2100	793	1565	1,3297	4,1024
21	300	2200	831	1639	1,3297	4,1024
21	300	2300	869	1714	1,3297	4,1024

Declaration of performance

No. DoP-ISG-3452-r01

21	300	2400	907	1788	1,3297	4,1024
21	300	2500	944	1863	1,3297	4,1024
21	300	2600	982	1937	1,3297	4,1024
21	300	2700	1020	2012	1,3297	4,1024
21	300	2800	1058	2086	1,3297	4,1024
21	300	2900	1095	2161	1,3297	4,1024
21	300	3000	1133	2235	1,3297	4,1024
21	400	400	193	382	1,3325	5,1960
21	400	500	241	477	1,3325	5,1960
21	400	600	290	572	1,3325	5,1960
21	400	700	338	668	1,3325	5,1960
21	400	800	386	763	1,3325	5,1960
21	400	900	435	859	1,3325	5,1960
21	400	1000	483	954	1,3325	5,1960
21	400	1100	531	1049	1,3325	5,1960
21	400	1200	580	1145	1,3325	5,1960
21	400	1300	628	1240	1,3325	5,1960
21	400	1400	676	1336	1,3325	5,1960
21	400	1500	724	1431	1,3325	5,1960
21	400	1600	773	1526	1,3325	5,1960
21	400	1700	821	1622	1,3325	5,1960
21	400	1800	869	1717	1,3325	5,1960
21	400	1900	918	1813	1,3325	5,1960
21	400	2000	966	1908	1,3325	5,1960
21	400	2100	1014	2003	1,3325	5,1960
21	400	2200	1063	2099	1,3325	5,1960
21	400	2300	1111	2194	1,3325	5,1960
21	400	2400	1159	2290	1,3325	5,1960
21	400	2500	1207	2385	1,3325	5,1960
21	400	2600	1256	2480	1,3325	5,1960
21	400	2700	1304	2576	1,3325	5,1960
21	400	2800	1352	2671	1,3325	5,1960
21	400	2900	1401	2767	1,3325	5,1960
21	400	3000	1449	2862	1,3325	5,1960
21	500	400	233	461	1,3353	6,2115
21	500	500	291	577	1,3353	6,2115
21	500	600	350	692	1,3353	6,2115
21	500	700	408	807	1,3353	6,2115
21	500	800	466	922	1,3353	6,2115
21	500	900	525	1038	1,3353	6,2115
21	500	1000	583	1153	1,3353	6,2115
21	500	1100	641	1268	1,3353	6,2115
21	500	1200	699	1384	1,3353	6,2115
21	500	1300	758	1499	1,3353	6,2115
21	500	1400	816	1614	1,3353	6,2115
21	500	1500	874	1730	1,3353	6,2115
21	500	1600	933	1845	1,3353	6,2115
21	500	1700	991	1960	1,3353	6,2115
21	500	1800	1049	2075	1,3353	6,2115
21	500	1900	1108	2191	1,3353	6,2115
21	500	2000	1166	2306	1,3353	6,2115
21	500	2100	1224	2421	1,3353	6,2115
21	500	2200	1282	2537	1,3353	6,2115
21	500	2300	1341	2652	1,3353	6,2115
21	500	2400	1399	2767	1,3353	6,2115

Declaration of performance

No. DoP-ISG-3452-r01

21	500	2500	1457	2883	1,3353	6,2115
21	500	2600	1516	2998	1,3353	6,2115
21	500	2700	1574	3113	1,3353	6,2115
21	500	2800	1632	3228	1,3353	6,2115
21	500	2900	1690	3344	1,3353	6,2115
21	500	3000	1749	3459	1,3353	6,2115
21	600	400	272	538	1,3381	7,1669
21	600	500	339	673	1,3381	7,1669
21	600	600	407	807	1,3381	7,1669
21	600	700	475	942	1,3381	7,1669
21	600	800	543	1076	1,3381	7,1669
21	600	900	611	1211	1,3381	7,1669
21	600	1000	679	1345	1,3381	7,1669
21	600	1100	747	1480	1,3381	7,1669
21	600	1200	815	1614	1,3381	7,1669
21	600	1300	883	1749	1,3381	7,1669
21	600	1400	951	1883	1,3381	7,1669
21	600	1500	1018	2018	1,3381	7,1669
21	600	1600	1086	2152	1,3381	7,1669
21	600	1700	1154	2287	1,3381	7,1669
21	600	1800	1222	2421	1,3381	7,1669
21	600	1900	1290	2556	1,3381	7,1669
21	600	2000	1358	2690	1,3381	7,1669
21	600	2100	1426	2825	1,3381	7,1669
21	600	2200	1494	2959	1,3381	7,1669
21	600	2300	1562	3094	1,3381	7,1669
21	600	2400	1630	3228	1,3381	7,1669
21	600	2500	1697	3363	1,3381	7,1669
21	600	2600	1765	3497	1,3381	7,1669
21	600	2700	1833	3632	1,3381	7,1669
21	600	2800	1901	3766	1,3381	7,1669
21	600	2900	1969	3901	1,3381	7,1669
21	600	3000	2037	4035	1,3381	7,1669
21	700	400	309	612	1,3381	8,1527
21	700	500	386	765	1,3381	8,1527
21	700	600	463	918	1,3381	8,1527
21	700	700	541	1071	1,3381	8,1527
21	700	800	618	1224	1,3381	8,1527
21	700	900	695	1377	1,3381	8,1527
21	700	1000	772	1530	1,3381	8,1527
21	700	1100	850	1683	1,3381	8,1527
21	700	1200	927	1836	1,3381	8,1527
21	700	1300	1004	1989	1,3381	8,1527
21	700	1400	1081	2142	1,3381	8,1527
21	700	1500	1159	2295	1,3381	8,1527
21	700	1600	1236	2448	1,3381	8,1527
21	700	1700	1313	2601	1,3381	8,1527
21	700	1800	1390	2754	1,3381	8,1527
21	700	1900	1468	2907	1,3381	8,1527
21	700	2000	1545	3060	1,3381	8,1527
21	700	2100	1622	3213	1,3381	8,1527
21	700	2200	1699	3366	1,3381	8,1527
21	700	2300	1776	3519	1,3381	8,1527
21	700	2400	1854	3672	1,3381	8,1527
21	700	2500	1931	3825	1,3381	8,1527

Declaration of performance

No. DoP-ISG-3452-r01

21	700	2600	2008	3978	1,3381	8,1527
21	700	2700	2085	4131	1,3381	8,1527
21	700	2800	2163	4284	1,3381	8,1527
21	700	2900	2240	4437	1,3381	8,1527
21	700	3000	2317	4590	1,3381	8,1527
21	900	400	380	753	1,3382	10,0297
21	900	500	475	942	1,3382	10,0297
21	900	600	570	1130	1,3382	10,0297
21	900	700	665	1318	1,3382	10,0297
21	900	800	760	1506	1,3382	10,0297
21	900	900	855	1695	1,3382	10,0297
21	900	1000	951	1883	1,3382	10,0297
21	900	1100	1046	2071	1,3382	10,0297
21	900	1200	1141	2260	1,3382	10,0297
21	900	1300	1236	2448	1,3382	10,0297
21	900	1400	1331	2636	1,3382	10,0297
21	900	1500	1426	2825	1,3382	10,0297
21	900	1600	1521	3013	1,3382	10,0297
21	900	1700	1616	3201	1,3382	10,0297
21	900	1800	1711	3389	1,3382	10,0297
21	900	1900	1806	3578	1,3382	10,0297
21	900	2000	1901	3766	1,3382	10,0297
21	900	2100	1996	3954	1,3382	10,0297
21	900	2200	2091	4143	1,3382	10,0297
21	900	2300	2186	4331	1,3382	10,0297
21	900	2400	2281	4519	1,3382	10,0297
21	900	2500	2376	4708	1,3382	10,0297
21	900	2600	2471	4896	1,3382	10,0297
21	900	2700	2566	5084	1,3382	10,0297
21	900	2800	2662	5272	1,3382	10,0297
21	900	2900	2757	5461	1,3382	10,0297
21	900	3000	2852	5649	1,3382	10,0297
22	300	400	199	393	1,3264	5,4777
22	300	500	249	491	1,3264	5,4777
22	300	600	299	589	1,3264	5,4777
22	300	700	349	687	1,3264	5,4777
22	300	800	399	786	1,3264	5,4777
22	300	900	449	884	1,3264	5,4777
22	300	1000	499	982	1,3264	5,4777
22	300	1100	549	1080	1,3264	5,4777
22	300	1200	598	1178	1,3264	5,4777
22	300	1300	648	1277	1,3264	5,4777
22	300	1400	698	1375	1,3264	5,4777
22	300	1500	748	1473	1,3264	5,4777
22	300	1600	798	1571	1,3264	5,4777
22	300	1700	848	1669	1,3264	5,4777
22	300	1800	898	1768	1,3264	5,4777
22	300	1900	948	1866	1,3264	5,4777
22	300	2000	997	1964	1,3264	5,4777
22	300	2100	1047	2062	1,3264	5,4777
22	300	2200	1097	2160	1,3264	5,4777
22	300	2300	1147	2259	1,3264	5,4777
22	300	2400	1197	2357	1,3264	5,4777
22	300	2500	1247	2455	1,3264	5,4777
22	300	2600	1297	2553	1,3264	5,4777

Declaration of performance

No. DoP-ISG-3452-r01

22	300	2700	1347	2651	1,3264	5,4777
22	300	2800	1396	2750	1,3264	5,4777
22	300	2900	1446	2848	1,3264	5,4777
22	300	3000	1496	2946	1,3264	5,4777
22	400	400	253	498	1,3291	6,8718
22	400	500	316	623	1,3291	6,8718
22	400	600	379	747	1,3291	6,8718
22	400	700	442	872	1,3291	6,8718
22	400	800	505	996	1,3291	6,8718
22	400	900	568	1121	1,3291	6,8718
22	400	1000	631	1245	1,3291	6,8718
22	400	1100	695	1370	1,3291	6,8718
22	400	1200	758	1494	1,3291	6,8718
22	400	1300	821	1619	1,3291	6,8718
22	400	1400	884	1743	1,3291	6,8718
22	400	1500	947	1868	1,3291	6,8718
22	400	1600	1010	1992	1,3291	6,8718
22	400	1700	1073	2117	1,3291	6,8718
22	400	1800	1137	2241	1,3291	6,8718
22	400	1900	1200	2366	1,3291	6,8718
22	400	2000	1263	2490	1,3291	6,8718
22	400	2100	1326	2615	1,3291	6,8718
22	400	2200	1389	2739	1,3291	6,8718
22	400	2300	1452	2864	1,3291	6,8718
22	400	2400	1515	2988	1,3291	6,8718
22	400	2500	1579	3113	1,3291	6,8718
22	400	2600	1642	3237	1,3291	6,8718
22	400	2700	1705	3362	1,3291	6,8718
22	400	2800	1768	3486	1,3291	6,8718
22	400	2900	1831	3611	1,3291	6,8718
22	400	3000	1894	3735	1,3291	6,8718
22	500	400	303	598	1,3319	8,1563
22	500	500	378	747	1,3319	8,1563
22	500	600	454	896	1,3319	8,1563
22	500	700	530	1046	1,3319	8,1563
22	500	800	605	1195	1,3319	8,1563
22	500	900	681	1345	1,3319	8,1563
22	500	1000	757	1494	1,3319	8,1563
22	500	1100	832	1643	1,3319	8,1563
22	500	1200	908	1793	1,3319	8,1563
22	500	1300	984	1942	1,3319	8,1563
22	500	1400	1059	2092	1,3319	8,1563
22	500	1500	1135	2241	1,3319	8,1563
22	500	1600	1211	2390	1,3319	8,1563
22	500	1700	1286	2540	1,3319	8,1563
22	500	1800	1362	2689	1,3319	8,1563
22	500	1900	1438	2839	1,3319	8,1563
22	500	2000	1513	2988	1,3319	8,1563
22	500	2100	1589	3137	1,3319	8,1563
22	500	2200	1665	3287	1,3319	8,1563
22	500	2300	1740	3436	1,3319	8,1563
22	500	2400	1816	3586	1,3319	8,1563
22	500	2500	1892	3735	1,3319	8,1563
22	500	2600	1967	3884	1,3319	8,1563
22	500	2700	2043	4034	1,3319	8,1563

Declaration of performance

No. DoP-ISG-3452-r01

22	500	2800	2118	4183	1,3319	8,1563
22	500	2900	2194	4333	1,3319	8,1563
22	500	3000	2270	4482	1,3319	8,1563
22	600	400	350	693	1,3346	9,3563
22	600	500	438	866	1,3346	9,3563
22	600	600	526	1039	1,3346	9,3563
22	600	700	613	1212	1,3346	9,3563
22	600	800	701	1386	1,3346	9,3563
22	600	900	788	1559	1,3346	9,3563
22	600	1000	876	1732	1,3346	9,3563
22	600	1100	964	1905	1,3346	9,3563
22	600	1200	1051	2078	1,3346	9,3563
22	600	1300	1139	2252	1,3346	9,3563
22	600	1400	1226	2425	1,3346	9,3563
22	600	1500	1314	2598	1,3346	9,3563
22	600	1600	1401	2771	1,3346	9,3563
22	600	1700	1489	2944	1,3346	9,3563
22	600	1800	1577	3118	1,3346	9,3563
22	600	1900	1664	3291	1,3346	9,3563
22	600	2000	1752	3464	1,3346	9,3563
22	600	2100	1839	3637	1,3346	9,3563
22	600	2200	1927	3810	1,3346	9,3563
22	600	2300	2015	3984	1,3346	9,3563
22	600	2400	2102	4157	1,3346	9,3563
22	600	2500	2190	4330	1,3346	9,3563
22	600	2600	2277	4503	1,3346	9,3563
22	600	2700	2365	4676	1,3346	9,3563
22	600	2800	2453	4850	1,3346	9,3563
22	600	2900	2540	5023	1,3346	9,3563
22	600	3000	2628	5196	1,3346	9,3563
22	700	400	396	784	1,3385	10,4329
22	700	500	495	981	1,3385	10,4329
22	700	600	594	1177	1,3385	10,4329
22	700	700	693	1373	1,3385	10,4329
22	700	800	792	1569	1,3385	10,4329
22	700	900	891	1765	1,3385	10,4329
22	700	1000	990	1961	1,3385	10,4329
22	700	1100	1089	2157	1,3385	10,4329
22	700	1200	1188	2353	1,3385	10,4329
22	700	1300	1287	2549	1,3385	10,4329
22	700	1400	1386	2745	1,3385	10,4329
22	700	1500	1485	2942	1,3385	10,4329
22	700	1600	1584	3138	1,3385	10,4329
22	700	1700	1683	3334	1,3385	10,4329
22	700	1800	1782	3530	1,3385	10,4329
22	700	1900	1881	3726	1,3385	10,4329
22	700	2000	1980	3922	1,3385	10,4329
22	700	2100	2079	4118	1,3385	10,4329
22	700	2200	2177	4314	1,3385	10,4329
22	700	2300	2276	4510	1,3385	10,4329
22	700	2400	2375	4706	1,3385	10,4329
22	700	2500	2474	4903	1,3385	10,4329
22	700	2600	2573	5099	1,3385	10,4329
22	700	2700	2672	5295	1,3385	10,4329
22	700	2800	2771	5491	1,3385	10,4329

Declaration of performance

No. DoP-ISG-3452-r01

22	700	2900	2870	5687	1,3385	10,4329
22	700	3000	2969	5883	1,3385	10,4329
22	900	400	482	958	1,3463	12,359
22	900	500	602	1198	1,3463	12,359
22	900	600	722	1437	1,3463	12,359
22	900	700	843	1677	1,3463	12,359
22	900	800	963	1916	1,3463	12,359
22	900	900	1084	2156	1,3463	12,359
22	900	1000	1204	2395	1,3463	12,3590
22	900	1100	1324	2635	1,3463	12,359
22	900	1200	1445	2874	1,3463	12,359
22	900	1300	1565	3114	1,3463	12,359
22	900	1400	1686	3353	1,3463	12,359
22	900	1500	1806	3593	1,3463	12,359
22	900	1600	1926	3832	1,3463	12,359
22	900	1700	2047	4072	1,3463	12,359
22	900	1800	2167	4311	1,3463	12,359
22	900	1900	2288	4551	1,3463	12,359
22	900	2000	2408	4790	1,3463	12,359
22	900	2100	2528	5030	1,3463	12,359
22	900	2200	2649	5269	1,3463	12,359
22	900	2300	2769	5509	1,3463	12,359
22	900	2400	2890	5748	1,3463	12,359
22	900	2500	3010	5988	1,3463	12,359
22	900	2600	3130	6227	1,3463	12,359
22	900	2700	3251	6467	1,3463	12,359
22	900	2800	3371	6706	1,3463	12,359
22	900	2900	3492	6946	1,3463	12,359
22	900	3000	3612	7185	1,3463	12,359
33	300	400	276	540	1,3137	7,9082
33	300	500	345	675	1,3137	7,9082
33	300	600	414	809	1,3137	7,9082
33	300	700	483	944	1,3137	7,9082
33	300	800	552	1079	1,3137	7,9082
33	300	900	621	1214	1,3137	7,9082
33	300	1000	690	1349	1,3137	7,9082
33	300	1100	759	1484	1,3137	7,9082
33	300	1200	827	1619	1,3137	7,9082
33	300	1300	896	1754	1,3137	7,9082
33	300	1400	965	1889	1,3137	7,9082
33	300	1500	1034	2024	1,3137	7,9082
33	300	1600	1103	2158	1,3137	7,9082
33	300	1700	1172	2293	1,3137	7,9082
33	300	1800	1241	2428	1,3137	7,9082
33	300	1900	1310	2563	1,3137	7,9082
33	300	2000	1379	2698	1,3137	7,9082
33	300	2100	1448	2833	1,3137	7,9082
33	300	2200	1517	2968	1,3137	7,9082
33	300	2300	1586	3103	1,3137	7,9082
33	300	2400	1655	3238	1,3137	7,9082
33	300	2500	1724	3373	1,3137	7,9082
33	300	2600	1793	3507	1,3137	7,9082
33	300	2700	1862	3642	1,3137	7,9082
33	300	2800	1931	3777	1,3137	7,9082
33	300	2900	2000	3912	1,3137	7,9082

Declaration of performance

No. DoP-ISG-3452-r01

33	300	3000	2069	4047	1,3137	7,9082
33	400	400	349	684	1,3169	9,9055
33	400	500	437	856	1,3169	9,9055
33	400	600	524	1027	1,3169	9,9055
33	400	700	611	1198	1,3169	9,9055
33	400	800	699	1369	1,3169	9,9055
33	400	900	786	1540	1,3169	9,9055
33	400	1000	873	1711	1,3169	9,9055
33	400	1100	960	1882	1,3169	9,9055
33	400	1200	1048	2053	1,3169	9,9055
33	400	1300	1135	2224	1,3169	9,9055
33	400	1400	1222	2395	1,3169	9,9055
33	400	1500	1310	2567	1,3169	9,9055
33	400	1600	1397	2738	1,3169	9,9055
33	400	1700	1484	2909	1,3169	9,9055
33	400	1800	1572	3080	1,3169	9,9055
33	400	1900	1659	3251	1,3169	9,9055
33	400	2000	1746	3422	1,3169	9,9055
33	400	2100	1834	3593	1,3169	9,9055
33	400	2200	1921	3764	1,3169	9,9055
33	400	2300	2008	3935	1,3169	9,9055
33	400	2400	2096	4106	1,3169	9,9055
33	400	2500	2183	4278	1,3169	9,9055
33	400	2600	2270	4449	1,3169	9,9055
33	400	2700	2358	4620	1,3169	9,9055
33	400	2800	2445	4791	1,3169	9,9055
33	400	2900	2532	4962	1,3169	9,9055
33	400	3000	2620	5133	1,3169	9,9055
33	500	400	419	822	1,3202	11,7501
33	500	500	524	1028	1,3202	11,7501
33	500	600	628	1234	1,3202	11,7501
33	500	700	733	1439	1,3202	11,7501
33	500	800	838	1645	1,3202	11,7501
33	500	900	943	1850	1,3202	11,7501
33	500	1000	1047	2056	1,3202	11,7501
33	500	1100	1152	2262	1,3202	11,7501
33	500	1200	1257	2467	1,3202	11,7501
33	500	1300	1362	2673	1,3202	11,7501
33	500	1400	1466	2878	1,3202	11,7501
33	500	1500	1571	3084	1,3202	11,7501
33	500	1600	1676	3290	1,3202	11,7501
33	500	1700	1781	3495	1,3202	11,7501
33	500	1800	1885	3701	1,3202	11,7501
33	500	1900	1990	3906	1,3202	11,7501
33	500	2000	2095	4112	1,3202	11,7501
33	500	2100	2200	4318	1,3202	11,7501
33	500	2200	2304	4523	1,3202	11,7501
33	500	2300	2409	4729	1,3202	11,7501
33	500	2400	2514	4934	1,3202	11,7501
33	500	2500	2619	5140	1,3202	11,7501
33	500	2600	2723	5346	1,3202	11,7501
33	500	2700	2828	5551	1,3202	11,7501
33	500	2800	2933	5757	1,3202	11,7501
33	500	2900	3038	5962	1,3202	11,7501
33	500	3000	3142	6168	1,3202	11,7501

Declaration of performance

No. DoP-ISG-3452-r01

33	600	400	486	956	1,3234	13,4834
33	600	500	608	1195	1,3234	13,4834
33	600	600	729	1433	1,3234	13,4834
33	600	700	851	1672	1,3234	13,4834
33	600	800	972	1911	1,3234	13,4834
33	600	900	1094	2150	1,3234	13,4834
33	600	1000	1215	2389	1,3234	13,4834
33	600	1100	1337	2628	1,3234	13,4834
33	600	1200	1458	2867	1,3234	13,4834
33	600	1300	1580	3106	1,3234	13,4834
33	600	1400	1701	3345	1,3234	13,4834
33	600	1500	1823	3584	1,3234	13,4834
33	600	1600	1944	3822	1,3234	13,4834
33	600	1700	2066	4061	1,3234	13,4834
33	600	1800	2187	4300	1,3234	13,4834
33	600	1900	2309	4539	1,3234	13,4834
33	600	2000	2430	4778	1,3234	13,4834
33	600	2100	2552	5017	1,3234	13,4834
33	600	2200	2673	5256	1,3234	13,4834
33	600	2300	2795	5495	1,3234	13,4834
33	600	2400	2916	5734	1,3234	13,4834
33	600	2500	3038	5973	1,3234	13,4834
33	600	2600	3159	6211	1,3234	13,4834
33	600	2700	3281	6450	1,3234	13,4834
33	600	2800	3402	6689	1,3234	13,4834
33	600	2900	3524	6928	1,3234	13,4834
33	600	3000	3645	7167	1,3234	13,4834
33	700	400	547	1085	1,3393	14,3833
33	700	500	684	1356	1,3393	14,3833
33	700	600	821	1627	1,3393	14,3833
33	700	700	958	1898	1,3393	14,3833
33	700	800	1095	2170	1,3393	14,3833
33	700	900	1231	2441	1,3393	14,3833
33	700	1000	1368	2712	1,3393	14,3833
33	700	1100	1505	2983	1,3393	14,3833
33	700	1200	1642	3254	1,3393	14,3833
33	700	1300	1779	3526	1,3393	14,3833
33	700	1400	1916	3797	1,3393	14,3833
33	700	1500	2052	4068	1,3393	14,3833
33	700	1600	2189	4339	1,3393	14,3833
33	700	1700	2326	4610	1,3393	14,3833
33	700	1800	2463	4882	1,3393	14,3833
33	700	1900	2600	5153	1,3393	14,3833
33	700	2000	2737	5424	1,3393	14,3833
33	700	2100	2873	5695	1,3393	14,3833
33	700	2200	3010	5966	1,3393	14,3833
33	700	2300	3147	6238	1,3393	14,3833
33	700	2400	3284	6509	1,3393	14,3833
33	700	2500	3421	6780	1,3393	14,3833
33	700	2600	3557	7051	1,3393	14,3833
33	700	2700	3694	7322	1,3393	14,3833
33	700	2800	3831	7594	1,3393	14,3833
33	700	2900	3968	7865	1,3393	14,3833
33	700	3000	4105	8136	1,3393	14,3833
33	900	400	662	1334	1,3712	15,6077

Declaration of performance

No. DoP-ISG-3452-r01

33	900	500	827	1667	1,3712	15,6077
33	900	600	993	2000	1,3712	15,6077
33	900	700	1158	2334	1,3712	15,6077
33	900	800	1324	2667	1,3712	15,6077
33	900	900	1489	3001	1,3712	15,6077
33	900	1000	1655	3334	1,3712	15,6077
33	900	1100	1820	3667	1,3712	15,6077
33	900	1200	1986	4001	1,3712	15,6077
33	900	1300	2151	4334	1,3712	15,6077
33	900	1400	2317	4668	1,3712	15,6077
33	900	1500	2482	5001	1,3712	15,6077
33	900	1600	2648	5334	1,3712	15,6077
33	900	1700	2813	5668	1,3712	15,6077
33	900	1800	2979	6001	1,3712	15,6077
33	900	1900	3144	6335	1,3712	15,6077
33	900	2000	3310	6668	1,3712	15,6077
33	900	2100	3475	7001	1,3712	15,6077
33	900	2200	3641	7335	1,3712	15,6077
33	900	2300	3806	7668	1,3712	15,6077
33	900	2400	3972	8002	1,3712	15,6077
33	900	2500	4137	8335	1,3712	15,6077
33	900	2600	4303	8668	1,3712	15,6077
33	900	2700	4468	9002	1,3712	15,6077
33	900	2800	4634	9335	1,3712	15,6077
33	900	2900	4799	9669	1,3712	15,6077
33	900	3000	4965	10002	1,3712	15,6077

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

.....



.....
(place and date of issue)

.....