

TECHNICAL DATA SHEET



PRODUCT NAME

blackbolt® Release Agent

PRODUCT NUMBER

3356985119

PRODUCT DESCRIPTION

The product operates anti-statically and is used in countless working operations in industry. Prevents sticking of almost all kinds of sizing agents and resins. Release Agent for all forms of wood processing machinery, sawmills etc., where silicone products are undesirable.

PROPERTIES

For the timber industry
Silicone-free, anti-statically and friction-reducing
Prevents rust and corrosion
Prevents adhesion

DIRECTIONS FOR USE

Shake the container and spray directly on to the article.

MARKINGS/SAFETY

Flammable aerosol. Pressurised container: May burst if heated. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. **Keep out of reach of children.**



Warning!

| | |
|------------|----------------|
| PR number | - |
| Net | 355 g. |
| Volumen | 500 ml. |
| Propellant | Carbon dioxide |

| | |
|------------|--|
| Shelf life | Three years from date of manufacture. The product can be used for up to six years after the date of production, provided there is sufficient spray pressure to allow it to be applied to the surface in a satisfactory manner. |
|------------|--|