

SIMATIC ET 200SP, TM PULSE 2X24V PWM AND PULSE
OUTPUT 2 CHANNELS 2 A FOR VALVES AND DC MOTORS



General information	
Product type designation	TM Pulse 2x24 V
Firmware version	V1.0
FW update possible	Yes
usable BaseUnits	BU type B1
Color code for module-specific color identification plate	CC40
Product function	
I&M data	Yes; I&M 0
Isochronous mode	Yes
Engineering with	
STEP 7 TIA Portal configurable/integrated as of version	V13 SP1
STEP 7 configurable/integrated as of version	V5.5 SP4 and higher
PROFIBUS as of GSD version/GSD revision	GSD Revision 5
PROFINET as of GSD version/GSD revision	GSDML V2.31
Supply voltage	
Load voltage L+	

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes; against destruction

Input current

Current consumption, max.	70 mA; without load
---------------------------	---------------------

Encoder supply

Number of outputs	2; A common 24V encoder supply for both channels
-------------------	--

24 V encoder supply

• 24 V	Yes; L+ (-0.8 V)
• Short-circuit protection	Yes; per module, electronic
• Output current, max.	300 mA

Power loss

Power loss, typ.	1.7 W
------------------	-------

Address area

Occupied address area

• Inputs	16 byte; 8 per channel
• Outputs	24 byte; 12 per channel

Digital inputs

Number of digital inputs	2; 1 per channel
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes

Digital input functions, parameterizable

• Freely usable digital input	Yes
• HW enable for digital output	Yes

Input voltage

• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V
• permissible voltage at input, min.	-30 V
• permissible voltage at input, max.	30 V

Input current

• for signal "1", typ.	2.5 mA
------------------------	--------

Input delay (for rated value of input voltage)

for standard inputs

— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	4 µs; for parameterization "none"

— at "1" to "0", min.

4 µs; for parameterization "none"

Digital outputs

Type of digital output	P- and M-switching
Number of digital outputs	2; 1 per channel
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	6.8 A with Standard output, 2 A with High Speed output
Limitation of inductive shutdown voltage to	-0.8 V
Controlling a digital input	Yes
Accuracy of pulse duration	±100 ppm ±0.5 µs with High Speed output, ±100 ppm ±9 µs with Standard output
minimum pulse duration	1.5 µs; With High Speed output, 10 µs with Standard output

Digital output functions, parameterizable

- | | |
|--------------------------------------|--|
| • Freely usable digital output | Yes |
| • PWM output | Yes |
| — Number, max. | 2; 1 per channel |
| — Cycle duration, parameterizable | Yes; Max. 85 s |
| — ON period, min. | 0 % |
| — ON period, max. | 100 % |
| — Resolution of the duty cycle | 0.0036 %; For S7 analog format, min. 20 ns |
| • Connection of a proportional valve | Yes |
| • Dithering | Yes |
| — Frequency adjustable | Yes |
| — Amplitude adjustable | Yes |
| • Current measurement | Yes |
| • Current control | Yes |
| • Connection of a DC motor | Yes |
| • ON-delay | Yes |
| • OFF-delay | Yes |
| • Frequency output | Yes |
| • Pulse train | Yes |
| • Pulse output | Yes |

Switching capacity of the outputs

- | | |
|-----------------------------|----------------------------------|
| • with resistive load, max. | 2 A |
| • on lamp load, max. | 10 W; 1 W with High Speed output |

Load resistance range

- | | |
|---------------|--------------------------------------|
| • lower limit | 12 Ω; 240 ohm with High Speed output |
| • upper limit | 12 kΩ |

Output voltage

- | | |
|--------------------------|----|
| • Type of output voltage | DC |
|--------------------------|----|

• for signal "0", max.	1 V
• for signal "1", min.	23.2 V; L+ (-0.8 V)
Output current	
• for signal "1" rated value	2 A; 0.1 A with High Speed output, observe derating
Output delay with resistive load	
• "0" to "1", typ.	0 µs; With High Speed output, 4.5 µs with Standard output
• "0" to "1", max.	0.8 µs; With High Speed output, 9 µs with Standard output
• "1" to "0", typ.	0 µs; With High Speed output, 4.5 µs with Standard output
• "1" to "0", max.	0.8 µs; With High Speed output, 9 µs with Standard output
Parallel switching of two outputs	
• for uprating	Yes
Switching frequency	
• with resistive load, max.	100 kHz; With High Speed output, 10 kHz with standard output
• with inductive load, max.	100 kHz; With High Speed output, 10 kHz with standard output
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per channel, max.	2 A
• Current per group, max.	4 A
• Current per module, max.	4 A
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Bus cycle time (TDP), min.	250 µs; with 1 channel configuration, 375 µs with 2 channel configuration
Jitter, max.	1 µs; typically ±
Interrupts/diagnostics/status information	
Diagnostics	Yes
Substitute values connectable	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes

Permissible potential difference	
between different circuits	75 V DC/60 V AC (base isolation)
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, max.	60 °C; Observe derating
• vertical installation, max.	50 °C; Observe derating
Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	20 mm
Weights	
Weight, approx.	50 g
last modified:	22.01.2016