

# SIEMENS

## Product data sheet

**6GK1905-0CB00**

|                                                                      |  |                                                                                                                   |
|----------------------------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------|
| [nicht versorgt: PMD_ABS675_001_000]                                 |  | PROFIBUS ECOFAST HYBRID PLUG 180,(ECOFAST CU),<br>2 X CU;<br>4 X 1.5SQMM CU SOCKET CONNECTOR HANBRID<br>PACK OF 5 |
| •                                                                    |  | 9.6 kbit/s ... 12 Mbit/s                                                                                          |
| <b>Interfaces</b>                                                    |  |                                                                                                                   |
| Number of electrical connections                                     |  |                                                                                                                   |
| •                                                                    |  | 1                                                                                                                 |
| • for network components and terminal equipment                      |  | 1                                                                                                                 |
| Design of the electrical connection / [nicht versorgt - FastConnect] |  | No                                                                                                                |
| <b>Mechanical data</b>                                               |  |                                                                                                                   |
| material / of the housing                                            |  | plastic                                                                                                           |
| <b>Design, dimensions and weight</b>                                 |  |                                                                                                                   |
| Width                                                                |  | 27 mm                                                                                                             |
| Height                                                               |  | 27 mm                                                                                                             |
| Depth                                                                |  | 71 mm                                                                                                             |
| Net weight                                                           |  | 40 g                                                                                                              |
| <b>Permitted ambient conditions</b>                                  |  |                                                                                                                   |
| Ambient temperature                                                  |  |                                                                                                                   |
| • during operating                                                   |  | -20 °C ... 70 °C                                                                                                  |
| • during storage                                                     |  | -40 °C ... 80 °C                                                                                                  |
| • during transport                                                   |  | -40 °C ... 80 °C                                                                                                  |
| <b>Product properties, functions, components / general</b>           |  |                                                                                                                   |
| Product feature / [not supplied - silicon-free]                      |  | Yes                                                                                                               |
| Composant produit                                                    |  |                                                                                                                   |
| • décharge de traction                                               |  | Yes                                                                                                               |
| <b>Standards, specifications, approvals</b>                          |  |                                                                                                                   |
| Verification of suitability                                          |  |                                                                                                                   |

- RoHS conformity
- UL-registration

Yes

No

**letzte Änderung:**

Nov 21, 2011