



A technical line drawing of a cable assembly. The cable is long and flexible, forming a large loop. At each end, there is a connector. The connector on the left is a standard ST connector with a threaded body and a small pin. The connector on the right is a more complex, multi-segmented assembly. A dashed line indicates a connection point between the two connectors, with an arrow pointing to the label 'ST CONNECTOR' at the bottom.

1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. CONSTRUCTED WITH 9/125 MICRON SINGLEMODE CABLE AND A ZIRCONIA SPLIT SLEEVE.
3. EXTRA SPLIT SLEEVES ARE PROVIDED AS REPLACEMENTS.
4. PATCHCORD LENGTH IS 20.3 cm [ 8" ].
5. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTIONS OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

INTERFACE  
FOR CONNECTION TO PRE-POLISHED  
CONNECTOR WITH 2.50mm FERRULE

ST CONNECTOR  
FOR CONNECTION TO V.F.L. UNIT

