

TECHNICAL DATA SHEET



PRODUCT NAME

blackbolt® NSF H1 Silicone spray

PRODUCT NUMBER

3356985015

PRODUCT DESCRIPTION

Siliconespray is foodstuffs-approved under NSF H1. It operates anti-statically and is used as a slip agent and lubricant with countless functions in the food industry. Used as a lubricant on conveyor belts, skids, pipes, cable runs, etc. Withstands high temperatures and has good properties of resistance to being washed away by water. May also be used as a lubricant for offset, folding and cutting machines. Softens rubber mouldings and prevents frost adhesion. The products acts well in connection with HACCP and GMP approval.

PROPERTIES

NSF H1 Foodstuffs approved

Slip agent and lubricant

For assembly of PVC pipes, cable runs etc.

DIRECTIONS FOR USE

Shake the container and spray directly on to the article. May be used where contact with foodstuffs may occur.

Operating temperature range -50° C to +200° C.

MARKINGS/SAFETY

Extremely flammable aerosol. Pressurised container: May burst if heated. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F. **Keep out of reach of children.**



Danger!

PR number	2114571
Net	355 g.
Volumen	500 ml.
Propellant	Carbon dioxide

Shelf life	Three years from date of manufacture. The product can be used for up to six years after the date of production, provided there is sufficient spray pressure to allow it to be applied to the surface in a satisfactory manner.
------------	--