



PVL350



PVL130S



PVL130P



PVL130L

HYDRAULIC PRESS PISTOL

Offers the new and easy way to do battery powered crimping of small and medium size terminals within the Elpress system.

Suppliers article No EK354ML- PVL350
 EK50ML - PVL130S
 EK1550ML - PVL130P

Technical information

Weight 1,62 kg incl battery PVL350
 1,02 kg incl battery PVL130S
 1,56 kg incl battery PVL130P+PVL130L

Crimp force min 35 kN PVL350 + 15 kN PVL130S + 13 kN PVL130P+L
 Crimps/charge 85 (PV350) or 150(PV130x) depending on size and temperature

Crimp time 3-4 s(PVL350) + <1,5 s (PVL130S) + 2-4 s (PVL130P+L)
 depending on size

Ambient temperature -10° C - +40° C

Hydraulic oil Hydrex MV22 or similar

Article No

Battery PVBP-LION MINI	8010-058600	DeWalt article No DCB127, 2 Ah, 10,8VDC
Charger PVBC-LION MINI	8010-058700	DeWalt article No DCB115, 10.8V Charging time approx 40 min
Plastic case PVL130,350L	8064-002200	Suppliers article No KKMLELP
Plastic case PVL130S	8064-002100	Suppliers article No KKEK50MLGLDSA

Operating range

PVL350 Cu 4-95 mm² Connectors
 Cu 6-10 mm² C-sleeves
 Cu 6-16 mm² CUT-connectors

PVL130S+PVL130P Cu 0,5-6 mm² Pre-insulated connector
 Cu 0,25-2,5 mm² Un-insulated indent crimp
 Cu 4-10 mm² Un-insulated W-crimp
 Cu 0,5-6 mm² Un-insulated roll-crimp
 Cu 0,5-50 mm² End ferrules

PVL130L Cu Ø5+Ø7 mm Transformer tap changer