

Data sheet

6GK5798-2PP00-2AA6

Product type designation

IWLAN panel feedthrough N-Connect/N-Connect Female/Female
N-Connect Female/female Panel feedthrough, cabinet bushing, 2.4 GHz and 5 GHz for Wall thickness max. 4.5 mm



Electrical data	
Number of electrical connections	2
Type of electrical connection	N-Connect female/N-Connect female
Transmission frequency	0 ... 11 GHz
Impedance	50 Ω
Ambient conditions	
Ambient temperature	
• during operation	-30 ... +100 °C
• during storage	-30 ... +100 °C
• during transport	-30 ... +100 °C
Protection class IP	IP68
Design, dimensions and weights	
Diameter	20.7 mm
Length	38 mm
Net weight	55 g
Standards, specifications, approvals	
Certificate of suitability	

- RoHS conformity

Yes

Further information / Internet-Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAX Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/snst>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

12/17/2019