

Product name IQ Welding Hose Oxygen Blue

Description Lining: SBR/EPDM, black

Reinforcement : PVA Cover : EPDM, blue

Lengths  $\overline{50 \text{ MT}}$ 

Application Lightweight, flexible, smooth, blue hose for oxygen, to EN559

and ISO 3821. For use with industrial autogenic welding equipment, usually together with red acetylene hose. Also

ideal for natural gas and air.

Temperature -30°C til 80°C,



Nominal	Inner	Outer		A 23° C		T		
Diameter	Diameter	diameter	Working- pressure	Burst- Presure	Bending radius	Length	Wall thickness	Weight/meter
mm	"	mm	Bar	Bar	mm	mt	mm	g/m
5,0	-	12,0	20	60	50	50	7,0	115
6,3	1/4"	13,3	20	60	63	50	7,0	146
8,0	-	14,6	20	60	80	50	6,6	172
10,0	-	17,0	20	60	100	50	7,0	203
12,5	1/2"	19,4	20	60	125	50	6,9	257
20,0	3/4"	28,5	20	60	200	50	8,5	399
25,0	1"	35,0	20	60	220	50	10,0	480
32,0	1 1/4"	44,0	10	20	175	50	12,0	775
51,0	2"	65,0	10	20	420	50	14,0	1880

Tolerance on weight: ± 5%

**Tolerance on other data:** according to ISO 1307

Firma.MTDK
------------